

NetApp® OnCommand™ Installation and Setup Guide For Use with Core Package 5.0 and Host Package 1.0

NetApp, Inc.
495 East Java Drive
Sunnyvale, CA 94089 U.S.A.
Telephone: +1 (408) 822-6000
Fax: +1 (408) 822-4501
Support telephone: +1 (888) 4-NETAPP
Documentation comments: doccomments@netapp.com
Information Web: <http://www.netapp.com>

Part number: 215-05164_A0
August 2011

Contents

Overview of OnCommand manageability software components	9
Core Package and Host Package installation and configuration checklists	9
OnCommand installation scenarios	10
OnCommand architecture	11
What a host service is	12
Contents of the OnCommand Core Package	14
Components installed with the OnCommand Core Package	14
Functionality available with the OnCommand Core Package	14
Contents of the OnCommand Host Package	16
Components installed with the OnCommand Host Package in a VMware environment	16
Functionality available with the OnCommand Host Package in a VMware environment	17
Components installed with the OnCommand Host Package in a Hyper-V environment	17
Functionality available with the OnCommand Host Package in a Hyper- V environment	18
Comparison of OnCommand Standard and Express editions	19
Comparison of Standard and Express edition functionality	20
System requirements	23
Browser requirements	23
Accessing the OnCommand console on a Linux-based PC	24
License requirements	25
Network storage requirements for database files	25
OnCommand Core Package hardware and software requirements	26
Software required prior to installing the OnCommand Core Package	26
Software required for some environments	26
Windows Server 2008 with 1 to 25 storage systems	27
Windows Server 2008 with 25 or more storage systems	28
Windows Server 2003 with 1 to 25 storage systems	29
Windows Server 2003 with 25 or more storage systems	29
Linux workstation or server with 1 to 25 storage systems	30

Linux workstation or server with 25 or more storage systems	31
Required ports for the Core Package	32
OnCommand Host Package hardware and software requirements	33
Hardware requirements	34
Operating system requirements for VMware environments	34
Software required prior to installing the OnCommand Host Package for VMware environments	35
Operating system requirements for Hyper-V environments	36
Software required prior to installing the OnCommand Host Package for Hyper-V environments	37
Required ports for the Host Package	38
Installing the OnCommand Core Package	41
Downloading the OnCommand Core Package	41
Installing the OnCommand Core Package on Windows	42
Installing the OnCommand Core Package on Linux	44
Installing the OnCommand Core Package with a script	45
Scripted install options for the OnCommand Core Package on Windows ...	46
Scripted install options for the OnCommand Core Package on Linux	47
Setting up Web security after restoring a database on a new OnCommand Core Package installation	48
Installing NetApp Management Console	49
Installing or upgrading OnCommand Windows PowerShell cmdlets	50
Installing the OnCommand Host Package	51
Downloading the OnCommand Host Package	51
Installing the OnCommand Host Package in a VMware environment	52
Installing the OnCommand Host Package in a Hyper-V environment	55
Installing the OnCommand Host Package with a script	57
Scripted install options for the OnCommand Host Package in a VMware environment	58
Scripted install options for the OnCommand Host Package in a Hyper-V environment	59
Setting up your system	61
Configuring the OnCommand Express edition server	61
Configuring the OnCommand Standard edition server with host services	65
Verifying that a host service is registered with the DataFabric Manager server	66

Authorizing a host service to access storage system credentials	68
Associating a host service with the vCenter Server	69
Verifying communication between the host service and the OnCommand plug-in	72
Associating storage systems with a host service	73
Editing storage system login and NDMP credentials from the Host Services tab	75
Registering the OnCommand Plug-in for VMware with a vCenter Server	77
How to manually transition SnapManager for Hyper-V dataset information	79
Determining whether a storage system belongs to a workgroup or a domain	79
Updating the SnapDrive for Windows service account	80
Adding port exceptions to Windows Firewall	80
Regenerating an SSL certificate for the OnCommand Host Package	81
Using a certificate signed by a certificate authority	81
Certificate-based authentication	83
Certificate information	83
Managing certificates for cloud service clients	83
Generating a key and self-signed certificate	84
Adding a certificate in the truststore	84
Removing a certificate from the truststore	84
Displaying a list of certificates in a truststore	84
Displaying details about certificates in a truststore	85
Showing the contents of the DataFabric Manager server key and certificate file	85
Displaying DataFabric Manager server certificate details	86
Disabling certificate-based authentication	86
Managing certificates for host services clients	86
Authorizing a host service certificate	87
Migrating certificates, keys, and truststores manually	87
Upgrading to the OnCommand Core and Host Packages	89
Upgrading to the OnCommand Core Package on Windows	89
Upgrading to the OnCommand Core Package on Linux	90
Upgrading to the OnCommand Host Package in a VMware environment	91
Upgrading to the OnCommand Host Package in a Hyper-V environment	94
Upgrade issues with DataFabric Manager 3.8 or earlier	97
Uninstalling the OnCommand Core and Host Packages	101

Uninstalling the OnCommand Core Package on Windows	101
Uninstalling the OnCommand Core Package on Linux	102
Uninstalling the OnCommand Host Package in a VMware environment	102
Uninstalling the OnCommand Host Package in a Hyper-V environment	103
Troubleshooting OnCommand installation and setup	105
Address already in use	105
There is a problem with this Windows Installer package	105
Cursor displays in multiple locations in the same dashboard panel	105
Plug-in container for Firefox has stopped working	106
No related objects are displayed for a virtual object	106
Could not find any storage mapping for virtual object	107
Storage mapping fails for virtual machine and datastore created on VMFS datastore using FC LUN	107
Operation timed out	108
Primary key for table is not unique	108
NetApp icon does not appear in the vSphere Client	108
Access is denied	109
Error 1067 while starting webui service	109
Verifying host service to DataFabric Manager server communication	109
Administrators usergroup does not exist on <vFiler name>	110
Host service fails to connect to DataFabric Manager server after a restart	110
Host service is unresponsive after successful installation of OnCommand Host Package	110
Installing and configuring the OnCommand Core Package in an MSCS environment	113
Preparing to install the OnCommand Core Package in an MSCS environment	113
Prerequisites for installing the OnCommand Core Package in MSCS	113
Configuration requirements for the OnCommand Core Package in MSCS	114
Configuration limitations for the OnCommand Core Package in MSCS ...	114
Installing the OnCommand Core Package in an MSCS environment	115
Configuring MSCS to install the OnCommand Core Package	115
Installing the OnCommand Core Package in MSCS	116
Example of MSCS initial setup	118
DataFabric Manager server service resources added to MSCS	118
Configuring the OnCommand Core Package in an MSCS environment	119

Adding the cluster services using a script	120
Script options for configuring services in MSCS	121
Bringing DataFabric Manager server cluster services online in MSCS	121
Configuring DataFabric Manager server to use the cluster name in MSCS	121
Configuring DataFabric Manager server in MSCS manually	122
Configuring a host service in MSCS	127
Managing DataFabric Manager server in an MSCS environment	128
Best practices to start and stop DataFabric Manager server services in MSCS	128
Restoring the DataFabric Manager server database in MSCS	128
Configuring DataFabric Manager server to use HTTPS in MSCS	129
DataFabric Manager server monitoring in MSCS	131
Data shared by MSCS cluster nodes	131
Data that is not shared by MSCS cluster nodes	132
Uninstalling the OnCommand Core Package in an MSCS environment	133
Upgrading the OnCommand Core Package in an MSCS environment	133
Installing and configuring the OnCommand Core Package in a VCS environment	137
Preparing to install the OnCommand Core Package in a VCS environment	137
Prerequisites for installing the OnCommand Core Package in VCS	137
Configuration requirements for the OnCommand Core Package in VCS ..	138
Configuration limitations for the OnCommand Core Package in VCS	138
Installing the OnCommand Core Package in a VCS environment	139
Configuring VCS to install the OnCommand Core Package	139
Installing the OnCommand Core Package in VCS	139
DataFabric Manager server service resources added to VCS	141
Configuring the OnCommand Core Package in a VCS environment	141
Configuring DataFabric Manager server on the first node in VCS	142
Configuring DataFabric Manager server on the second node in VCS	142
Adding the cluster services using a script	143
Script options for configuring services in VCS	144
Bringing DataFabric Manager server cluster services online in VCS	144
Configuring DataFabric Manager server in VCS manually	145
Configuring a host services in VCS	147
Managing the DataFabric Manager server in a VCS environment	147

Best practices to start and stop DataFabric Manager server services in VCS	147
Restoring the DataFabric Manager server database in VCS	148
Configuring the DataFabric Manager server to use HTTPS in VCS	148
Data shared by VCS cluster nodes	150
Data that is not shared by VCS cluster nodes	151
Uninstalling the OnCommand Core Package in a VCS environment	152
Upgrading the OnCommand Core Package in a VCS environment	152
Copyright information	155
Trademark information	157
How to send your comments	159
Index	161

Overview of OnCommand manageability software components

The OnCommand suite is composed of two installation packages. The OnCommand Core Package provides backup and restore capabilities, monitoring, and provisioning for a physical storage environment. It also provides basic support for virtual storage environments. If you need to discover your virtual environment and want to take advantage of the full range of management and monitoring capabilities for virtual storage environments, you must install the OnCommand Host Package.

Core Package and Host Package installation and configuration checklists

It is helpful to use checklists to verify that you have completed each task in the installation and configuration process, including reviewing system requirements; downloading and installing a variety of software; and, if your environment includes virtual objects, configuring the host service.

Plan for, download, and install the software

This checklist provides an overview of the installation process for OnCommand Core Package and OnCommand Host Package. The OnCommand Host Package software is required only for a virtual environment. If you are installing in a purely physical environment and are not managing VMware or Hyper-V virtual objects, you need not install the Host Package software or configure the host service.

1. [Review the system requirements](#) on page 23.
 - Browser requirements
 - License requirements
 - Network storage requirements
 - Core Package hardware and software requirements
 - Host Package hardware and software requirements
Required if installing in a virtual environment.
2. [Download the OnCommand Core Package software](#) on page 41.
3. [Optional: Download the OnCommand Host Package software](#) on page 51.
Required if installing in a virtual environment.
4. Optional: [Download the Host Agent software](#) on page 26.
5. Optional: [Download the Open Systems SnapVault software](#) on page 26.
6. Install the Core Package software: [Windows](#) on page 42 , [Linux](#) on page 44 , or [by script](#) on page 45.

7. Install the Host Package software: *VMware* on page 52 , *Hyper-V* on page 55 , or *by script* on page 57.
Required if installing in a virtual environment.
8. Optional: *Install the Host Agent software* on page 26.
9. Optional: *Install the Open Systems SnapVault software* on page 26.
10. Configure the host service: *Standard installation* on page 65 or *Express installation* on page 61

Configure the host service

If you selected the Express edition during the Core Package installation, you can use the Express Configuration wizard to configure your software. The wizard can be accessed from the Administration menu in the OnCommand console. After completing the wizard, you can use the following checklist to verify the results.

If you selected the Standard edition during the OnCommand Core Package installation, use this checklist to verify that you have completed all of the configuration tasks.

1. *Verify that the host service is registered with the DataFabric Manager server* on page 66.
2. *Authorize the host service to access storage system credentials.* on page 68
3. *Associate the host service with the vCenter Server* on page 69.
4. *Verify that the host service is communicating with the VMware or Hyper-V plug-in* on page 72.
5. *Associate storage systems with the host service* on page 73.
6. *Verify that storage system credentials are valid* on page 75.
7. Optional: *Install NetApp Management Console* on page 49.
8. Optional: *Install the OnCommand Windows PowerShell cmdlets* on page 50.

When the configuration tasks are complete, you can create backup jobs from the Datasets tab.

OnCommand installation scenarios

Depending on your storage environment, you must choose among installing the OnCommand Core Package, the OnCommand Host Package, or both packages.

There are four basic installation environments:

- If your storage environment includes physical storage objects, you should download and install Core Package software and also the Host Package software to only monitor virtual objects.
- If you have a VMware environment and want to manage both physical and virtual objects, then you must install both Core and Host Packages.

- If you have a Microsoft Hyper-V storage environment and want to manage both physical and virtual objects, you must install both Core and Host Packages.
- If you are managing only virtual objects and do not require the Backup and Recovery capability, you can install only Host Package software.

If you are installing both Core and Host Packages, you should install Core Package software prior to installing Host Package software. If you install Host Package software first, you must start the Configuration wizard after you finish installing Core Package software unless you already have an earlier version of DataFabric Manager server in your environment.

You can install Core Package software and Host Package software on either a 32-bit or 64-bit Microsoft Windows system and you also can install Core Package software on a 32-bit or 64-bit Linux system. Your Windows and Linux hosts must meet minimum hardware requirements before you can install either the Core Package or the Host Package. The hardware requirements vary depending on the operating system being used and the number of nodes in the environment.

Related concepts

[Installing the OnCommand Core Package](#) on page 41

[OnCommand Core Package hardware and software requirements](#) on page 26

[Installing the OnCommand Host Package](#) on page 51


[OnCommand Host Package hardware and software requirements](#) on page 33

OnCommand architecture

OnCommand Core and Host Packages include interaction among front-end user interfaces (such as the OnCommand console, the NetApp Management Console, the Operations Manager console, and the OnCommand Plug-in for VMware) and back-end servers or services (such as the DataFabric Manager server, host services, Hyper-V and VMware plug-ins, SnapDrive for Windows, and storage systems).

The OnCommand console provides GUI management for Hyper-V objects and an alternative GUI for VMware objects. You can launch the Operations Manager console and the NetApp Management Console to manage your physical environment.

The OnCommand Plug-in for VMware is a plug-in to the vCenter Server that provides management of VMware virtual objects.



Related concepts

[Contents of the OnCommand Core Package](#) on page 14

[Contents of the OnCommand Host Package](#) on page 16

[Comparison of OnCommand Standard and Express editions](#) on page 19

[What a host service is](#) on page 12

What a host service is

The host service is software that runs on a physical machine, a Hyper-V parent, or in a virtual machine. The host service software includes plug-ins that enable the DataFabric Manager server to discover, back up, and restore virtual objects, such as virtual machines and datastores. The host service also enables you to view virtual objects in the OnCommand console.

When you make changes to the virtual infrastructure, automatic notification is sent from the host service to the DataFabric Manager server. You can manually start a rediscovery job to see your changes. You might need to refresh the host service information to see the updates in the OnCommand console.

The host service is included as part of the installation of the OnCommand Host Package. You can install multiple host services on multiple vCenter Servers, virtual machines, or Hyper-V parents.

You must register at least one host service with the DataFabric Manager server and associate a host service with the virtual infrastructure (VMware or Hyper-V) before you can back up or restore data. Registration can be done during the installation process or after installation, from the Host Services tab accessible from the Administration menu in the OnCommand console. After registration, you can monitor and manage host services from the Host Services tab.

The host service notifies the DataFabric Manager server regarding the progress of operations. If the DataFabric Manager server goes down, the host service caches messages and pushes the messages to

the server as soon as the server is available. The DataFabric Manager server reviews the messages and if any operations are incomplete or have failed, the server might restart these operations.

In addition, if the DataFabric Manager server is unavailable, you can still perform backup and restore operations from the host service by using the OnCommand PowerShell cmdlets.

Guidelines for managing host services

Following are some guidelines to consider when managing host services.

- Messages from host services are stored persistently in the DataFabric Manager server database `hsNotifications` table. This table continues to grow over time and can quickly become huge in a large environment. You can use the following global options to manage the size of this table:
 - `hsNotificationsMaxCount`
 - `hsNotificationsPurgingInterval`
- If the Hyper-V parent is part of a cluster, you must install the OnCommand Host Package on each node of the cluster and all the cluster nodes must have the same TCP/IP port number to enable communication between host services on different nodes. You must register and authorize each node with the same DataFabric Manager server.
- When you register a host service with the DataFabric Manager server, you can type the fully qualified domain name (FQDN) or IP address in the IPv4 format.
- If you change the certificate on a host service or uninstall a host service and then reinstall it, you must unregister the host service from DataFabric Manager server using the `-f` flag. See the `unregister` man page for more information.
- In a Hyper-V cluster only, if you manually shut down a host service on the node that is designated as the owner of a cluster and the node is active, the host service on both the cluster and the node become inactive.
- The OnCommand Host Package upgrade does not force host services to reregister with DataFabric Manager server. Therefore, if you unregister a host service from DataFabric Manager server prior to an OnCommand Host Package upgrade, you must manually register the host service to DataFabric Manager server after the upgrade is finished.

Related tasks

[Installing the OnCommand Host Package in a VMware environment](#) on page 52

[Installing the OnCommand Host Package in a Hyper-V environment](#) on page 55

Contents of the OnCommand Core Package

Understanding what components compose the OnCommand Core Package and what these components enable you to do helps you determine which components you want to enable during the installation and setup process.

Related concepts

[Comparison of OnCommand Standard and Express editions](#) on page 19

Components installed with the OnCommand Core Package

Understanding the different components of the OnCommand Core Package helps you determine which components you want to enable during the installation and setup process.

The following components are installed on your system:

DataFabric Manager server	Enabled by default.
DataFabric Manager server services	Enabled by default.
NetApp Management Console with protection, provisioning, and Performance Advisor capabilities	Bundled with the Core Package but must be installed separately.
OnCommand Windows PowerShell cmdlets	Downloaded with the Core Package but must be installed separately. Perform local backup and restore operations of virtual objects, as well as mount and unmount operations, using the Windows PowerShell interface.

Related tasks

[Downloading the OnCommand Core Package](#) on page 41

[Installing the OnCommand Core Package on Windows](#) on page 42

[Installing the OnCommand Core Package on Linux](#) on page 44

Functionality available with the OnCommand Core Package

You can manage physical storage objects on primary and secondary storage after installing OnCommand Core Package software. The Core Package also provides basic monitoring of virtual objects if Host Package software has been installed because the Host Package contains hypervisor plug-ins that perform virtual object discovery.

The Core Package includes the OnCommand graphical user interface (GUI) console from which you can access storage management functionality that was previously accessible through separate NetApp software products. OnCommand delivers access to this functionality through three GUI consoles.

OnCommand console

- View a set of dashboard panels that provide high-level status of physical and virtual objects and support drill-down capabilities.
- Create and edit datasets for protecting virtual objects.
- Initiate back up and recovery of virtual objects, which is executed by the host service plug-ins.
- Provide launch points to other capabilities in the Core Package.
- Export, share, schedule, sort, filter, hide and print data in the reports for physical objects.

Operations Manager console

- Manage users and roles.
- Monitor clusters, storage controllers, and vFiler units.
- Monitor physical objects for performance issues and failures.
- Manage storage systems and vFiler units.
- Schedule and manage scripts.
- Track storage usage and available capacity.

NetApp Management Console

- Provision physical resources.
- Back up and restore physical objects.
- Manage space on secondary storage.
- Provide disaster recovery for physical objects (automated failover and manual failback).
- Monitor performance.
- View dashboards for physical objects.
- Create and edit storage services.

PowerShell Cmdlets for OnCommand

- Manage OnCommand protection-related capabilities through the command-line interface.

Related tasks

[Downloading the OnCommand Core Package](#) on page 41

[Installing the OnCommand Core Package on Windows](#) on page 42

[Installing the OnCommand Core Package on Linux](#) on page 44

Contents of the OnCommand Host Package

Understanding what components compose the OnCommand Host Package and what these components enable you to do helps you determine which components you want to enable during the installation and setup process.

Related concepts

[What a host service is](#) on page 12

Components installed with the OnCommand Host Package in a VMware environment

Understanding the different components of the OnCommand Host Package in a VMware environment helps you prepare for installing the Host Package on your system.

The following components are installed on your system:

OnCommand Plug-in for VMware	A client application used to centrally manage your virtual infrastructure from the vSphere Client. The OnCommand Plug-in for VMware includes the Monitoring and Host Configuration, Provisioning and Cloning, and Backup and Recovery capabilities. It also includes the Legacy Backup and Recovery capability, which enables you to recover data from backups created before the introduction of OnCommand management software.
OnCommand host service VMware plug-in	A plug-in that receives and processes events in a VMware environment, including discovering, restoring, and backing up virtual objects such as virtual machines or datastores. This plug-in executes the events received from the host service.
Host service	Software that enables the DataFabric Manager server to forward requests, such as the request for a restore operation, to the appropriate plug-in and to send the final results of the specified job to that plug-in.
Host service Windows PowerShell cmdlets	Cmdlets that perform virtual object discovery, local restore operations, and host configuration when the DataFabric Manager server is unavailable.

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

[Installing the OnCommand Host Package in a VMware environment](#) on page 52

Functionality available with the OnCommand Host Package in a VMware environment

You can discover and manage virtual objects after installing OnCommand Host Package software. There are two separate GUIs from which you can manage virtual environments.

OnCommand console

- Create a dataset and then add virtual machines or datastores to the dataset for data protection.
- Assign local protection and optionally remote protection policies to the dataset.
- View storage details/space details for a virtual object.
- Perform an on-demand backup of a dataset.
- Mount existing backups onto an ESX Server to support tasks such as backup verification, single file restore, and restoration of a virtual machine to an alternate location.
- Restore data from local and remote backups as well as restoring data from backups made before the introduction of OnCommand management software.
- View storage details and space details for a virtual object.

OnCommand Plug-in for VMware

- Manage NetApp functionality using the vSphere Client.
- View virtual-to-storage mapping.
- View storage utilization reporting.
- Provision and resize datastores.
- Clone virtual servers and desktops.
- Perform an on-demand backup of a dataset.
- Run scheduled local and remote backups.
- Mount existing backups onto an ESX Server to support tasks such as backup verification, single file restore, and restoration of a virtual machine to an alternate location.

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

[Installing the OnCommand Host Package in a VMware environment](#) on page 52

Components installed with the OnCommand Host Package in a Hyper-V environment

Understanding the different components of the OnCommand Host Package in a Hyper-V environment helps you prepare for installing the Host Package on your system.

The following components are installed on your system:

SnapDrive for Windows	Software used in the Hyper-V environment for storage discovery and to manage LUNs or Snapshot copies.
OnCommand host service Hyper-V plug-in	A plug-in that receives and processes events in a Hyper-V environment, including discovering, restoring, and backing up virtual objects such as virtual machines. This plug-in executes the events received from the host service.
Host service	Software that enables the DataFabric Manager server to forward requests, such as the request for a restore operation, to the appropriate plug-in and to send the final results of the specified job to that plug-in.
Host service Windows PowerShell cmdlets	Cmdlets that perform virtual object discovery, local restore operations, and host configuration when the DataFabric Manager server is unavailable.

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

[Installing the OnCommand Host Package in a Hyper-V environment](#) on page 55

Functionality available with the OnCommand Host Package in a Hyper-V environment

You can discover and manage virtual objects after installing OnCommand Host Package software.

OnCommand console	<ul style="list-style-type: none"> • View and monitor your inventory of Hyper-V servers. • Create a dataset and then add virtual machines to the dataset for data protection. • Assign local protection and optionally remote protection policies to the dataset. • Perform an on-demand backup of a dataset. • Run scheduled and local and remote backups. • Restore a virtual machine from a backup to its original location. • Restore a virtual machine from local and remote backups. • Enables backups of virtual machines in cluster shared volumes. • Enables restore of virtual machines in cluster shared volumes. • View storage details for a virtual object.
--------------------------	---

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

[Installing the OnCommand Host Package in a Hyper-V environment](#) on page 55

Comparison of OnCommand Standard and Express editions

During an initial OnCommand Core Package installation, you can choose to install either the Standard edition or the Express edition of the DataFabric Manager server, depending on your deployment requirements.

The DataFabric Manager server is included as part of the OnCommand Core Package installation and provides infrastructure services such as discovery, monitoring, role-based access control (RBAC), auditing, and logging. If you are upgrading from a previous version of the DataFabric Manager server, the OnCommand Standard edition is automatically selected.

Express edition

The OnCommand Express edition is intended for smaller environments of no more than four storage systems and no more than one vCenter Server, Hyper-V Server, or Hyper-V cluster.

Because of the reduced software footprint, the Express edition can be installed on a shared system. If you are also installing the OnCommand Host Package for your virtualized environment, you can install the Core and Host packages on the same system. After installation is successfully completed, you can use the Express edition configuration wizard to set up the services installed on your system. The wizard simplifies configuration by automating aspects of the configuration process.

The Express edition has the same level of data protection capability as the Standard edition, but with reduced monitoring capabilities for storage. Smaller environments generally do not require all of the functionality needed for large-scale environments. Eliminating unnecessary monitoring increases the performance levels in a small environment.

After installation of the Express edition, you must configure your environment before you can create backups. The simplest way to complete the configuration is to use the Express configuration wizard, accessed from the Administration menu in the OnCommand console. The wizard configures your host service (required for virtual environments), discovers storage on your system, and groups that storage into a logical entity called a resource pool.

You can upgrade from the Express edition to the Standard edition if you later determine that you want to use the additional monitoring functionality provided by the Standard edition.

Standard edition

The OnCommand Standard edition provides functionality in the DataFabric Manager server that is needed for larger deployments. This additional functionality requires that OnCommand and its DataFabric Manager server must be installed on a dedicated system.

The Standard edition does not offer a configuration wizard because its additional functionality requires more configuration considerations. You can do the post-installation configuration from the OnCommand console graphical user interface.

After the Standard edition is installed, you cannot downgrade to the OnCommand Express edition without losing the content of your existing database. The extended functionality and server database cannot be downsized to work with the Express edition.

Related tasks

[Installing the OnCommand Core Package on Windows](#) on page 42

[Installing the OnCommand Core Package on Linux](#) on page 44

Comparison of Standard and Express edition functionality

Specific DataFabric Manager server functionality is automatically enabled or disabled in the Standard and Express editions of OnCommand.

Available Feature	Standard edition	Express edition
Chargeback reports	Y	Y
DataFabric Manager (DFM) Services, all	Y	Y
Discovery of agents, clusters, and SAN	Y	N
Discovery of storage systems	Y	Y
Events and alerts available	Y	Y
Monitoring of agents, clusters, host RBAC, quotas, SAN hosts, SRM, and Vservers	Y	N
Monitoring of multiple storage system configurations	Y	N
Performance Advisor, in the NetApp Management Console	Y	N
Protection capability, in the NetApp Management Console	Y	Y
Provisioning capability, in the NetApp Management Console	Y	Y
Role-based access control (RBAC)	Y	Y
Schedule pre-configured for DataFabric Manager server database backups	N	Y
SOAP and ZAPI Interfaces	Y	Y
Storage services and resource pools configured automatically	N	Y
Web UI reporting	Y	Y

Available Feature	Standard edition	Express edition
<p>Editing monitoring intervals, in the Operations Manager console and the CLI</p>	<p>All monitoring intervals may be edited</p>	<p>The following monitoring intervals are read-only; however, the default is set to a higher interval than those in the Standard edition:</p> <ul style="list-style-type: none"> • Snapshot monitoring interval • File system monitoring interval • LUN monitoring interval • SnapMirror monitoring interval • SnapVault monitoring interval • Discovery interval • shareMonInterval (CLI-only) • dpReaperInterval (CLI-only)

System requirements

Before you install software, you must ensure that your storage system conforms to all supported platform requirements. Servers running OnCommand Core Package or Host Package must meet specific software, hardware, and operating system requirements.

Browser requirements

Before you begin the installation, confirm that you are using a Microsoft Internet Explorer or Mozilla Firefox browser that is supported by the OnCommand management software.

Supported browsers

The OnCommand management software supports the following browsers, based on the operating system and the GUI console used:

Operating system	OnCommand package installed	OnCommand GUI console used	Supported browser
Windows	Core Package only	OnCommand console only	Microsoft Internet Explorer 8 or Mozilla Firefox versions 3.0, 3.5, and 3.6
Windows	Core Package and Host Package	OnCommand console and OnCommand Plug-in for VMware	Windows Internet Explorer 8 only
Linux	Core Package only	OnCommand console only	No browsers supported on Linux hosts. Use Microsoft Internet Explorer 8 or Mozilla Firefox versions 3.0, 3.5, or 3.6 on a Windows system.

See the Interoperability Matrix Tool for possible updates to this information.

Browser requirements and limitations

Microsoft Internet Explorer, version 8

- You must disable the Compatibility View feature before launching the OnCommand console. For details, see the Microsoft support site.
- Ensure that the following security features are enabled:
 - Binary and script behaviors

To enable this feature, from the Tools menu, choose **Internet Options > Security > Custom level > ActiveX controls and plug-ins > Binary and scrip behaviors > Enable**.

- Active scripting

To enable this feature, from the Tools menu, choose **Internet Options > Security > Custom level > ActiveX controls and plug-ins > Active scripting > Enable**.

- If enhanced security is enabled in Internet Explorer 8, you might have to add `http://DataFabric Manager server IP address:8080` to the browser's list of trusted sites.

To add the DataFabric Manager server URL to the list of trusted sites, from the Tools menu, choose **Internet Options > Security > Sites** and add the URL.

Browser support with Linux The OnCommand software does not provide browser support for Linux hosts. However, you can install and run DataFabric Manager server on a Linux workstation or server, and launch the OnCommand console GUI using the Internet Explorer 8 or Firefox browser on a Windows system.

Related information

[Microsoft Support](#)

[NetApp Interoperability Matrix Tool - http://now.netapp.com/NOW/products/interoperability/](http://now.netapp.com/NOW/products/interoperability/)

Accessing the OnCommand console on a Linux-based PC

If you install and run DataFabric Manager server on a Linux workstation or server, you must launch the OnCommand console GUI using the Internet Explorer 8 or Firefox browser on a separate Windows system to manage the DataFabric Manager server, which is running on a Linux-based computer.

Steps

1. Install the OnCommand Core Package on a Linux workstation or server.
2. Install the NetApp Management Console on a Windows machine.
3. Install the Firefox or Internet Explorer browser on the same Windows machine as the NetApp Management Console.
4. Configure the NetApp Management Console and the browser to point to the Linux workstation or server where the DataFabric Manager server is installed.
5. Launch the OnCommand console GUI using the Internet Explorer or Firefox browser that is running on the Windows machine where it can communicate with the DataFabric Manager server that is running on the Linux workstation or server.

License requirements

Each of the OnCommand components has specific licensing requirements.

Core Package	The OnCommand Core Package does not require a license.
Host Package	The OnCommand Host Package requires one license per storage system, but it does not generate any license key.
DataFabric Manager server	The DataFabric Manager server requires one core license key, which is free and is used only to establish a unique serial number for the server.
Data ONTAP requirements	<p>Certain OnCommand functionality requires other types of licenses for Data ONTAP.</p> <ul style="list-style-type: none"> • NetApp has announced the end of availability for SAN licenses. DataFabric Manager server customers should check with their NetApp sales representative regarding other NetApp SAN management solutions. • Because NetApp has announced the end of availability for the Business Continuance Option (BCO) license, BCO customers should migrate their environment to the OnCommand console and use the protection capability of the NetApp Management Console.

See the Interoperability Matrix Tool for details.

Related information

[NetApp Interoperability Matrix Tool - http://now.netapp.com/NOW/products/interoperability/](http://now.netapp.com/NOW/products/interoperability/)

Network storage requirements for database files

To enable optimal database access and performance results, DataFabric Manager server requires that DataFabric Manager server database files be installed on a server using either SAN or iSCSI to connect to the network.

Sybase and DataFabric Manager server do not support accessing DataFabric Manager server Sybase database files on NAS because database recovery cannot be guaranteed and because of the potential impact to performance.

Related information

[Running a SQL Anywhere Database File that is Stored Remotely from the Server Machine Starting the Database Server](#)

OnCommand Core Package hardware and software requirements

Before installing the OnCommand Core Package, ensure that your system meets the hardware and software requirements.

Software required prior to installing the OnCommand Core Package

Before installing the OnCommand Core Package, you must preinstall Adobe Flash Player 10.0 or later on the server where the Core Package will be installed or your install cannot complete.

You can download the software from the Adobe downloads site.

Before you download Flash Player, ensure that file downloads are enabled in your Web browser, and, if you are using Microsoft Internet Explorer, verify that the security settings for ActiveX controls are enabled.

You must install Adobe Flash Player from each browser type you intend to use with the OnCommand console, even if the browsers are on the same system. For example, if you have both Mozilla Firefox and Microsoft Internet Explorer on the same system and you think you might use both browsers to access the OnCommand console, install Adobe Flash Player using the Firefox browser, and then install Adobe Flash Player using the Internet Explorer browser.

Related information

[Adobe Downloads](#)

Software required for some environments

You must separately download and install Open Systems SnapVault and NetApp Host Agent software for certain environment configurations.

Both products can be downloaded from the NetApp Support Site Download page, which is accessible from support.netapp.com. They can be installed either before or after you install the OnCommand Core Package.

Open Systems SnapVault

Open Systems SnapVault is required only if you intend to back up and restore data residing on non-NetApp physical storage systems. OnCommand Core Package supports the use of Open Systems SnapVault to back up and restore virtual machines in a non-NetApp storage environment, but it is not required. OnCommand Core Package supports Open Systems SnapVault versions 2.5, 2.6, and 2.6.1. However, the minimum version required for back up and restore of virtual machines in VMware is Open Systems SnapVault version 2.6 or later.

For information about installing and managing the Host Agent software, see the *Open Systems SnapVault Installation and Administration Guide*.

NetApp Host Agent

NetApp Host Agent is required if you want OnCommand to monitor SAN hosts or File SRM-generated file system data. The Host Agent software collects information such as operating system name and version, HBA port details, and file-system metadata, and then sends that information to the DataFabric Manager server. The NetApp Host Agent software must be installed on any Windows or Linux hosts from which you want to monitor SAN host or File SRM data with NetApp OnCommand management software.

NetApp Host Agent is also required if you want to remotely start, stop or restart Open Systems SnapVault software by using NetApp Management Console. In this case, the Host Agent must be installed on the same machine as OSSV.

The minimum version supported by OnCommand Core Package is NetApp Host Agent version 2.7.

For information about installing and managing the Host Agent software, see the *NetApp Host Agent Installation and Administration Guide*.

Windows Server 2008 with 1 to 25 storage systems

These requirements apply to systems running Windows 32-bit OS on x86 hardware and Windows 64-bit OS on x64 hardware.

Operating system requirements

The software requirements are as follows:

- Microsoft Windows Server 2008, Enterprise or Standard edition
- Microsoft Windows 2008 R2, Enterprise or Standard edition
- Microsoft Windows Server 2008 or 2008 R2 running on VMware ESX 3.5 or 4.0
- Microsoft Hyper-V Server 2008 or Hyper-V Server 2008 R2

Note: If you want to use rsh and are installing DataFabric Manager server on Windows Server 2008, install Subsystem for UNIX-based Applications (SUA) or Service for UNIX (SFU) to support execution of rsh commands.

Hardware requirements

The hardware requirements are as follows:

Hardware	Requirements
Processor	<ul style="list-style-type: none"> • Intel or AMD x64 processor • 2 GHz or faster CPU
Memory	<ul style="list-style-type: none"> • 32-bit OS: 3 GB RAM (minimum) • 64-bit OS: 4 GB RAM (minimum)

Hardware	Requirements
Disk space	<ul style="list-style-type: none"> • 10 GB (minimum) • 40 GB (recommended)
Temporary disk space for installation	<ul style="list-style-type: none"> • 4 GB

Windows Server 2008 with 25 or more storage systems

These requirements apply to systems running Windows 32-bit OS on x86 hardware and Windows 64-bit OS on x64 hardware.

Operating system requirements

The software requirements are as follows:

- Microsoft Windows Server 2008, Enterprise or Standard edition
- Microsoft Windows 2008 R2, Enterprise or Standard edition
- Microsoft Windows Server 2008 or 2008 R2 running on VMware ESX 3.5 or 4.0
- Microsoft Hyper-V Server 2008 or Hyper-V Server 2008 R2

Note: Windows 32-bit OS does not support the use of more than 4 GB of RAM. Therefore, using Windows 64-bit OS is recommended with configurations that support more than 25 storage systems.

Note: If you want to use rsh and are installing DataFabric Manager server on Windows Server 2008, install Subsystem for UNIX-based Applications (SUA) or Service for UNIX (SFU) to support execution of rsh commands.

Hardware requirements

The hardware requirements are as follows:

Hardware	Requirements
Processor	<ul style="list-style-type: none"> • Intel or AMD x64 processor • 2 GHz or faster CPU
Memory	<ul style="list-style-type: none"> • 32-bit OS: 4 GB RAM minimum • 64-bit OS: <ul style="list-style-type: none"> 6 GB RAM minimum 12 GB RAM recommended

Hardware	Requirements
Disk space	<ul style="list-style-type: none"> • 12 GB (minimum) • 60 GB (recommended)
Temporary disk space for installation	<ul style="list-style-type: none"> • 4 GB

Windows Server 2003 with 1 to 25 storage systems

These requirements apply to systems running Windows 32-bit OS on x86 hardware and Windows 64-bit OS on x64 hardware.

Operating system requirements

The software requirements are as follows:

- Microsoft Windows Server 2003, Enterprise or Standard edition
- Microsoft Windows Server 2003 running on VMware ESX 3.5 or later

Hardware requirements

The hardware requirements are as follows:

Hardware	Requirements
Processor	<ul style="list-style-type: none"> • Intel or AMD x64 processor • 2 GHz or faster CPU
Memory	<ul style="list-style-type: none"> • 32-bit OS: 3 GB RAM (minimum) • 64-bit OS: 4 GB RAM (minimum)
Disk space	<ul style="list-style-type: none"> • 10 GB (minimum) • 40 GB (recommended)
Temporary disk space for installation	<ul style="list-style-type: none"> • 4 GB

Windows Server 2003 with 25 or more storage systems

These requirements apply to systems running Windows 32-bit OS on x86 hardware and Windows 64-bit OS on x64 hardware.

Operating system requirements

The software requirements are as follows:

- Microsoft Windows Server 2003, Enterprise or Standard edition
- Microsoft Windows Server 2003 running on VMware ESX 3.5 or later

Note: Windows 32-bit OS does not support the use of more than 4 GB of RAM. Therefore, using Windows 64-bit OS is recommended with configurations that support more than 25 storage systems.

Hardware requirements

The hardware requirements are as follows:

Hardware	Requirements
Processor	<ul style="list-style-type: none"> • Intel or AMD x64 processor • 2 GHz or faster CPU
Memory	<ul style="list-style-type: none"> • 32-bit OS: 4 GB RAM minimum • 64-bit OS: <ul style="list-style-type: none"> 6 GB RAM minimum 12 GB RAM recommended
Disk space	<ul style="list-style-type: none"> • 12 GB (minimum) • 60 GB (recommended)
Temporary disk space for installation	<ul style="list-style-type: none"> • 4 GB

* Operating system support for Physical Address Extension (PAE) is required. See the documentation for your operating system for details about enabling PAE.

Linux workstation or server with 1 to 25 storage systems

These requirements apply to systems running Linux workstation or server. They also apply to 32-bit and 64-bit environments.

Operating system requirements

The software requirements for Linux workstation or server are as follows:

- Oracle Enterprise Linux 4.8 or 5.4, x86, 32-bit or 64-bit
- Red Hat Enterprise Linux AS 4.8 or 5.4, x86, 32-bit or 64-bit
- Red Hat Enterprise Linux Advanced Platform 5.4, x86, 32-bit or 64-bit
- SUSE Linux Enterprise Server 10 SP3 or 11, x86, 32-bit or 64-bit

The software requirements for Linux server on VMware ESX 3.5 or 4.0 are as follows:

- Red Hat Enterprise Linux AS 4.8 or 5.4, x86, 32-bit or 64-bit

- SUSE Linux Enterprise Server 10 SP3 or 11, x86, 32-bit or 64-bit

Hardware requirements

The hardware requirements for Linux workstation or server and Linux server on VMware ESX 3.5 and 4.0 are as follows:

Hardware	Requirements
Processor	<ul style="list-style-type: none"> • Intel or AMD x64 processor • 2 GHz or faster CPU
Memory	<ul style="list-style-type: none"> • 32-bit OS: 3 GB RAM (minimum) • 64-bit OS: 4 GB RAM (minimum)
Disk space	<ul style="list-style-type: none"> • 4 GB of free disk space (minimum) • 8 GB (recommended)
Temporary disk space for installation	<ul style="list-style-type: none"> • 4 GB

Linux workstation or server with 25 or more storage systems

These requirements apply to systems running Linux workstation or server and Linux server on VMware ESX 3.5 or 4.0. They also apply to 32-bit and 64-bit environments.

Operating system requirements

The software requirements for Linux workstation or server are as follows:

- Oracle Enterprise Linux 4.8 or 5.4, x86, 32-bit or 64-bit
- Red Hat Enterprise Linux AS 4.8 or 5.4, x86, 32-bit or 64-bit
- Red Hat Enterprise Linux Advanced Platform 5.4, x86, 32-bit or 64-bit
- SUSE Linux Enterprise Server 10 SP3 or 11, x86, 32-bit or 64-bit

The software requirements for Linux server on VMware ESX 3.5 or 4.0 are as follows:

- Red Hat Enterprise Linux AS 4.8 or 5.4, x86, 32-bit or 64-bit
- SUSE Linux Enterprise Server 10 SP3 or 11, x86, 32-bit or 64-bit

Note: A 32-bit OS does not support the use of more than 4 GB of RAM. Therefore, using a 64-bit OS is recommended with configurations that support more than 25 storage systems.

Hardware requirements

The hardware requirements for Linux workstation or server and Linux server on VMware ESX 3.5 and 4.0 are as follows:

Hardware	Requirements
Processor	<ul style="list-style-type: none"> Intel or AMD x64 processor 2 GHz or faster CPU
Memory	<ul style="list-style-type: none"> 32-bit OS: 4 GB RAM minimum 64-bit OS: <ul style="list-style-type: none"> 6 GB RAM minimum 12 GB RAM recommended
Disk space	<ul style="list-style-type: none"> 4 GB of free disk space (minimum) 8 GB (recommended)
Temporary disk space for installation	<ul style="list-style-type: none"> 4 GB

Required ports for the Core Package

You might need to configure your firewall to open default ports that enable communication between DataFabric Manager server and various components, such as managed storage systems, agents, and so on. If a port is not open, communication fails between DataFabric Manager server and the storage system or other component.

The following are the default ports that must be open on your firewall:

Default port number	Description
22	The port used for initiating, on storage systems, a secure cluster console, secure storage system takeover and giveback, secure remote command execution. The port is also used for vFiler unit monitoring and management.
23	The port used to initiate a telnet session to managed storage systems.
25	The SMTP port used by DataFabric Manager server to send e-mail for alarms and autosupport notification when the <code>autosupportProtocol</code> option is set to SMTP.
80	The port used for storage system management.
161	The port used to communicate with storage systems.
162	The port used by managed storage systems to send SNMP traps to DataFabric Manager server to speed up monitoring of important events. This port is configurable.

Default port number	Description
443	The port used for SecureAdmin-based storage system management.
514	The port used for initiating on storage systems a cluster console, storage system takeover and giveback, remote command execution, and for vFiler unit monitoring and management.
4092	The port used to connect to the NetApp Host Agent.
4093	The port used for a secure connection to the NetApp Host Agent.
8080	This port is used for Operations Manager console access. Note: If you install the OnCommand Express edition on the same system on which the vCenter Server and the vSphere are installed, you might get a message indicating that port 8080 is already in use and that you must select a different port. Follow the directions in the message to set a different port and start the service manually.
8088	The port used for NetApp Management Console access.
8443	The port used for secure Operations Manager console access.
8488	The port used for secure NetApp Management Console access.
10000	The port used by Backup Manager, Disaster Recovery Manager, and Protection Manager to monitor and manage storage system SnapVault and SnapMirror relationships, and SnapVault relationships from Open Systems SnapVault agents.

Related references

[Required ports for the Host Package](#) on page 38

OnCommand Host Package hardware and software requirements

Before installing the OnCommand Host Package in a VMware or a Hyper-V environment, ensure that your system meets the hardware and software requirements.

Hardware requirements

Your Windows system must meet minimum hardware requirements before you can install the OnCommand Host Package. These requirements apply to all virtual environments. The actual requirements depend on your system configuration.

Hardware	Requirements
Processor	<ul style="list-style-type: none"> • Intel or AMD x64 processor • 2 GHz or faster Intel or AMD x86 processor
Memory	<ul style="list-style-type: none"> • 1 GB RAM (minimum for 32-bit environments) • 2 GB RAM (recommended for 32-bit environments) • 2 GB RAM (minimum for 64-bit environments) • 4 GB RAM (recommended for 64-bit environments)
Disk space	<ul style="list-style-type: none"> • 1 GB (minimum) • 2 GB (recommended)
Temporary disk space for installation	<ul style="list-style-type: none"> • 5 GB Required for the Windows drive

Operating system requirements for VMware environments

You must ensure that the OnCommand Host Package supports your operating system.

Operating systems

The Host Package for VMware environments supports the following operating systems:

- Microsoft Windows Server 2003 or 2003 R2
- Microsoft Windows Server 2008 or 2008 R2 running on VMware ESX 3.5 or later

See the Interoperability Matrix Tool for details.

Related information

NetApp Interoperability Matrix Tool - <http://now.netapp.com/NOW/products/interoperability/>

Software required prior to installing the OnCommand Host Package for VMware environments

Before installing the OnCommand Host Package for VMware environments for the first time, you must have certain Microsoft software installed. These must be installed on each system on which the Host Package is installed.

Microsoft .NET Framework

OnCommand supports Microsoft .NET 3.5 SP1, but not 4.0. If you have 4.0 installed, you do not need to downgrade; just install 3.5 SP1. Both .NET versions can be installed on the system. OnCommand uses 3.5 by default.

Microsoft Net.TCP Port Sharing Service

This service is not enabled by default and it must be manually enabled prior to installing the Host Package. See the [Microsoft MSDN library](#) for more information.

Microsoft Windows PowerShell

Search using the text string "PowerShell" on the Microsoft Support site and select the appropriate version for your system. The minimum required version is PowerShell 1.0, but PowerShell 2.0 is recommended because it is required to use the DataFabric Manager server PowerShell Cmdlets.

Note: On Windows Server 2008, PowerShell 1.0 is installed by default, but you need to enable it on the server. You must download and install PowerShell 2.0.

Note: On Windows Server 2003, you must download and install PowerShell.

Windows Installer 4.5 or later (Windows Server 2003)

When you connect to the console session of Windows 2003, use one of the following commands
`mstsc /v:<vmip> /admin` or `mstsc /v:<vmip> /console`

Microsoft Visual C++ 2008 SP Redistributable Package on Windows Server 2008 Server Core installations

The following software packages are only required for the server core or minimal installation option for Windows Server 2008. You can view information about and download the software from the Microsoft Download Center. See the [Microsoft Download Center](#) for more information.

- For 32-bit systems, you must install the Microsoft Visual C++ 2008 SP Redistributable Package (x86).
- For 64-bit systems, you must install the Microsoft Visual C++ 2008 SP Redistributable Package (x86) and the Microsoft Visual C++ 2008 SP Redistributable Package (x64).

Microsoft Hotfixes

The following hotfixes are required and can be downloaded from the Microsoft support site:

- KB886695
- KB925336
- KB968730
- KB981929
- KB983280

The following Windows Server 2003 hotfixes are required when you install the OnCommand Host Package and SnapDrive for Windows on VMs for RDM LUN creation and management:

- KB919117
- KB931300
- KB932755
- KB937382

Related information

[Microsoft Support](#)

Operating system requirements for Hyper-V environments

You must ensure that the OnCommand Host Package supports your operating system.

Operating systems

The Host Package for Hyper-V environments supports the following operating systems:

- Microsoft Windows Server 2008 or 2008 R2
- Microsoft Hyper-V Server 2008 or Hyper-V Server 2008 R2

See the Interoperability Matrix Tool for details.

Related information

[NetApp Interoperability Matrix Tool - http://now.netapp.com/NOW/products/interoperability/](http://now.netapp.com/NOW/products/interoperability/)

Software required prior to installing the OnCommand Host Package for Hyper-V environments

Before installing the OnCommand Host Package for Hyper-V environments for the first time, you must have certain Microsoft software installed. These must be installed on each system on which the Host Package is installed.

Microsoft .NET Framework

OnCommand supports Microsoft .NET 3.5 SP1, but not 4.0. If you have 4.0 installed, you do not need to downgrade; just install 3.5 SP1. Both .NET versions can be installed on the system. OnCommand uses 3.5 by default.

Microsoft Net.TCP Port Sharing Service

This service is not enabled by default and it must be manually enabled prior to installing the Host Package. See the *Microsoft MSDN library* for more information.

Microsoft Windows PowerShell

Search using the text string "PowerShell" on the Microsoft Support site and select the appropriate version for your system. The minimum required version is PowerShell 1.0, but PowerShell 2.0 is recommended because it is required to use the DataFabric Manager server PowerShell Cmdlets.

Note: On Windows Server 2008, PowerShell 1.0 is installed by default, but you need it enable it on the server. You must download and install PowerShell 2.0.

Microsoft Visual C++ 2008 SP Redistributable Package on Windows Server 2008 Server Core installations

The following software packages are only required for the server core or minimal installation option for Windows Server 2008. You can view information about and download the software from the Microsoft Download Center. See the *Microsoft Download Center* for more information.

- You must install the Microsoft Visual C++ 2008 SP Redistributable Package (x64).

Microsoft Hotfixes

The following hotfixes are required and can be downloaded from the Microsoft support site:

- KB974930
- KB975354
- KB975921
- KB977096
- KB978157
- KB981929

- KB2416849

In addition, SnapDrive for Windows requires the following hotfixes to work properly:

- KB950927
- KB952790
- KB955656
- KB956697

The following Windows Server 2003 hotfixes are required when you install the OnCommand Host Package and SnapDrive for Windows on VMs for pass-through LUN creation and management:

- KB919117
- KB931300
- KB932755
- KB937382

Related information

[Microsoft Support](#)

Required ports for the Host Package

The OnCommand Host Package uses designated ports to enable communication between components. If the Windows Firewall is enabled, you must ensure that the firewall is set to allow exceptions.

For firewalls other than Windows, you must manually grant access to specific ports that are to be used for the Host Package installation. The installer attempts to create the necessary exceptions to specific ports in your Windows firewall; if you have other types of firewalls in place, verify that these ports are available.

All of the ports listed can be used to install the Host Package with a script except where noted in the table.

The Host Package uses the following default ports in a VMware environment:

Note: The installer automatically creates firewall exceptions for the first seven ports listed in the table.

Default port number	Description
8699	The port used by the OnCommand Host service administrator.
808	The OnCommand TCP/IP endpoint.
8799	The port used by the OnCommand Host service agent.
8897	The port used by the OnCommand file service.

Default port number	Description
8044	The port used by the OnCommand Host service VMware plug-in.
8143	The port used by the OnCommand Plug-in for VMware.
8043	The port used by SnapManager for Virtual Infrastructure.
8480	The port used by the DataFabric Manager server.
8488	The DataFabric Manager server HTTPS port, which is used for HTTP connections.
8053	The default port that the OnCommand host service VMware plug-in uses to send data to SnapDrive for Windows. Note: You must manually create a firewall exception for this port after you finish installing the Host Package.
443	The port used by the vCenter Server. Note: This port is only used for installing the Host Package with a script.

The Host Package uses the following default ports in a Hyper-V environment:

Note: The installer automatically creates firewall exceptions for the first four ports listed in the table.

Default port number	Description
8699	The port used by the OnCommand Host service administrator.
808	The OnCommand TCP/IP endpoint.
8799	The port used by the OnCommand Host service agent.
8897	The port used by the OnCommand file service.
8804	The port used by the OnCommand Host service Hyper-V plug-in.
8480	The port used by the DataFabric Manager server.
8488	The DataFabric Manager server HTTPS port, which is used for HTTP connections.

Default port number	Description
4094	The HTTP port. Note: This port is only used for installing the Host Package with a script.
4095	The HTTPS port. Note: This port is only used for installing the Host Package with a script.

Related references

Required ports for the Core Package on page 32

Installing the OnCommand Core Package

The OnCommand Core Package provides management capabilities for your physical storage environment and, when the OnCommand Host Package is also installed, the OnCommand console can display the physical-to-virtual mapping as well as provide policy-based local and remote backup and recovery for virtual objects.

Downloading the OnCommand Core Package

Before installing the OnCommand Core Package, you need to download the software package from the NOW site.

Before you begin

- You must have a NOW account.

About this task

You can choose from four executable files:

- Windows 64-bit
- Windows 32-bit
- Linux 64-bit
- Linux 32-bit

Steps

1. Specify the following URL in the browser address field:
`http://now.netapp.com/NOW/cgi-bin/software`
2. Locate and select the OnCommand Core Package.
3. From the drop-down list, select the operating system platform on which you are installing the Core Package and click **Go!**
4. Click **View & Download** for the software version you want to install.
5. On the Description Page, click **Continue**.
6. Review and accept the license agreement.
7. On the Download Page, click the link for the installation file:
 - For 32-bit systems, click **occore-setup-5-0-win-x86.exe**.
 - For 64-bit systems, click **occore-setup-5-0-win-x64.exe**.

8. Click Save File.

Note: Do not change the default location of the local TempFolder directory or the installation will fail. The installer automatically extracts the installation files to the %TEMP% location.

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

Installing the OnCommand Core Package on Windows

After you have met the guidelines, requirements, and restrictions for installing the OnCommand Core Package, you can follow the prompts in the installation wizard to install the software.

Before you begin

- The system that you use for your Core Package installation must belong to a domain rather than a workgroup.
- You must have administrator privileges for the Windows computer on which you are installing the Core Package.
- You must have the following items:
 - DataFabric Manager server license key
 - Credentials for network access
 - The IP address of the server on which you are installing the software
 - Directory path where you want to install, if different from the default location
- In addition, your antivirus software must include the following changes:
 - Either the antivirus software is disabled or an exclusion is added for DataFabric Manager server before you install OnCommand Core Package or the installation will fail.
 - The Sybase ASA files are excluded to avoid both DataFabric Manager server performance issues and the possibility of database corruption.

About this task

During the Core Package installation, if you select the Standard edition in the installation wizard, you configure it manually. If you select the Express edition, you can use the Express Configuration wizard to configure a host service.

For optimal performance, you should install the Core Package software on a dedicated system, especially if you are managing more than thirty storage systems with DataFabric Manager server.

Steps

1. Start the Core Package installation wizard.

2. Choose the edition of OnCommand Core Package that you want to install, the Standard edition or Express edition.
3. Select the installation location, if different from the default.
Note: Do not change the default location of the local TempFolder directory or the installation will fail. The installer automatically extracts the installation files to the %TEMP% location.
4. Review the summary screen and consider whether you want to make changes before completing the install process, then click **Install**.
5. When the Installation Complete screen appears, click **Next** to continue.
6. If you want to launch the OnCommand console, select Launch OnCommand console.
If you have not yet installed the OnCommand Host Package, download and install that first and then launch the OnCommand console from your browser.
7. Click **Finish**.

After you finish

- During the installation process, the installer creates some temporary folders that are automatically deleted the next time you reboot the system. You can delete these folders without adversely affecting the installation of the Core Package.
- You should clear the browser cache before you first launch the OnCommand console and when upgrading to a new version of the software.
- When you finish installing the Core Package, you can install the Host Package and use the configuration wizard to configure a host service.

Related concepts

[OnCommand Core Package hardware and software requirements](#) on page 26

[Installing the OnCommand Host Package](#) on page 51

[Comparison of OnCommand Standard and Express editions](#) on page 19

Related tasks

[Downloading the OnCommand Core Package](#) on page 41

[Determining whether a storage system belongs to a workgroup or a domain](#) on page 79

Related references

[Software required prior to installing the OnCommand Core Package](#) on page 26

Installing the OnCommand Core Package on Linux

After you have met the guidelines, requirements, and restrictions for installing the OnCommand Core Package, you can follow the prompts in the installation wizard to install the software.

Before you begin

- You must have the following items:
 - DataFabric Manager server license key
 - Credentials for network access
 - The IP address of the server on which you are installing the software
 - Directory path where you want to install, if different from the default location
- In addition, your antivirus software must include the following changes:
 - The antivirus software is either disabled or an exclusion is added for DataFabric Manager server before you install OnCommand Core Package or the installation will fail.
 - Sybase ASA files are excluded to avoid both DataFabric Manager server performance issues and the possibility of database corruption.
- If you are installing the Core Package on Red Hat Enterprise Linux Advanced Platform 5.x, the SELinux status must be disabled.

About this task

During the Core Package installation, if you select the Standard edition, you configure it manually. If you select the DataFabric Manager server Express edition in the Setup wizard, you can use the Express edition configuration wizard to simplify the setup of your environment.

For optimal performance, you should install the Core Package software on a dedicated system, especially if you are managing more than thirty storage systems with DataFabric Manager server.

Steps

1. Run the setup file:
 - For 32-bit systems, choose `occore-setup-5-0-linux.sh`
 - For 64-bit systems, choose `occore-setup-5-0-linux-x64.sh`
2. Follow the prompts, then select Standard edition or Express edition to indicate which version of DataFabric Manager server you want to install:
 - If you select the Standard edition, you configure your environment information, and your future backup and recovery operations manually in the OnCommand console following the installation.
 - If you select the Express edition, you can use the Express Edition Configuration wizard to simplify the setup of your environment, and your future backup and recovery operations.

3. Continue answering the questions as you are prompted.

When the URL for launching the OnCommand console is displayed, the installation is complete.

4. Copy and paste that URL into a browser to launch the OnCommand console.

Related concepts

[Installing the OnCommand Host Package](#) on page 51

[OnCommand Core Package hardware and software requirements](#) on page 26

[Comparison of OnCommand Standard and Express editions](#) on page 19

Related tasks

[Downloading the OnCommand Core Package](#) on page 41

Related references

[Software required prior to installing the OnCommand Core Package](#) on page 26

Installing the OnCommand Core Package with a script

You can quickly deploy the OnCommand Core Package using a scripted, unattended installation. The installation script contains the installation settings for the Core Package.

Before you begin

- You must have administrator privileges for the Windows computer on which you are installing the Core Package.
- The script must contain the following required information:
 - OnCommand server license key
 - Credentials for network access
 - IP address of the server on which you are installing
 - Directory path where you want to install if different from the default location

About this task

The installation script can reside in one of the following locations:

- Default installation script
- FTP
- HTTP/HTTPS
- NFS
- Local disk
- USB flash drive

Steps

1. Create a script using the supported commands.
2. Edit the installation script as needed to change the options that are unique for each installation.
3. Save the script to the location from which you want to run it.
4. Run the scripted installation or set a schedule for when the script is to run.

After you finish

- If you selected the DataFabric Manager server Express edition in the Setup wizard during the installation process, you can use the DataFabric Manager server Express Edition Configuration wizard to simplify the setup of your environment for initial backup and recovery operations.
- If you selected DataFabric Manager server Standard edition during the installation process, you must configure your environment manually before backup and recovery operations can take place.

Related references

[Required ports for the Core Package](#) on page 32

Scripted install options for the OnCommand Core Package on Windows

If you choose to, you can use these options to make settings in your Windows install script.

The following options can be used in the script:

Script	Description
/S	<ul style="list-style-type: none"> • Performs the installation silently without any installation screens appearing.
/EXPRESS_EDITION=<YES NO>	<ul style="list-style-type: none"> • Specifies the type of installation as Express edition or Standard edition. <p data-bbox="610 1236 895 1256">/EXPRESS_EDITION=YES</p> <ul style="list-style-type: none"> • Installs the Express edition. <p data-bbox="610 1340 881 1361">/EXPRESS_EDITION=NO</p> <ul style="list-style-type: none"> • Installs the Standard edition. • If this switch is not specified, for a fresh install, the Standard edition is installed; for an upgrade, the installer checks the previous edition in use, then upgrades that edition.

Script	Description
/LICENSEKEY=<license_key>	<ul style="list-style-type: none"> Specifies the DataFabric Manager server license key.
/UPGRADE	<ul style="list-style-type: none"> Specifies that an upgrade needs to be done.

There are no switches for the following situations:

- Accepting or rejecting the AutoSupport agreement from the CLI. Whenever a silent installation is invoked, the installation assumes that you accept the AutoSupport agreement.
- Specifying whether or not you want to take a backup during the upgrade. In a silent upgrade, a backup is always taken.
- Specifying the installation directory or database backup location directory. Otherwise, the default DataFabric Manager server paths are used.

Scripted install options for the OnCommand Core Package on Linux

If you choose to, you can use these options to make settings in your Linux install script.

The following options can be used in the script:

Option	Description
-a	<ul style="list-style-type: none"> The AutoSupport (ASUP) notice agreement is accepted if specified. If not specified in the command line during the invocation of the installer, then an interactive message of the ASUP notice is displayed on the terminal. You provide <i>yes</i> or <i>no</i> then.
-d <installation_directory>	<ul style="list-style-type: none"> Specifies the path of the installation directory. If not specified, the installation happens in the default directory. For example, <code>/opt/NTAPdfm/</code>
-l <licenses_key>	<ul style="list-style-type: none"> Specifies the license key on the command line. If not specified, an interactive message that prompts you to enter the license key displays on the terminal.
-b <yes no>	<ul style="list-style-type: none"> Specifies whether or not to do a database backup during the upgrade.
-B <backup_file_name>	<ul style="list-style-type: none"> Specifies the backup file name on the command line. If not specified, it would be the default backup file name that gets stored in the <code>data</code> directory of the installation directory.

Option	Description
-n	<ul style="list-style-type: none"> Specifies that you agree with removing NetCache support if you upgrade your DataFabric Manager server. It is used only for upgrades from DataFabric Manager server versions earlier than 3.8. If the option is not specified, and you are upgrading from a version earlier than 3.8, an interactive message that mentions the removal of NetCache support from DataFabric Manager server displays.
-s	<ul style="list-style-type: none"> Specifies whether Express edition or Standard edition needs to be installed. It takes the value <code>yes</code> to install Express edition or <code>no</code> to install Standard edition. If this switch is not specified, for a fresh install, it displays the installation choice selection interactive message; for an upgrade, the installer checks the previous edition in use, then upgrades that edition without displaying the interactive message.
-w <wrapper_directory>	<ul style="list-style-type: none"> Specifies the path for installing DataFabric Manager server CLI wrappers.

Setting up Web security after restoring a database on a new OnCommand Core Package installation

You can restore a database backup from another DataFabric Manager server instance to the new DataFabric Manager server installation, for instance, when you want to upgrade your hardware; however, database backups do not include the key and certificate file, so these must be generated or imported, and HTTPS must be enabled if it was set on the old system.

About this task

Perform these steps from a console session on the new DataFabric Manager server after you install the OnCommand Core Package.

Steps

1. Perform one of the following actions:
 - Enter the `dfm ssl service setup` command to create new client certificates.
 - Enter `dfm ssl server import` to import an existing certificate.

2. If the HTTPS service was enabled on the system from which the database backup was made, you must also enable the HTTPS service on the new system by entering `dfm option set httpsEnabled=Yes`.

Installing NetApp Management Console

You can download and install NetApp Management Console through the OnCommand console. NetApp Management Console is required to perform many of your physical storage tasks.

Before you begin

You must be authorized to perform all the steps of this task; your RBAC administrator can confirm your authorization in advance.

About this task

During this task, the OnCommand console launches the Operations Manager console. Depending on your browser configuration, you can return to the OnCommand console by using the Alt-Tab key combination or clicking the OnCommand console browser tab. After the completion of this task, you can leave the Operations Manager console open, or you can close it to conserve bandwidth.

Steps

1. Log in to the OnCommand console if necessary.
2. Click the **File** menu, then click **Download Management Console**.

A separate browser tab or window opens to the Management Console Software page in the Operations Manager console.

3. Click the download link for the Linux or Windows installation.
4. In the download dialog box, click **Save File**.

The executable file is downloaded to your local system, from the system on which the OnCommand Core Package was installed.

5. From the download directory, run the `nmconsole-setup-xxx.xxx` executable file.

The NetApp Management Console installation wizard opens.

6. Follow the prompts to install NetApp Management Console.

Result

After installation, you can access NetApp Management Console from the following locations:

- On Windows systems, the default installation path is `C:\Program Files\NetApp\Management Console`.

You can launch the console from the NetApp directory on the Start menu.

- On Linux systems, the default installation path is `/usr/lib/ NetApp/management_console/`. You can launch the console from `/usr/bin`.

Installing or upgrading OnCommand Windows PowerShell cmdlets

The Windows PowerShell cmdlets are not automatically installed with the OnCommand console. To use the Windows PowerShell cmdlets with the OnCommand console, you must manually install them. You also need to manually upgrade the cmdlets if you upgrade your version of OnCommand console.

Before you begin

You must have installed the appropriate version of OnCommand.

Steps

1. Navigate to the installation folder for OnCommand Core Package.
2. Navigate to the appropriate folder:

If you have installed the OnCommand Core Package...	Then
A Windows server	Navigate to the <code>DFM_Install_dir>\DFM\web\clients</code> folder.
A Linux server	Navigate to the folder.

This folder contains the Windows PowerShell installation package.

3. Execute the installation file:

If you are installing the cmdlets on...	Then
The same Windows server	Double-click the executable file and follow the installation wizard prompts.
A different Windows server	Copy the installation file to the server or workstation where you want to install the cmdlets and then execute the installation.
A Linux server	Copy the installation file to the server or workstation where you want to install the cmdlets and then execute the installation.

After you finish

You can now execute the Windows PowerShell cmdlets for OnCommand console.

Installing the OnCommand Host Package

The OnCommand Host Package provides management capabilities for your virtualized environment and, when the OnCommand Core Package is also installed, for your physical storage environment..

You can install the OnCommand Host Package using the installation wizard, or you can run a silent (unattended) installation by using a script at a Windows command prompt. Additionally, with the Core and Host Packages installed, policy-based local and remote backup and recovery are available from both the vCenter Server GUI as well as the OnCommand console.

Downloading the OnCommand Host Package

The OnCommand Host Package provides management capabilities for your virtual environment. Before installing the OnCommand Host Package, you need to download the software package from the NetApp NOW site.

Before you begin

- You must have a NOW account.

About this task

You can choose from two executable files:

- Windows 64-bit
- Windows 32-bit

Steps

1. Specify the following URL in the browser address field:
`http://now.netapp.com/NOW/cgi-bin/software`
2. Locate and select the OnCommand Host Package.
3. From the drop-down list, select the operating system platform on which you are installing the Host Package and click **Go!**
4. Click **View & Download** for the software version you want to install.
5. On the Description Page, click **Continue**.
6. Review and accept the license agreement.
7. On the Download Page, click the link for the installation file:
 - For 32-bit systems, click **ochost-setup-1-0-x86.exe**.

- For 64-bit systems, click **ochost-setup-1-0-x64.exe**.

8. Click **Save File**.

Note: Do not change the default location of the local TempFolder directory or the installation will fail. The installer automatically extracts the installation files to the %TEMP% location.

Related tasks

[Downloading the OnCommand Core Package](#) on page 41

Installing the OnCommand Host Package in a VMware environment

After you have reviewed the guidelines, requirements, and restrictions for installing the OnCommand Host Package for VMware environments, you can execute the installation wizard to install the software.

Before you begin

- The system that you use for your Host Package installation must belong to a domain rather than a workgroup.
- You must have administrator privileges for the Windows computer on which you are installing the Host Package.
- The DNS name of the Windows computer on which you are installing the Host Package must match the actual computer name and the computer name cannot be more than 15 characters.
- The Windows firewall must be set to allow exceptions.
- You must have the following items available:
 - A Windows system account user name and password
 - The path of the directory to which you want to install, if different from the default
 - The IP address, user name, and password of the DataFabric Manager server
 - The IP address, user name, and password of the vCenter Server

About this task

If you are installing the Host and Core Packages on the same system, a fully qualified domain name must be used for the Core Package instead of *localhost*.

The installer creates a locks directory, which is used to coordinate access to resources in the vSphere Client. The locks directory is located under the OnCommand directory. You must not change the name or the location of this directory.

The IP address and host name for the system on which you are installing the Host Package must have a DNS registration that resolves properly between the host service and the DataFabric Manager server.

You should use a dedicated Windows server for each vCenter Server instance. Having other applications installed on the same server can take up valuable system resources and might drastically reduce performance.

If the installer fails during the installation of the Host Package, the installer does not rollback the changes made to the system. You must manually remove the Host Package using the Control Panel application for your operating system and then delete the folder where the Host Package was installed.

Steps

1. Double-click the executable file to launch the OnCommand Host Package installer:

- For 32-bit systems, click `ochost-setup-1-0-x86.exe`.
- For 64-bit systems, click `ochost-setup-1-0-x64.exe`.

2. Depending on your operating system, you must either enable Windows PowerShell or install it before you can continue with the installation of the Host Package:

Note: An error message appears if PowerShell is not installed. PowerShell 1.0 is required but PowerShell 2.0 is recommended.

- On Windows Server 2008 R2, PowerShell is installed by default and you do not need to enable it on the server.
- On Windows Server 2008, PowerShell is not installed by default and you must enable it on the server after it is installed.
To enable PowerShell, follow the instructions in the pop-up dialog box.
- On Windows Server 2003 or 2003 R2, you must download and install PowerShell.

3. Select the installation location.

4. On the Virtual Infrastructure Options page, click **VMware** if it is not selected by default.

5. On the Service Credentials page, type the user name and password for the system on which you are installing the Host Package.

You must type the user name in the following format:

domain name\user name

6. On the Configure Communication Ports page, type the port numbers that you want to use or accept the default port numbers.

Note: For custom firewalls, ensure that the Core and Host Packages are using the same port numbers.

7. On the Configure DataFabric Manager server page, type the IP address and the user name and password used to access the DataFabric Manager server.

If you want to monitor your virtual environment or use the Backup and Recovery capability, you must type the credentials for the DataFabric Manager server. You can skip the validation of the DataFabric Manager server if you do not have the server credentials available or if you are going

to use only the Monitoring and Host Configuration or Provisioning and Cloning capabilities of the OnCommand Plug-in for VMware.

8. On the Plug-in Service and vCenter Server Information page, provide the following information:
 - a. Type the IP address of the system on which you are installing the Host Package.
 - b. Type the host name or IP address of the system on which the vCenter Server is installed and the user name and password that allows the vSphere Client to communicate with the vCenter Server.
9. Click **Install** on the summary page, and then click **Finish**.

When you next reboot the system, you might see some hidden MS-DOS command windows briefly appear in the background during the removal of installer support files that could not be deleted during the installation of the Host Package.

After you finish

- During the installation process, the installer creates some temporary folders that are automatically deleted when you next reboot the system.
You can delete these folders without adversely affecting the installation of the Host Package.
- The host service must be configured to perform backups.
You must associate storage systems with a host service when you complete the installation of the Host Package. If you selected the OnCommand Express edition during the installation of the Core Package, you can use the configuration wizard to configure the host service. If you selected the Standard edition, you must configure the host service from the Host Services tab accessible from the Administration menu of the OnCommand console.

Related concepts

[Comparison of OnCommand Standard and Express editions](#) on page 19

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

[Registering the OnCommand Plug-in for VMware with a vCenter Server](#) on page 77

[Determining whether a storage system belongs to a workgroup or a domain](#) on page 79

[Configuring the OnCommand Express edition server](#) on page 61

Related references

[Operating system requirements for VMware environments](#) on page 34

[Software required prior to installing the OnCommand Host Package for VMware environments](#) on page 35

[Required ports for the Host Package](#) on page 38

Installing the OnCommand Host Package in a Hyper-V environment

After you have reviewed the guidelines, requirements, and restrictions for installing the OnCommand Host Package for Hyper-V environments, you can execute the installation wizard to install the software.

Before you begin

- You must use the same user account as the SnapDrive for Windows service to install the Host Package.
- The system that you use for your Host Package installation must belong to a domain rather than a workgroup.
- You must have administrator privileges for the Windows computer on which you are installing the Host Package.
- The Windows firewall must be set to allow exceptions.
- If SnapDrive for Windows is already installed on the system and RBAC is enabled, the AccessControl.xml file, which is in the root volume of the storage system, must be deleted from the storage system.
- If SnapDrive for Windows or SnapManager for Hyper-V is already installed on the system, the SnapDrive for Windows service must have been stopped.
- You must have the following items available:
 - A Windows system account user name and password
 - The path of the directory to which you want to install, if different from the default
 - The IP address, user name, and password of the DataFabric Manager server

About this task

If you are installing the Host and Core Packages on the same system, a fully qualified domain name must be used for the Core Package instead of *localhost*.

If the Hyper-V parent is part of a cluster, you must install the Host Package on each node of the cluster and all the cluster nodes must share the same TCP/IP port to enable communication between host services on different nodes. You must register and authorize each node with the same DataFabric Manager server.

The IP address and host name for the system on which you are installing the Host Package must have a DNS registration that resolves properly between the host service and the DataFabric Manager server.

Steps

1. Double-click the executable file to launch the OnCommand Host Package installer.

- Click `ochost-setup-1-0-x64.exe`.
2. Depending on your operating system, you must either install Windows PowerShell or enable it before you can continue with the installation of the Host Package.
Note: An error message appears if PowerShell is not installed. PowerShell 1.0 is required but PowerShell 2.0 is recommended.
 - On Windows Server 2008 R2, PowerShell is installed by default and you do not need to enable it on the server.
 - On Windows Server 2008, PowerShell is not installed by default and you must enable it on the server after it is installed.
To enable PowerShell, follow the instructions in the pop-up dialog box.
 3. Select the installation location.
 4. On the Virtual Infrastructure Options page, click **Hyper-V** if it is not selected by default.
 5. On the Service Credentials page, type the user name and password for the system on which you are installing the Host Package.

You must type the user name in the following format:

domain name\user name

6. On the Configure Communication Ports page, type the port numbers that you want to use or accept the default port numbers.
Note: For custom firewalls, ensure that the Core and Host Packages are using the same port numbers.
7. On the Configure DataFabric Manager server page, type the IP address and the user name and password used to access DataFabric Manager server.
You can skip the validation of the DataFabric Manager server at this point if you do not have the server credentials available.
8. Click **Install** on the summary page, and then click **Finish**.
When you next reboot the system, you might see some hidden MS-DOS command windows briefly appear in the background during the removal of installer support files that could not be deleted during the installation of the Host Package.

After you finish

- During the installation process, the installer creates some temporary folders that are automatically deleted when you next reboot the system.
You can delete these folders without adversely affecting the installation of the Host Package.
- From the Hyper-V host on which the Host Package and SnapDrive for Windows is installed, ensure that you can ping the storage system containing the virtual objects.

If you cannot ping the storage system from the Hyper-V host, you must add the system to the etc \hosts file on the Hyper-V host. Otherwise, your backup and restore operations might not complete successfully.

- The host service must be configured to perform backups.
You must associate storage systems with a host service when you complete the installation of the Host Package. If you selected the OnCommand Express edition during the installation of the Core Package, you can use the configuration wizard to configure the host service. If you selected the Standard edition, you must configure the host service from the Host Services tab accessible from the Administration menu of the OnCommand console.

Related concepts

[Comparison of OnCommand Standard and Express editions](#) on page 19

[How to manually transition SnapManager for Hyper-V dataset information](#) on page 79

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

[Determining whether a storage system belongs to a workgroup or a domain](#) on page 79

[Updating the SnapDrive for Windows service account](#) on page 80

[Adding port exceptions to Windows Firewall](#) on page 80

[Configuring the OnCommand Express edition server](#) on page 61

Related references

[Operating system requirements for Hyper-V environments](#) on page 36

[Software required prior to installing the OnCommand Host Package for Hyper-V environments](#) on page 37

[Required ports for the Host Package](#) on page 38

Installing the OnCommand Host Package with a script

You can quickly deploy the OnCommand Host Package by creating a script customized to the needs of your particular environment, and then performing an unattended installation. The installation script that you create contains your customized installation settings for the Host Package.

Before you begin

- You must have administrator privileges for the Windows computer on which you are installing the Host Package.
- Your script must contain the following required information:
 - Credentials for network access
 - IP address of the server on which you are installing

- The path of the directory to which you want to install, if different from the default location

About this task

You can store your customized installation script in one of the following locations:

- Default installation script
- FTP
- HTTP/HTTPS
- NFS
- Local disk
- USB flash drive

Steps

1. Create a script using the supported commands.
2. Edit the installation script as needed to change the options that are unique for each installation.
3. Save the script in the location from which you want to run it.
4. Run the scripted installation or set a schedule for when the script is to run.

After you finish

- You must configure the host service to work with the DataFabric Manager server.
If you selected the OnCommand Express edition during the installation of the Core Package, you can use the configuration wizard to configure the host service.

Related references

[Required ports for the Host Package](#) on page 38

Scripted install options for the OnCommand Host Package in a VMware environment

If you choose to install the OnCommand Host Package in a Windows environment by using an unattended script, you can use these options to create that script.

The following options can be used in the script:

Option	Description
<code>setup.exe /s/v /qn PLUGIN_TYPE=0</code>	<ul style="list-style-type: none"> • Performs the installation silently, without any interactive screens appearing.
<code>SVCUSERNAME</code>	<ul style="list-style-type: none"> • Specifies the host service user name.

Option	Description
SVCUSERPASSWORD	<ul style="list-style-type: none"> Specifies the host service password.
SVCCONFIRMUSERPASSWORD	<ul style="list-style-type: none"> Confirms the host service password.
DFM_SERVER_INFO	<ul style="list-style-type: none"> Specifies the DataFabric Manager server IP address.
DFM_SERVER_USERNAME	<ul style="list-style-type: none"> Specifies the DataFabric Manager server user name.
DFM_SERVER_PASSWORD	<ul style="list-style-type: none"> Specifies the DataFabric Manager server password.
VMWARE_PLUGIN_IP	<ul style="list-style-type: none"> Specifies the OnCommand Plug-in for VMware IP address
VCENTER_IP	<ul style="list-style-type: none"> Specifies the vCenter Server IP address.
VCENTER_USERNAME	<ul style="list-style-type: none"> Specifies the vCenter Server user name.
VCENTER_PASSWORD	<ul style="list-style-type: none"> Specifies the vCenter Server password.
PLUGIN_PORT	<ul style="list-style-type: none"> Specifies the default port.

Scripted install options for the OnCommand Host Package in a Hyper-V environment

If you choose to install the OnCommand Host Package in a Windows environment by using an unattended script, you can use these options to create that script.

The following options can be used in the script:

Script	Description
<code>setup.exe /s/v /qn PLUGIN_TYPE=1</code>	<ul style="list-style-type: none"> Performs the installation silently, without any interactive screens appearing.
SVCUSERNAME	<ul style="list-style-type: none"> Specifies the host service user name.
SVCUSERPASSWORD	<ul style="list-style-type: none"> Specifies the host service password.

Script	Description
SVCCONFIRMUSERPASSWORD	<ul style="list-style-type: none">• Confirms the host service password.
DFM_SERVER_INFO	<ul style="list-style-type: none">• Specifies the DataFabric Manager server IP address.
DFM_SERVER_USERNAME	<ul style="list-style-type: none">• Specifies the DataFabric Manager server user name.
DFM_SERVER_PASSWORD	<ul style="list-style-type: none">• Specifies the DataFabric Manager server password.
PLUGIN_PORT	<ul style="list-style-type: none">• Specifies the default port.
STOPSMHVSVC=1	<ul style="list-style-type: none">• Performs the installation in an environment in which Snapdrive for Windows or SnapManager for Hyper-V are already installed.

Setting up your system

After you finish installing the OnCommand Host Package or Core Package, you can configure your system.

Configuring the OnCommand Express edition server

You can use the Express Configuration wizard to simplify the setup of your system. The wizard sets up the Express edition server to discover and monitor storage systems and host services, populates a default resource pool, associates available storage, and creates and attaches a default storage service.

Before you begin

- You must have installed the following:
 - OnCommand Core Package
 - OnCommand Host Package
 - VMware vCenter or Microsoft Hyper-V
 - Adobe Flash Player 10.0 or later
 - OnCommand Windows PowerShell cmdlets
- You might need some or all of the following information to complete this task:
 - IP address or FQDN for each host service
 - vCenter Server name and credentials
 - Name and credentials for each storage system
 - Port numbers, if different than the defaults
 - NDMP user name and password
 - SNMP credentials


About this task

The **Express Configuration** wizard configures two default storage services, remote backup and mirror, with deduplication enabled for increased efficiency. You can validate your performance requirements to ensure these policies align with your requirements.


Steps

1. Click the **Administration** menu, then click the **Express Configuration** option.

The **Express Configuration** wizard might open automatically the first time you log in to the OnCommand console after you finish the Express edition installation.



2. On the **Add Host Service** page, click **Add** to register a host service with the DataFabric Manager server.



You must register each host service with the DataFabric Manager server, so that OnCommand is made aware of the host service and can manage it.

3. Enter the **IP Address/Name** and **Admin Port** for the host service, then click **Add**.

If using the name, it must be the fully qualified domain name (FQDN). If you are installing the Host Package and the DataFabric Manager server on the same system, you must specify the hostname or a fully qualified domain name, not localhost, for the DataFabric Manager server.


- Optional: If you need to edit settings for a host service, click **Edit**, make the changes, then click **OK**.

Editing is only enabled for host services that you add manually to the list.

- Optional: Add or edit other host services as needed, then click **Next**.

When you click **Next**, all of the hosts in the list are registered, authorized, and discovered.

- In the Virtual Center Server Details page, select a host service from the list.



- If a virtual center server is not listed for the host service, click **Add** and enter the virtual center server name and credentials, then click **OK**.

- On the Add Storage System page, click **Add** to register a storage system with the DataFabric Manager server.


You must register each storage system with the DataFabric Manager server, so that OnCommand is made aware of the storage system and can monitor it and use it for backup.

- Enter the **IP Address/Name**, **User Name**, and **Password** for the storage system.

The login credentials are validated and set in the DataFabric Manager server. Login credentials are required for backups to work.

- Optional: Modify the NDMP and SNMP settings in the Advanced Options section.

If the NDMP credentials are not set explicitly, then the login credentials are used for NDMP. NDMP credentials are required for backups to work.



11. Click Add.

The credentials are validated and the storage system you added appears in the list of storage systems.

12. Optional: If you need to edit the settings for a storage system, click **Edit**, make the changes, then click **OK**.

13. Optional: Add or edit other storage systems as needed, then click **Next**.

The storage systems for which you set the credentials are pushed to the host service and the systems are added to a default resource pool.

14. When the status screen appears, showing the configuration progress details, click **Finish.**

Result

The configuration wizard implements the following:

- The storage systems are configured in the DataFabric Manager server.
- The storage systems are associated with the selected host service.
- The storage systems are added to a default resource pool.
- A default remote protection storage service is created.

After you finish

You can monitor details of discovered virtual machines, from the Host Services window in the OnCommand console.

Verify that the SQL service is running. This service must be running for DataFabric Manager server database backup and restore operations to succeed.

Configuring the OnCommand Standard edition server with host services

You must configure the host services to communicate with DataFabric Manager server, vCenter Servers, and storage systems that are required for backup and recovery of your data.

Before you begin

You must have installed the following:

- OnCommand Core Package
- OnCommand Host Package
- Adobe Flash Player 10.0 or later
- OnCommand Windows PowerShell cmdlets

About this task

The tasks identified in this configuration process can also be completed after initial installation and configuration. See the OnCommand console Help for information.

During the configuration process, job status and details about jobs can be viewed from the Jobs tab.

After you finish

After completing the configuration process, you can create backups of virtual objects from the Server tab.

Steps

1. [Verifying that a host service is registered with the DataFabric Manager server](#) on page 66
2. [Authorizing a host service to access storage system credentials](#) on page 68
If the host service is not authorized, you must authorize the host service to access the storage system credentials before you can create backup jobs.
3. [Associating a host service with the vCenter Server](#) on page 69
In a VMware environment, you must authorize each host service and associate it with a vCenter Server. This provides part of the communication needed for discovery, monitoring, backup, and recovery of virtual server objects such as virtual machines and datastores.

4. *Verifying communication between the host service and the OnCommand plug-in* on page 72
You can verify that the host service is communicating with the OnCommand Host Service Hyper-V Plug-in or VMware Plug-in by ensuring that virtual machines are associated with the host service. If the host service is not communicating with the plug-in, the software cannot perform backup jobs.
5. *Associating storage systems with a host service* on page 73
For each host service instance, you must associate one or more storage systems that host virtual machines for the host service. This enables communication between the service and storage to ensure that storage objects, such as virtual disks, are discovered and that host service features work properly.
6. *Editing storage system login and NDMP credentials from the Host Services tab* on page 75
You must have valid login and NDMP credentials for storage systems so they can be accessed by the DataFabric Manager server. If the server cannot access the storage, your backups might fail.

Verifying that a host service is registered with the DataFabric Manager server


You must properly register a host service with a DataFabric Manager server before the server can discover objects and before you can perform a backup in a virtual environment.

About this task

A host service can be registered with the DataFabric Manager server during installation, or later from the OnCommand console. However, you might want to verify that the registration is still valid when troubleshooting problems or prior to performing an action involving a host service, such as adding a storage system to a host service.

Steps

1. From the **Administration** menu, select **Host Services**.



The Host Services tab opens.

2. In the **Host Services** list, verify that the name of the host service is listed.

When a host service is registered with the DataFabric Manager server, it displays in the host services list.

3. For the selected host service, verify that the Discovery Status is OK and that the Status is Up.

After you finish

If the host service is not displayed in the list, you must add and configure the new host service.

If the host service Status is other than Up or the Discovery Status is other than OK, edit the host service to provide the correct properties.

Related tasks

[Associating a host service with the vCenter Server](#) on page 69

In a VMware environment, you must authorize each host service and associate it with a vCenter Server. This provides part of the communication needed for discovery, monitoring, backup, and recovery of virtual server objects such as virtual machines and datastores.

Authorizing a host service to access storage system credentials

If the host service is not authorized, you must authorize the host service to access the storage system credentials before you can create backup jobs.

Before you begin

The host service must be registered with the DataFabric Manager server prior to performing this task.


About this task

DataFabric Manager server does not support a host service created as a generic service from failover cluster manager in Microsoft Windows.

Steps

1. From the **Administration** menu, select the **Host Services** option.
2. In the **Host Services** list, select the host service that you want and click **Edit**.

If the host service is not displayed in the list, you must add the host service and verify that it is registered with the DataFabric Manager server.



3. In the **Edit Host Service** dialog box, click **Authorize**, review the certificate, and then click **OK**.

If the Authorize area is unavailable, the host service is already authorized.

When authorization is complete, the Authorize area becomes disabled.

4. Click **OK**.

After you finish

If you do not have storage systems associated with the host service, you must associate at least one storage system to be able to perform backups.

After you finish editing the host service properties, you can view job progress from the Jobs subtab on the Manage Host Services window and you can view details about each job from the Jobs tab.

Associating a host service with the vCenter Server

In a VMware environment, you must authorize each host service and associate it with a vCenter Server. This provides part of the communication needed for discovery, monitoring, backup, and recovery of virtual server objects such as virtual machines and datastores.

Before you begin

The host service must be registered with the DataFabric Manager server prior to performing this task; otherwise, it will not display in the list of available host services.

The following information must be available:

- Name or IP address of the vCenter Server
- User name and password for access to the vCenter Server

About this task

Authorization is required to create backup jobs as it allows the host service to access the storage system credentials.

DataFabric Manager server does not support a host service created as a generic service from failover cluster manager in Microsoft Windows.

Steps

1. From the **Administration** menu, select the **Host Services** option.
2. In the **Host Services** list, select the host service that you want and then click **Edit**.
If the host service is not displayed in the list, you must add the host service and verify that it is registered with the DataFabric Manager server.
3. In the **Edit Host Service** dialog box, click **Authorize**, review the certificate, and then click **OK**.
If the Authorize area is disabled, the host service is already authorized.

Edit Host Service

Name and Properties

IP Address/Name: EXCH20.example.com

Admin Port: 8699

Management Port: 8799

Authorization

Authorize this host service to access storage system credentials. **Authorize**

vCenter Properties

vCenter Name: exch21

User Name: *****

Password: *****

Storage Systems

Associate the storage systems to be managed by the host service.

Associate Edit

Storage System	Login Status (Server)	NDMP Status	Transport Protocol
afile7.example.com	Good	Good	https
afile8.example.com	Good	Good	https
exchfiler3.example.com	Good	Good	https

OK Cancel

4. Enter the vCenter Server properties.

You must specify the hostname or the fully qualified domain name for host service registration. Do not use localhost.

If the properties fields are populated, then a server is already associated with the host service that you selected.

If the vCenter Properties section is not displayed, you might have selected a host service that is installed in an environment other than VMware.

5. Click **OK**.

After you finish

If you do not have storage systems associated with the host service, you must associate at least one storage system to be able to perform backups.

After you finish editing the host service properties, you can view job progress from the Jobs subtab on the Manage Host Services window and you can view details about each job from the Jobs tab.

Related tasks

Verifying that a host service is registered with the DataFabric Manager server on page 66

You must properly register a host service with a DataFabric Manager server before the server can discover objects and before you can perform a backup in a virtual environment.

Adding and registering a host service

Before you can use a VMware or Hyper-V host, you must add the host service and register it with the DataFabric Manager server.

Before you begin

The host service firewall must be disabled for the administration and management ports.

You must be authorized to perform all the steps of this task; your RBAC administrator can confirm your authorization in advance.

Attention: Host services can be registered with only one DataFabric Manager server at a time. Before you register a host service with a new DataFabric Manager server, you must first manually unregister the host service from the old DataFabric Manager server. To unregister a host service you must use the DataFabric Manager server `hsid` command.

About this task

DataFabric Manager server does not support a host service created as a generic service from failover cluster manager in Microsoft Windows.

If you unregister a cluster level host service, DataFabric Manager server does not automatically register the host service when you re-register the node. You must re-register or add the host service using the cluster IP address.

Attention: If you change the name of the machine after installing the OnCommand Host Package, you must uninstall the OnCommand Host Package and perform a fresh installation.

Steps

1. Click the **Administration** menu, then click the **Host Services** option.
2. In the **Host Services** tab, click **Add**.
3. In the **Add Host Service** dialog box, type the IP address or the DNS name of the host on which the host service is installed.
4. If the administrative port has been changed in the host service to something other than the default, type in the changed port number.

This is the port that is used by plug-ins to discover information about the host service.

5. Click **Add**.

Result

The host service is added and registered with the DataFabric Manager server.

Tip: If you see an error stating that the requested operation did not complete in 60 seconds, wait several minutes and then click **Refresh** to see if the host service was actually added.

After you finish

To make the host service fully operational, you might need to authorize the host service. In a VMware environment, you must edit the host service to add the vCenter Server credentials.

Verifying communication between the host service and the OnCommand plug-in

You can verify that the host service is communicating with the OnCommand Host Service Hyper-V Plug-in or VMware Plug-in by ensuring that virtual machines are associated with the host service. If the host service is not communicating with the plug-in, the software cannot perform backup jobs.

About this task

If a host service is communicating with the Hyper-V or VMware plug-in, the virtual machines associated with the host service display in the VMs list on the Server tab.

Steps

1. Select the **Administration** menu and then select the **Host Services** option.
The Manage Host Services window opens.
2. In the Host Services list, identify the name of the host service that you want to validate.
3. Select the **View** menu and then select the **Server** option.
4. In the **Manage Server** window, select either the **VMware VMs** or **Hyper-V VMs** option in the navigation pane.
5. Scroll through the list of virtual machines to see if the VMs related to the host service are listed.
If the virtual machines are listed, the host service is communicating properly with the plug-in.

After you finish

If the virtual machines related to the host service do not display, consult the event logs on the host service system. You can also use the `List-HSResources` PowerShell cmdlet to verify that the host service is properly retrieving the virtual machine list from VMware or Hyper-V.

Associating storage systems with a host service

For each host service instance, you must associate one or more storage systems that host virtual machines for the host service. This enables communication between the service and storage to ensure that storage objects, such as virtual disks, are discovered and that host service features work properly.

Before you begin

If you add a new storage system to associate with the host service, you must have the following storage system information available:


- IP address or name
- Login and NDMP credentials
- Access protocol (HTTP or HTTPS)

About this task

In a VMware environment, if the storage system that you add uses the HTTP protocol but it has SSL enabled, then the host service uses HTTPS to communicate with the storage system. If the storage system that you add uses HTTP protocol and the storage system is not SSL enabled, then the host service uses HTTP to communicate with the storage system.

Steps

1. From the **Administration** menu, select **Host Services**.
2. From the **Host Services** list, select the host service with which you want to associate storage.
In the Storage Systems subtab is a list of storage systems currently associated with the host service you selected.
3. Click **Edit** to associate a new storage system.



The Edit Host Service dialog box opens.

4. In the Storage Systems area, click **Associate**.

Edit Host Service

Name and Properties

IP Address/Name: EXCH20.example.com

Admin Port: 8699

Management Port: 8799

Authorization

Authorize this host service to access storage system credentials.

vCenter Properties

vCenter Name: exch21

User Name: *****

Password: ●●●●●

Storage Systems


Associate the storage systems to be managed by the host service.

Storage System	Login Status (Server)	NDMP Status	Transport Protocol
afile7.example.com	Good	Unknown	https
afile8.example.com	Good	Good	https
exchfiles3.example.com	Good	Good	https

5. Associate the storage systems with the host service, as follows:

- To associate storage systems shown in the Available Storage Systems list, select the system names and click **OK**.
- To associate a storage system not listed in Available Storage Systems, click **Add**, enter the required information, and click **OK**.

The newly associated storage system displays in the Storage Systems area.



6. In the list of storage systems, verify that the status is Good for the login and NDMP credentials for each storage system.

After you finish

If the login or NDMP status is other than Good for any storage system, you must edit the storage system properties to provide the correct credentials before you can use that storage system.

After you finish editing the host service properties, you can view job progress from the Jobs subtab on the Manage Host Services window and you can view details about each job from the Jobs tab.

Editing storage system login and NDMP credentials from the Host Services tab

You must have valid login and NDMP credentials for storage systems so they can be accessed by the DataFabric Manager server. If the server cannot access the storage, your backups might fail.

Before you begin

Have the following storage system information available:

- IP address or name
- Login and NDMP credentials
- Access protocol (HTTP or HTTPS)

Steps

1. From the Administration menu, select **Host Services**.
2. In the **Host Services** list, select a host service.

The storage systems associated with the selected host service display in the Host Services tab.

3. In the **Host Services** tab, select a storage system with login or NDMP status of Bad or Unknown.

The screenshot shows the NetApp OnCommand console interface. The 'Host Services' tab is active, displaying a table of host services. The 'Edit' button is circled in the top left. Below the host services table, the details for the selected host service 'EXCH20.example.com' are shown. A sub-table titled 'Storage Systems' lists associated storage systems. In this sub-table, the 'NDMP Status' for the first storage system 'afiler7.example.com' is circled, showing 'Unknown'.

Name	IP Address	Admin Port	Management Port	Version	Discovery Status	Status
EXCH20.example.com	172.16.224.120	8099	8799	1.0.0.1492	OK	Up

Storage System Name	IP Address	System Status	Login Status (Host Service)	NDMP Status	Login Status (Server)	Transport Protocol
afiler7.example.com	10.225.221.47	Up	Good	Unknown	Good	https
afiler13-b.example.com	10.225.221.54	Up	Good	Good	Good	https

4. Click **Edit**.
5. In the **Edit Host Service** dialog box, click **Edit**.

Edit Host Service

Name and Properties

IP Address/Name: EXCH20.example.com

Admin Port: 8699

Management Port: 8799

Authorization

Authorize this host service to access storage system credentials.

vCenter Properties

vCenter Name: exch21

User Name: *****

Password: *****

Storage Systems

Associate the storage systems to be managed by the host service.

Storage System	Login Status (Server)	NDMP Status	Transport Protocol
afiler7.example.com	Good	Unknown	https
afiler8.example.com	Good	Good	https
exchfiles3.example.com	Good	Good	https

6. Enter the appropriate login and NDMP credentials and click **OK**.
7. In the **Host Services** tab, verify that the Login Status and NDMP Status are Good.
8. Click **OK**.

The storage system status columns in the Host Services tab update with the new status.

After you finish

After you finish editing the storage system properties, you can view job progress from the Jobs subtab on the Manage Host Services window and you can view details about each job from the Jobs tab.

Registering the OnCommand Plug-in for VMware with a vCenter Server

When the registration information for the OnCommand Plug-in for VMware changes, you must register the new server information for the vCenter Server or the DataFabric Manager server to

enable communication between the OnCommand Plug-in for VMware and the vCenter Server or the DataFabric Manager server.

About this task

The registration information that you specified during the installation of the Host Package might change in the following instances:

- If you decide to use a different vCenter Server than the one that you registered on the Plug-in Service and vCenter Server Information page of the installer.
- If a host service is already registered with the DataFabric Manager server and you install a new vCenter Server with a different IP address.
- If you did not specify the server credentials for the DataFabric Manager server on the Configure DataFabric Manager page of the installer.

You can only register one application (either the OnCommand Plug-in for VMware or the Virtual Storage Console) per vCenter Server. Because you can register only one application, you must either uninstall or disable Virtual Storage Console 2.x if you install the OnCommand Plug-in for VMware on the same system as the Virtual Storage Console.

Steps

1. On the system on which the Host Package is installed, specify the following URL in the browser address field:

```
https://localhost:8143/Register.html
```

2. In the Plugin service information section, select the IP address that the vCenter Server uses to access the OnCommand Plug-in for VMware.

Note: This IP address must be accessible from the vCenter Server. If you installed the OnCommand Plug-in for VMware on the same computer as the vCenter Server, this might be the same address that you use to access the vCenter Server.

3. Type the host name or IP address of the vCenter Server and the user credentials for the vCenter Server.

Note: You must have administrator privileges to register the OnCommand Plug-in for VMware with the vCenter Server. The administrator name is only required for registering the plug-in.

4. Type the host name or IP address of the DataFabric Manager server.
5. Click **Register**.

How to manually transition SnapManager for Hyper-V dataset information

You can use the stand-alone SnapManager for Hyper-V software to view your dataset protection schedules so that you can use them as a reference when adding and editing Hyper-V datasets in the OnCommand console.

You can still use the dataset and backup policies that you created using SnapManager for Hyper-V to protect your data until you have fully transitioned to the OnCommand console. As you create new datasets and protection schedules in the OnCommand console, you can begin deleting your protection policies in SnapManager for Hyper-V.

After you create a dataset and protection schedule in the OnCommand console, you should not use SnapManager for Hyper-V to back up the same virtual machines. If you use overlapping schedules for the same virtual machines, the backups might fail, because only one VSS backup can run at a time on a host. SnapManager for Hyper-V does not automatically delete old backups after you disable the protection policy, so you must manually delete them when they are no longer necessary.

You can also use SnapManager for Hyper-V backups to restore virtual machines until the retention policies have timed out. You should not restore the same virtual machines in SnapManager for Hyper-V and the OnCommand console at the same time. If you do so, the restore operation might fail.

After you transition all of your datasets and protection schedules to the OnCommand console, you can safely uninstall SnapManager for Hyper-V.

Determining whether a storage system belongs to a workgroup or a domain

The storage system that you use for the OnCommand Core or Host Package installation must belong to a domain rather than a workgroup. Prior to installing the Core or Host Packages, you must determine if the system belongs to a workgroup or a domain.

Step

1. Right-click **My Computer** and click **Properties** and the **Computer Name** tab.

For details, see the documentation for your Windows operating system.

The Computer Name tab displays either a Workgroup label or a Domain label.

Updating the SnapDrive for Windows service account

If you installed SnapDrive for Windows using a different user account than the user credentials for the OnCommand Host Package, you can manually change the SnapDrive service credentials to the ones that you used for the Host Package installation.

Steps

1. On the Windows server where you installed the Host Package, navigate to the Windows Control Panel and select **Administrative Tools > Services**.

For details, see the documentation for your Windows operating system.

2. Right-click the SnapDrive for Windows service and select **Properties** from the drop-down menu.
3. Type the new user credentials for the SnapDrive service.
4. Click **OK**.

Adding port exceptions to Windows Firewall

When you install the OnCommand Host Package in a Hyper-V environment, you must manually add port exceptions to the Windows Firewall that is specific to the Hyper-V plug-in service.

Steps

1. On the Windows server where you are going to install the Host Package, navigate to the Windows Control Panel and select **Control Panel > Windows Firewall**.

For details, see the documentation for your Windows operating system.

2. Click the **Exceptions** tab, and then click **Add Port**.
3. Type a name for the port exception in the **Name** field.
4. Type the port number that you want to add to the exceptions list in the **Port number** field.
5. Click either **TCP** or **UDP**, and then click **OK**.

After you finish

If the Windows Firewall is enabled on your host, you need to configure it to allow SnapDrive for Windows communications. See the *SnapDrive Installation and Administration Guide* for more information.

Regenerating an SSL certificate for the OnCommand Host Package

A self-signed certificate is generated during the installation of the OnCommand Host Package. You can change the keystore and private key passwords, which regenerates the SSL certificate and Java keystore for the Host Package.

Before you begin

- You must run the command from the VMware UI Plug-in installation root directory at `C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin`.

Steps

1. Connect to the Windows console session or the Windows PowerShell console.
2. Type the command `bin\nvpf ssl setup` to regenerate the SSL certificate.

If necessary, you are prompted for the keystore and private key passwords.

After you finish

- You must secure the `etc\keystore.properties` file and then restart the OnCommand Plug-in for VMware service.
- You can review and accept the SSL certificate after the vSphere Client receives the certificate when you click the NetApp icon in the vSphere Client.
You can then import the SSL certificate into the Trusted Root Certification Authorities store to prevent the SSL security warnings from appearing every time you launch the vSphere client. For details, see the documentation for your Windows operating system.

Using a certificate signed by a certificate authority

You can use the self-signed certificate generated during the installation of the OnCommand Host Package. This certificate enables you to transfer encrypted data, however, when you provide your own certificate authority (CA), this ensures that the certificate is unique for your environment.

Steps

1. Stop the OnCommand Plug-in for VMware or NetApp vSphere Plugin Framework service by opening the Services dialog box via the Windows start menu prior to installing the Host Package.
2. Generate a new keystore file by answering the certificate questions.
3. If there is not a `conf` directory, create one. Then, change the directory to `C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\jre\bin` and type `C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\jre\bin>keytool.exe -genkey -alias replaceWithHostnameOrIP -keystore C:\Program Files\NetApp`

\OnCommand Host Package\VMware UI Plugin\conf\nvpf.keystore, where replaceWithHostnameOrIP is the hostname or IP address used on the certificate.

4. Create a new certificate request to send to the certificate authority and type `C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\jre\bin>keytool.exe -certreq -alias replaceWithHostnameOrIP -keystore "C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\conf\nvpf.keystore" -file "C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\conf\myNewCertRequest.csr`, where replaceWithHostnameOrIP is the hostname or IP address used on the certificate.
5. Move the signed certificate and the CA certificate files to the `C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\conf\` directory.
6. Import the CA certificate into the keystore by typing `C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\jre\bin>keytool.exe -import -trustcacerts -alias root -file "C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\conf\meCACert.crt" -keystore "C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\conf\vsc.keystore`.
7. Import the signed certificate by typing `C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\jre\bin>keytool.exe -import -trustcacerts -alias replaceWithHostnameOrIP -file "C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\conf\newSignedCert.crt" -keystore "C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\conf\nvpf.keystore`, where replaceWithHostnameOrIP is the hostname or IP address used on the certificate.
8. Copy the `conf\nvpf.keystore` file to the `etc\nvpf.keystore` file.
9. Configure OnCommand Host Package VMware UI Plugin to use the new keystore with the CA signed certificate by opening a console window and navigating to `C:\Program Files\NetApp\OnCommand Host Package\VMware UI Plugin\etc\`.
10. Create a new file called `keystore.properties` and type `http.ssl.keystore.file=etc/nvpf.keystore`
`http.ssl.keystore.password=replaceWithPassword`
`http.ssl.key.password=replaceWithPassword`.
11. Create or modify the `nvpf.override` file and add `http.ssl.keystore.properties=etc/keystore.properties`.
12. If you use hostname instead of an IP address, add `server.host=replaceWithHostname` to the `nvpf.override` file.
13. Restart the OnCommand Plug-in for VMware or NetApp vSphere Plugin Framework service by opening the Services dialog box via the Windows start menu prior to installing the Host Package.

Certificate-based authentication

Connecting DataFabric Manager server to a virtual or cloud infrastructure network using certificate-based authentication means that authentication occurs using an SSL certificate. Using the certificate makes the requirement for user names or passwords unnecessary.

Certificate-based authentication occurs when a client, such as the host service or cloud orchestration tool, connects to the DataFabric Manager server with a Web service or ZAPI request. The client presents a self-signed certificate to DataFabric Manager server. In turn, DataFabric Manager server accepts the certificate, validates the certificate, and processes the request if it authenticates the client.

Certificate information

An SSL certificate is a digital document whose legitimacy is signed off by its creator. The certificate is used to verify that a key belongs to an individual or organization.

When you install DataFabric Manager server or the host service, the truststore contains no certificates to trust. You must add client certificates to the truststore before DataFabric Manager server will trust those client connections.

By default, the DataFabric Manager server installs the DataFabric Manager server key and certificate pair, and any trusted certificates in a repository called the DataFabric Manager server truststore

When DataFabric Manager server is installed, it is configured to not trust any public certificate authorities (CAs). If you want DataFabric Manager server to trust clients with certificates signed by a public CA, you must add the root CA certificate to the truststore.

Certificates are identified in the Windows Trusted Root Certification Authorities store with the following titles in the Issued To and Issued By columns:

- DataFabric Manager - VIM
- DFM Host Services for VIM
- DFM Plugin for VIM

Managing certificates for cloud service clients

You can manage certificates on your DataFabric Manager server for clients in a cloud infrastructure network, including generating a key and a self-signed certificate, adding certificates to a truststore, listing all certificates in a truststore, displaying details of certificates in a truststore, removing a certificate from a truststore, and disabling certificate-based authentication.

Generating a key and self-signed certificate

You can generate a key and certificate pair by using the `dfm ssl service setup` command.

Steps

1. On the DataFabric Manager server, open a console session.
2. Enter the following command:

```
dfm ssl service setup -f  
command.
```

The `-f` option causes the command to overwrite existing key and certificate pairs.

3. To force the DataFabric Manager server to immediately use the newly generate key, enter the following command: `dfm ssl service reload`.

Adding a certificate in the truststore

You can add certificates in the DataFabric Manager server truststore for clients in a cloud infrastructure network by using the `dfm ssl service truststore add` command. The certificate must be in pem format.

Steps

1. On the DataFabric Manager server, open a console session.
2. Enter the following command:

```
dfm ssl service truststore add -f cacert.pem  
.
```

The `-f` option installs adds the certificates without prompting you for permission.

Removing a certificate from the truststore

You can remove a cloud service client certificate from the DataFabric Manager server truststore by using the `dfm ssl service truststore remove` command.

Steps

1. On the DataFabric Manager server, open a console session.
2. Enter the following command:

```
dfm ssl service truststore remove certificate_number  
.
```

Displaying a list of certificates in a truststore

You can use the DataFabric Manager server command-line interface to display a list of all the certificates in a truststore. You might do this if you want to determine how long a certificate is valid,

to find information about the certificate's issuer, or to locate the certificate number assigned to specific certificate.

Steps

1. On the DataFabric Manager server, open a console session.
2. Enter the following command:

```
dfm ssl service truststore list
```

Displaying details about certificates in a truststore

You can display the details about one certificate or about all certificates in a truststore. Details displayed include certificate serial number, signature algorithm, issuer, valid from and valid to dates, and public key algorithm.

Steps

1. On the DataFabric Manager server, open a console session.
2. Enter the following command: **dfm ssl service truststore detail *certificate number***.

certificate number displays details for a specific certificate in a truststore.

Use the `dfm ssl service truststore list` command to find certificate numbers.

Showing the contents of the DataFabric Manager server key and certificate file

You display the contents of a key and certificate file by using the DataFabric Manager server command-line interface. The key and certificate file contents are displayed in hexadecimal format.

Steps

1. On the DataFabric Manager server, open a console session.
2. Enter the following command:

```
dfm ssl service show -c -k -f -o output
```

`-c` selects the certificate for printing; `-k` selects the key for printing; `-o` saves the information to a file; `-f` overwrites the file without prompting.

Displaying DataFabric Manager server certificate details

You can display the DataFabric Manager server certificate details, including the certificate serial number, valid to and valid from dates, and signature algorithm.

Before you begin

The system date and time must be correct on the system where DataFabric Manager server is installed before you check the certificate details; otherwise, the Not Before and Not After dates might display incorrectly in the command output.

Steps

1. On the DataFabric Manager server, open a console session.
2. Enter the following command:

```
dfm ssl service detail -f -o outputfile
```

`-f` overwrites the file without prompting; `-o` saves the information to a file.

Disabling certificate-based authentication

DataFabric Manager server uses certificate-based authentication by default to authenticate clients in a cloud infrastructure network. You can disable this feature, however, so that clients cannot use a root certificate to connect to the DataFabric Manager server. You might want to disable certificate-based authentication when you know a certificate is expiring or you are replacing a certificate.

Steps

1. On the DataFabric Manager server console, open a the command-line interface.
2. Enter the following command:

```
dfm option set serverCertAuthEnabled=No
```

Managing certificates for host services clients

You can manage certificates for host services clients on your DataFabric Manager server, including registering certificates, authorizing certificates, unregistering certificates, and displaying certificate information for a specific host service.

Authorizing a host service certificate

When you register a new host service with DataFabric Manager server, you must manually authorize the authentication certificate so that requests from the host service to DataFabric Manager server are successful.

Steps

1. Enter the following command from a DataFabric Manager server console session:

```
dfm hs list
```

The host requesting authorization is listed with the status "Authorization Pending".

2. Record the ID number of the host requiring authorization.

The host ID is located in the first column of the list output.

3. Using the ID number you recorded in Step 2, enter the following command:

```
dfm hs authorize ID number
```

You are asked whether you authorize the host service to use this DataFabric Manager server.

4. Enter *y* to authorize the host service certificate.

Migrating certificates, keys, and truststores manually

During DataFabric Manager server database backups, the directories containing certificates, keys, and truststores for both cloud service clients and host service clients are not backed up. If you want to restore database backups to a different DataFabric Manager server, you must manually migrate the certificates, keys, and truststore directories or the restore fails.

About this task

This procedure is not required when you back up and restore the database to the same DataFabric Manager server.

Steps

1. On the DataFabric Manager server you want to migrate, back up the database.
2. On the DataFabric Manager server you just backed up, copy the following three folders from the `\DataFabric Manager install directory\conf\keys\` directory:
 - `certs`
 - `private_keys`
 - `truststore`
3. Restore the database to the new DataFabric Manager server.

4. Copy the three folders from the original DataFabric Manager server to the same directory on the destination DataFabric Manager server.
5. Perform one of the following actions, depending on which type of clients you are migrating:
 - If you migrate clients in a cloud infrastructure, after the migration, generate a new DataFabric Manager server certificate on the destination DataFabric Manager server by entering `dfm ssl service setup`, and then load the new certificate by entering `dfm ssl service reload`

Note: If you do not generate a new certificate, the new DataFabric Manager server will load the certificate that was migrated from the original DataFabric Manager server causing DataFabric Manager server hostname validation to fail on cloud service clients.
 - If you are migrating host service clients, after the migration, unregister the host service and then register the new host service from the Host Services tab in the OnCommand console.

Related tasks

Verifying that a host service is registered with the DataFabric Manager server on page 66

You must properly register a host service with a DataFabric Manager server before the server can discover objects and before you can perform a backup in a virtual environment.

Upgrading to the OnCommand Core and Host Packages

You can upgrade to the OnCommand Core or Host Packages to use the monitoring tools and dashboards of the OnCommand console instead of reinstalling previous versions of DataFabric Manager server, Virtual Storage Console (VSC), Rapid Cloning Utility (RCU), SnapManager for Virtual Infrastructure (SMVI), or SnapManager for Hyper-V (SMHV).

Upgrading to the OnCommand Core Package on Windows

If you have a previous version of the DataFabric Manager server running on your system, you can upgrade to the Standard edition of the server by installing the OnCommand Core Package.

Before you begin

- The system that you use for your Core Package installation must belong to a domain rather than a workgroup.
- You must have administrator privileges for the Windows computer on which you are installing the Core Package.
- You must have the following items:
 - DataFabric Manager server license key
 - Credentials for network access
 - The IP address of the server on which you are installing the software
 - Directory path where you want to install, if different from the default location

If you are upgrading to the OnCommand Core Package while also migrating to a new system, it is recommended that you use the original DataFabric Manager server installation path to avoid errors caused by path setting option changes for DataFabric Manager server databases.

For example, if the original installation path is `C:\Program Files (x86)\NetApp\DataFabric Manager`, use that and not the new default path `C:\Program Files\NetApp\DataFabric Manager`.

About this task

You can only upgrade to the Standard edition of the DataFabric Manager server.

The installation software automatically detects and stops any DataFabric Manager server services that are running on the system.

Steps

1. Start the Core Package installation wizard.

2. Review and accept the license and AutoSupport agreements.

You cannot install the Core Package unless you accept the license agreement.

3. Accept the default installation location or enter the folder location where you want to install the software.
4. When prompted, confirm if you want the database backed up.

Backing up the database can take several minutes to many hours, depending on the size of your database.

Attention: If you do not back up the database, you will lose your data.

5. Review the summary screen and consider whether you want to make changes before completing the install process, then click **Install**.
6. When the Installation Complete screen appears, click **Next** to continue.
7. Click **Finish** to close the wizard.

After you finish

- When you finish installing the Core Package, you can install the Host Package and use the configuration wizard to configure a host service.
- You should clear the browser cache before you first launch the OnCommand console and when upgrading to a new version of the software.

Related tasks

[Downloading the OnCommand Core Package](#) on page 41

[Installing the OnCommand Core Package on Windows](#) on page 42

[Determining whether a storage system belongs to a workgroup or a domain](#) on page 79

Upgrading to the OnCommand Core Package on Linux

If you have a previous version of the DataFabric Manager server running on your system, you can upgrade to the Standard edition of the server by installing the OnCommand Core Package.

Before you begin

- If you have a large database, you might prefer to back it up prior to starting the setup wizard.
- You must have administrator privileges for the Windows computer on which you are installing the Core Package.
- You must have the following items:
 - DataFabric Manager server license key
 - Credentials for network access

- The IP address of the server on which you are installing the software
- Directory path where you want to install, if different from the default location

About this task

The installation software automatically detects and stops any DataFabric Manager server services that are running on the system.

Step

1. To upgrade OnCommand Core Package on your Linux system, run the setup file:

- For 32-bit systems, choose `occore-setup-5-0-linux.sh`
- For 64-bit systems, choose `occore-setup-5-0-linux-x64.sh`

The installation begins.

Related tasks

[Downloading the OnCommand Core Package](#) on page 41

[Installing the OnCommand Core Package on Linux](#) on page 44

Upgrading to the OnCommand Host Package in a VMware environment

When you upgrade to the OnCommand Host Package from a previous version of SnapManager for Virtual Infrastructure (SMVI), the DataFabric Manager server uses a host service to discover and monitor virtual objects such as virtual machines or datastores for the Backup and Recovery capability. You do not need to connect to the DataFabric Manager server if you are upgrading from a previous version of Virtual Storage Console (VSC) or the Rapid Cloning Utility (RCU).

Before you begin

- The system that you use for your Host Package installation must belong to a domain rather than a workgroup.
- You must have administrator privileges for the Windows computer on which you are installing the Host Package.
- The DNS name of the Windows computer on which you are installing the Host Package must match the actual computer name and the computer name cannot be more than 15 characters.
- You must back up the `smvi.override` file from the previous installation directory if you are upgrading from SMVI 1.x, SMVI 2.x, or VSC 2.0 to OnCommand.
- The Windows firewall must be set to allow exceptions.
- You must stop the Server Manager administrative tool on Windows 2008 systems.
- If there is an existing VSC 2.x installation on a different system but registered to the same vCenter Server, an error message appears that the VSC software is already registered.

You must stop the OnCommand Plug-in for VMware or NetApp vSphere Plugin Framework service by opening the Services dialog box via the Windows start menu.

- You must stop any service or process that is using the same Java Runtime Environment (JRE) that is installed with the Host Package.
- VSC 1.x, RCU, and SMVI extensions must be uninstalled from the vCenter Server.
- You must have the following items available:
 - A Windows system account user name and password
 - A Host Package install location if not the default
 - The IP address, user name, and password of the DataFabric Manager server
 - The IP address, user name, and password of the vCenter Server

About this task

If you are installing the Host and Core Packages on the same system, a fully qualified domain name must be used for the Core Package instead of *localhost*.

The installer creates a locks directory, which is used to coordinate access to resources in the vSphere Client. The locks directory is located within the OnCommand directory. You must not change the name or the location of this directory.

The IP address and host name for the system on which you are installing the Host Package must have a DNS registration that resolves properly between the host service and the DataFabric Manager server.

You should use a dedicated Windows server for each vCenter Server instance. Having other applications installed on the same server can take up valuable system resources and might drastically reduce performance.

If you want to revert to an earlier version of VSC, RCU, or SMVI after installing the Host Package, you must uninstall the Host Package prior to installing the earlier version of VSC, RCU, or SMVI.

If the installer fails during the installation of the Host Package, the installer does not rollback the changes made to the system. You must manually remove the Host Package using the Control Panel application for your operating system and then delete the folder where the Host Package was installed.

Steps

1. Double-click the executable file to launch the OnCommand Host Package installer:
 - For 32-bit systems, click `ochost-setup-1-0-x86.exe`.
 - For 64-bit systems, click `ochost-setup-1-0-x64.exe`.
2. Depending on your operating system, you must either install Windows PowerShell or enable it before you can continue with the installation of the Host Package.

Note: An error message appears if PowerShell is not installed. PowerShell 1.0 is required but PowerShell 2.0 is recommended.

- On Windows Server 2008 R2, PowerShell is installed by default and you do not need to enable it on the server.
- On Windows Server 2008, PowerShell is not installed by default and you must enable it on the server after it is installed.
To enable PowerShell, follow the instructions in the pop-up dialog box.

- On Windows Server 2003 or 2003 R2, you must download and install PowerShell.

3. Select the installation location.
4. On the Virtual Infrastructure Options page, click **VMware** if it is not selected by default.
5. On the Service Credentials page, type the user name and password for the system on which you are installing the Host Package.

You must type the user name in the following format:

domain name\user name

6. On the Configure Communication Ports page, type the port numbers that you want to use or accept the default port numbers.

Note: For custom firewalls, ensure that the Core and Host Packages are using the same port numbers.

7. On the Configure DataFabric Manager server page, type the IP address and the user name and password used to access DataFabric Manager server.

If you want to monitor your virtual environment or use the Backup and Recovery capability, you must type the credentials for the DataFabric Manager server. You can skip the validation of the DataFabric Manager server if you do not have the server credentials available or if you are going to use only the Monitoring and Host Configuration or Provisioning and Cloning capabilities of the OnCommand Plug-in for VMware.

8. On the Plug-in Service and vCenter Server Information page, provide the following information:
 - a. Type the admin IP address of the system on which you are installing the Host Package.
 - b. Type the host name or IP address of the system on which the vCenter Server is installed and the user name and password that allows the vSphere Client to communicate with the vCenter Server.

9. Click **Install** on the summary page, and then click **Finish**.

When you next reboot the system, you might see some hidden MS-DOS command windows briefly appear in the background during the removal of installer support files that could not be deleted during the installation of the Host Package.

10. If you have RCU 3.0 installed on your system, click **Yes** on the confirmation prompt to uninstall the application.

After you finish

- During the installation process, the installer creates some temporary folders that are automatically deleted when you next reboot the system.
You can delete these folders without adversely affecting the installation of the Host Package.
- The host service must be configured to perform backups.
You must associate storage systems with a host service when you complete the installation of the Host Package. If you selected the OnCommand Express edition during the installation of the Core Package, you can use the configuration wizard to configure the host service. If you selected the Standard edition, you must configure the host service from the Host Services tab accessible from the Administration menu of the OnCommand console.
- You must copy any changes that were made in the previous `smvi.override` file to the new `smvi.override` file that is installed with the Host Package.

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

[Installing the OnCommand Host Package in a VMware environment](#) on page 52

[Determining whether a storage system belongs to a workgroup or a domain](#) on page 79

Related references

[Required ports for the Host Package](#) on page 38

Upgrading to the OnCommand Host Package in a Hyper-V environment

When you upgrade to the OnCommand Host Package from a previous version of SnapManager for Hyper-V, the DataFabric Manager server uses a host service to discover and monitor virtual objects such as virtual machines.

Before you begin

- You must use the same user account as the SnapDrive for Windows service to install the Host Package.
- The system that you use for your Host Package installation must belong to a domain rather than a workgroup.
- You must have administrator privileges for the Windows computer on which you are installing the Host Package.
- The Windows firewall must be set to allow exceptions.
- You must stop the Server Manager administrative tool on Windows 2008 systems.
- If SnapDrive for Windows is already installed on the system and RBAC is enabled, the `AccessControl.xml` file, which is in the root volume of the storage system, must be deleted from the storage system.

- You must stop the SnapDrive for Windows service if SnapDrive for Windows or SnapManager for Hyper-V is already installed on the system.
- You must have the following items available:
 - A Windows system account user name and password
 - A Host Package install location if not the default
 - The IP address, user name, and password of the DataFabric Manager server

About this task

If you are installing the Host and Core Packages on the same system, a fully qualified domain name must be used for the Core Package instead of *localhost*.

If the Hyper-V parent is part of a cluster, you must install the Host Package on each node of the cluster and all the cluster nodes must share the same TCP/IP port to enable communication between host services on different nodes. You must register and authorize each node with the same DataFabric Manager server.

The IP address and host name for the system on which you are installing the Host Package must have a DNS registration that resolves properly between the host service and the DataFabric Manager server.

Steps

1. Double-click the `ochost-setup-1-0-x64.exe` file to launch the OnCommand Host Package installer.
2. Depending on your operating system, you must either install Windows PowerShell or enable it before you can continue with the installation of the Host Package.

Note: An error message appears if PowerShell is not installed. PowerShell 1.0 is required but PowerShell 2.0 is recommended.

- On Windows Server 2008 R2, PowerShell is installed by default and you do not need to enable it on the server.
- On Windows Server 2008, PowerShell is not installed by default and you must enable it on the server after it is installed.

To enable PowerShell, follow the instructions in the pop-up dialog box.

3. Select the installation location.
4. On the Virtual Infrastructure Options page, click **Hyper-V** if it is not selected by default.
5. On the Service Credentials page, type the user name and password for the system on which you are installing the Host Package.

You must type the user name in the following format:

`domain name\user name`

6. On the Configure Communication Ports page, type the port numbers that you want to use or accept the default port numbers.

Note: For custom firewalls, ensure that the Core and Host Packages are using the same port numbers.

7. On the Configure DataFabric Manager server page, type the IP address and the user name and password used to access DataFabric Manager server.

You can skip the validation of the DataFabric Manager server at this point if you do not have the server credentials available.

8. Click **Install** on the summary page, and then click **Finish**.

When you next reboot the system, you might see some hidden MS-DOS command windows briefly appear in the background during the removal of installer support files that could not be deleted during the installation of the Host Package.

After you finish

- During the installation process, the installer creates some temporary folders that are automatically deleted when you next reboot the system.
You can delete these folders without adversely affecting the installation of the Host Package.
- From the Hyper-V host on which the Host Package and SnapDrive for Windows is installed, ensure that you can ping the storage system containing the virtual objects.
If you cannot ping the storage system from the Hyper-V host, you must add the system to the etc \hosts file on the Hyper-V host. Otherwise, your backup and restore operations might not complete successfully.
- The host service must be configured to perform backups.
You must associate storage systems with a host service when you complete the installation of the Host Package. If you selected the OnCommand Express edition during the installation of the Core Package, you can use the configuration wizard to configure the host service. If you selected the Standard edition, you must configure the host service from the Host Services tab accessible from the Administration menu of the OnCommand console.

Related tasks

[Downloading the OnCommand Host Package](#) on page 51

[Installing the OnCommand Host Package in a Hyper-V environment](#) on page 55

[Determining whether a storage system belongs to a workgroup or a domain](#) on page 79

[Updating the SnapDrive for Windows service account](#) on page 80

[Adding port exceptions to Windows Firewall](#) on page 80

Related references

[Required ports for the Host Package](#) on page 38

Upgrade issues with DataFabric Manager 3.8 or earlier

You can upgrade to OnCommand management software from previous versions of the DataFabric Manager server. However, due to changes in system behavior between releases, you might have to resolve issues before upgrading.

The following issues are associated with upgrading to OnCommand Core Package 5.0 from DataFabric Manager versions 3.8 and earlier. Issues associated with upgrading from DataFabric Manager server 4.0 or later to OnCommand Core Package are covered in the requirements and installation instructions throughout this guide and in the *Core Package Release Notes*.

Supported methods to upgrade from Windows 2000 to Windows Server 2003

DataFabric Manager 3.7 or later does not support Windows 2000. Therefore, you must upgrade your server operating system to Windows Server 2003 before you upgrade to DataFabric Manager 3.7 or later. If you currently run DataFabric Manager software on Windows 2000, upgrade to DataFabric Manager 3.0.1 or later and then upgrade the operating system to Windows Server 2003.

If you have Windows Server 2003 already installed on another system, install DataFabric Manager 3.7 or later on it, and then migrate the database from the Windows 2000 system.

For information about database backup, see the section on setting up the DataFabric Manager database backup in the *Operations Manager Administration Guide*. For information about migrating the database, see the manual (man) page for the `dfm datastore setup <dfm-data-dir>` command.

Supported methods to upgrade from Solaris to Windows or Linux

DataFabric Manager 3.8 and later does not support Solaris. Therefore, you must migrate the DataFabric Manager database on Solaris to a server running Windows or Linux before you upgrade to DataFabric Manager 3.8 or later.

You can migrate the database by creating an archive copy of the backup by using the `dfm backup create <backup_filename>` command, then restore the database by using the `dfm backup restore <backup_filename>` command.

Upgrading from DataFabric Manager 3.7.1

If you have created custom reports with GUILink and SecureGUILink as fields in DataFabric Manager 3.7.1 or earlier, upgrading to DataFabric Manager 3.8 or later causes the `dfm report view` command to fail. You must open the custom report in Operations Manager and save the report to view it.

Upgrading from DataFabric Manager 3.7 on Linux

If you are upgrading from DataFabric Manager 3.7 to DataFabric Manager 3.8 or later on Linux, the upgrade might fail with the following notification:

```
rpm: /opt/NTAPdfm/lib/libgcc_s.so.1: version `GCC_4.2.0' not found
(required by /usr/lib/libstdc++.so.6)
```

You can resolve this issue by deleting the entry `/opt/NTAPdfm/lib` from the environment variable `LD_LIBRARY_PATH`.

Upgrading from DataFabric Manager 3.7 or earlier

If you are upgrading from DataFabric Manager 3.7 or earlier to DataFabric Manager 3.8 or later, you must delete the existing Data Source Name (DSN) entry for the Adaptive Server Anywhere 9.0 driver and create a new DSN entry for SQL Anywhere 10.

Upgrading from DataFabric Manager 3.5 or earlier

If you are upgrading from DataFabric Manager 3.5 or earlier to DataFabric Manager 3.6 or later, it takes a long time to upgrade the performance data files (data of 20 GB or more). The length of time depends on the platform used. The space used by the performance data files increases by about 65% during the upgrade.

Upgrading from DataFabric Manager 3.2 or earlier

Because of database schema changes, you might experience a delay of several minutes to a few hours when upgrading from DataFabric Manager 3.2 or earlier.

The time required to perform the upgrade depends on the size of the database, the amount of history in the database, the CPU speed, and the I/O throughput of the system. The following processes might require a lot of time:

- Merging rotating history tables
- Populating history tables
- Populating volume history tables
- Populating aggregate history tables
- Reloading the database into the latest file format (at the end of upgrade)

Upgrading from DataFabric Manager 3.1

After an upgrade from DataFabric Manager 3.1, Last Backup Status of All Primary Directories in Storage Systems under the Backup Manager tab is shown as unknown.

This issue is resolved after DataFabric Manager runs a backup job for the relationship.

Upgrading from DataFabric Manager 2.1 or earlier, on Windows

Because of a database upgrade that is no longer supported on a Windows platform, you must first upgrade to DataFabric Manager 2.2 or later (up to DataFabric Manager 3.2) before you upgrade to DataFabric Manager 4.0.

Windows installation path for DataFabric Manager

Upgrading to DataFabric Manager 3.6 or later	<p>Following are the default installation paths for various versions of DataFabric Manager:</p> <ul style="list-style-type: none"> • DataFabric Manager 3.8 through 4.0.1 on Windows 32-bit platform: C:\Program Files\NetApp\DataFabric Manager 64-bit platform: C:\Program Files (x86)\NetApp\DataFabric Manager • DataFabric Manager 3.6 or later (up to 3.7.1): C:\Program Files\NetApp\DataFabric • Versions earlier than DataFabric Manager 3.6: C:\Program Files\Network Appliance\DataFabric
---	---

Windows Server 2003 default browser security setting recommendations

After Windows Server 2003 is installed, the default security setting for the browser is “high.” This setting can cause the browser to block certain actions that can interfere with your DataFabric Manager upgrade.

To ensure the best browsing experience when using DataFabric Manager, you might need to adjust your browser security setting to “medium.”

Installing DataFabric Manager in a custom Linux directory

If you used the `-d <new directory>` command to install DataFabric Manager 3.2 or earlier in a custom directory, the DataFabric Manager software was installed in an NTAPdfm directory that was automatically created within the new directory you specified.

If you use the `-d <new directory>` command to install DataFabric Manager 3.3 or later in a custom directory, DataFabric Manager is installed in the new directory you specify; no additional NTAPdfm directory is created.

Viewing dynamic data

To use Disaster Recovery, the browser that you use to view Operations Manager must support Java applets.

Conversion of group names from DataFabric Manager 3.1 or earlier

The naming convention for hierarchical groups uses the forward slash character (/) as a separator between levels in the hierarchy. If you upgrade from DataFabric Manager 3.1 or earlier, any group that uses the forward slash character in its name is renamed so that the group is not mistaken for a subgroup in a hierarchy.

Each forward slash character is replaced by a hyphen character (-). If the new name is already in use by another group, DataFabric Manager adds an increasing numeric suffix to the name until an unused name is derived. For example, DataFabric Manager would try to rename group apple/orange to

appleorange, then to apple-orange1, then to apple-orange2, and so on, until an unused group name is found.

Upgrade considerations for configuration groups

After upgrading from DataFabric Manager 3.1 or earlier, some administrators of configuration resource groups might gain additional privileges through inheritance. Before upgrading, review the privileges for group hierarchies that include configuration resource groups and make adjustments as necessary.

Uninstalling the OnCommand Core and Host Packages

If you are no longer using the package or need additional space, it might be necessary to uninstall and remove packages. When you uninstall the OnCommand Core or Host Package from your system, the installer automatically removes all components.

Uninstalling the OnCommand Core Package on Windows

You can uninstall the OnCommand Core Package using the Control Panel application for your operating system.

Before you begin

- Before uninstalling the software, ensure there are no dependencies on it because the wizard uninstalls all associated components.

Steps

1. On the Windows server where you installed the Host Package, navigate to the Windows Control Panel and select **Control Panel > Add/Remove Programs** (Windows Server 2003) or **Control Panel > Programs and Features** (Windows Server 2008).

For details, see the documentation for your Windows operating system.

2. Scroll through the list of installed programs to find the program that you want to remove.
3. Click the program you want to uninstall, then click **Uninstall/Change** or **Change/Remove** depending on your operating system.

The NetApp install wizard opens.

4. Select **Remove**, then click **Next**.
5. Click **Uninstall**.
6. If requested, reboot the system.

A system reboot is required when, during the uninstall process, the `\DataFabric Manager\DFM` program directory is not moved to a new directory. The new directory is created with a name that indicates the date and time you performed the uninstall; for example, `\DataFabricManager\DFM-20110622140520\`, which specifies that the OnCommand Core Package was uninstalled on June 22, 2011, at 2:05:20 PM. When this uninstall directory is not created, you must reboot to complete the uninstall process, and before you can perform a fresh install of the OnCommand Core Package.

Related tasks

[Installing the OnCommand Core Package on Windows](#) on page 42

Uninstalling the OnCommand Core Package on Linux

You can use the command `rpm -e` to uninstall the OnCommand Core Package on Linux.

Before you begin

- Before uninstalling the software, ensure there are no dependencies on it because the uninstall wizard uninstalls all associated components.

Step

1. At the command prompt, type the command to uninstall the OnCommand Core Package. For example, `rpm -e NTAPdfm`.

The software automatically uninstalls.

Related tasks

[Installing the OnCommand Core Package on Linux](#) on page 44

Uninstalling the OnCommand Host Package in a VMware environment

You can uninstall the OnCommand Host Package from your system using the Control Panel application for your operating system. When you uninstall the Host Package in a VMware environment, you cannot select which OnCommand Plug-in for VMware capabilities you want to uninstall, because the entire application is removed. When you uninstall the Host Package, the host service does not unregister from the DataFabric Manager server.

Before you begin

- You must save any files that contain data such as local backups, scheduled jobs, or datasets. You can find these files in the installation folder. The uninstall process removes all Host Package files.
- You must stop any service or process that is using the same Java Runtime Environment (JRE) that is installed with the Host Package.

About this task

If you want to revert to an earlier version of VSC, RCU, or SMVI after installing the Host Package, you must uninstall the Host Package prior to installing the earlier version of VSC, RCU, or SMVI.

Steps

1. On the Windows server where you installed the Host Package, navigate to the Windows Control Panel and select **Control Panel > Add/Remove Programs** (Windows Server 2003) or **Control Panel > Programs and Features** (Windows Server 2008).

For details, see the documentation for your Windows operating system.

2. Scroll through the list of installed programs to find the program that you want to remove.
3. Click once on the program you want to uninstall and then click **Uninstall/Change** or **Change/Remove**, depending on your operating system.

The install wizard opens.

4. On the Welcome page of the installation wizard, click **Next** to continue.
5. Click **Uninstall**.

After you finish

- When you finish uninstalling the Host Package, you might need to manually close the port used for OnCommand Host Service Management.
- You must disable all the ports opened by the installer for all profiles as appropriate for your operating system.

Related tasks

[Installing the OnCommand Host Package in a VMware environment](#) on page 52

[Upgrading to the OnCommand Host Package in a VMware environment](#) on page 91

Related references

[Required ports for the Host Package](#) on page 38

Uninstalling the OnCommand Host Package in a Hyper-V environment

You can uninstall the OnCommand Host Package from your system using the Control Panel application for your operating system. When you uninstall the Host Package, SnapDrive for Windows is also uninstalled, unless you have SnapManager for Hyper-V 1.0 installed on your system. When you uninstall the Host Package, the host service does not unregister from the DataFabric Manager server.

Before you begin

- You must save any files that contain data such as local backups, scheduled jobs, or datasets.

You can find these files in the installation folder. The uninstall process removes all Host Package files.

About this task

You should not uninstall the Host Package in the following instances:

- If there is disk support for a guest operating system on a virtual machine
- If there are single file restore sessions created by a virtual machine

Steps

1. On the Windows server where you installed the Host Package, navigate to the Windows Control Panel and select **Control Panel > Programs and Features**.

For details, see the documentation for your Windows operating system.

2. Scroll through the list of installed programs to find the program that you want to remove.
3. Click once on the program you want to uninstall and then click **Uninstall/Change** or **Change/Remove**, depending on your operating system.

The install wizard opens.

4. In the installation wizard, select **Remove** and click **Next**.
5. Click **Uninstall**.

After you finish

- When you finish uninstalling the Host Package, you might need to manually close the port used for OnCommand Host Service Management.
- You must disable all the ports opened by the installer for all profiles as appropriate for your operating system.

Related tasks

[Installing the OnCommand Host Package in a Hyper-V environment](#) on page 55

[Upgrading to the OnCommand Host Package in a Hyper-V environment](#) on page 94

Related references

[Required ports for the Host Package](#) on page 38

Troubleshooting OnCommand installation and setup

If you encounter unexpected behavior during the installation or when using OnCommand, you can use specific troubleshooting procedures to identify and resolve the cause of such issues.

Address already in use

Description	This message occurs when the Windows computer has run out of outbound ports. A Transmission Control Protocol (TCP) connection has closed, causing the socket pair associated with the connection to go into a TIME-WAIT state. This prevents other connections from using the TCP protocol, source Internet Protocol (IP) address, destination IP address, source port, and destination port for an unknown period of time.
Corrective action	Reduce the length of the TCP TIME-WAIT delay. See the Microsoft MSDN library for more information.

There is a problem with this Windows Installer package

Description	This message occurs when you uninstall an application by using the Add or Remove Programs tool in Windows server. The Windows Installer service manages the installation and removal of programs. If there is a problem with the registration of the Microsoft installation engine, you might not be able to remove programs that you have installed by using the Windows installer.
Corrective action	Unregister and reregister the Windows Installer service. See KB891985 on the Microsoft support site for more information.

Cursor displays in multiple locations in the same dashboard panel

Cause	This problem occurs when you use the Firefox browser to open the OnCommand console.
Corrective action	Disable a browser setting in Firefox, as follows: <ol style="list-style-type: none"> 1. Open the Firefox browser and click the Tools menu, then click Options.

2. Click the **Advanced** tab.
3. Clear the Always use the cursor keys to navigate within pages option.
4. Restart the Firefox browser.

Plug-in container for Firefox has stopped working

Cause While installing DataFabric Manager server Express edition, the configuration wizard might crash.

Corrective action Update the Adobe Flash Player plug-in.
See the Mozilla Firefox Help for more information.

Related information

[Firefox Help](#)

No related objects are displayed for a virtual object

Issue No physical servers corresponding to a virtual object are displayed in the Related Objects list in the Server tab of the OnCommand console.

Cause This problem occurs when you add or register a new host service but the mapping between the physical servers and virtual objects does not occur.

Corrective action

1. Refresh the monitor by opening a console session and type the following command:

```
dfm host discover -m share <storage system>
```
2. To view the results, type the following command:

```
dfm details <storage system>
```
3. Search for the `shareTimestamp` value to ensure that discovery for the storage system is complete.
4. Click **Rediscover** in the Host Services tab of the OnCommand console to rediscover the host service.
5. Verify that the physical servers are displayed in the Related Objects list in the Server tab.

Could not find any storage mapping for virtual object

Description	<p>This message occurs in the following circumstances:</p> <ul style="list-style-type: none"> • When you create a new dataset in the OnCommand console and add virtual objects from the OnCommand Plug-in for VMware to the dataset • When you create a new dataset in the OnCommand console that contains a datastore or a virtual machine from an NFS-based qtree
Corrective action	<ol style="list-style-type: none"> 1. Refresh the monitor by opening a console session and type the following command: <pre>dfm host discover -m share <storage system></pre> 2. To view the results, type the following command: <pre>dfm details <storage system></pre> <p>If you created a dataset from an NFS-based qtree, then you must set the export permission for the qtree in the storage system.</p> 3. Search for the <code>shareTimestamp</code> value to ensure that discovery for the storage system is complete. 4. Click Rediscover in the Host Services tab of the OnCommand console to rediscover the host service. 5. Verify that the physical servers are displayed in the Related Objects list in the Server tab.

Storage mapping fails for virtual machine and datastore created on VMFS datastore using FC LUN

Issue	Host service does not display any storage mapping in the OnCommand console for virtual machine and datastore created on VMFS datastore using FC LUN.
Cause	This problem occurs when you do not correctly unmap an FC LUN from the ESX host and there are non-accessible LUNs in the datastore that you created, the SCSI target might not get updated in the vCenter Server inventory.
Corrective action	Remove the non-accessible LUN and rescan the storage adapter.

Operation timed out

Description	This message occurs when an ESX or vCenter Server is busy creating snapshots or running local backups. In this instance, a copy operation for a restore might timeout from the vCenter server and the restore operation fails.
Corrective action	You can retry the restore operation when the ESX or vCenter Server is not as busy or you can use a different ESX or vCenter Server that is also connected to the same datastores.

Primary key for table is not unique

Description	This message occurs if the virtual machine, when adding the entire virtual machine folder to the vCenter Server inventory, was moved rather than copied. The virtual machine then has the same universal unique identifier (UUID) as the original virtual machine to which the virtual machine folder was copied. This UUID conflict with that of the original virtual machine causes the host service discovery to fail.
Corrective action	

NetApp icon does not appear in the vSphere Client

Issue	The NetApp is missing in the home page of the vSphere Client.
Cause	This problem might occur in the following circumstances: <ul style="list-style-type: none"> • If you recently restarted OnCommand Plug-in for VMware service, the vSphere Client might have started before the service registered the extension because the vSphere Client does not check for registrations that occur after you launch the vSphere Client • If the OnCommand Plug-in for VMware becomes unregistered with the vCenter Server for the following reasons: <ul style="list-style-type: none"> • If you are upgrading to the Host Package but the upgrade does not complete successfully • If you stop the OnCommand Plug-in for VMware service or it crashes
Corrective action	Register the OnCommand Plug-in for VMware with the vCenter Server if the plug-in becomes unregistered or enable the plug-in, as follows:

1. Close the vSphere Client GUI and then restart the vSphere Client if the OnCommand Plug-in for VMware service is running, but the NetApp icon does not appear in the GUI.
If restarting the vSphere Client does not work, you can enable the plug-in.
2. Open the Plug-in Manager dialog box and check for any errors.
For details, see the vSphere Client Online Help.
3. Right-click the error and select **Enable** from the drop-down list.

Access is denied

Description	This message occurs when you successfully install the Host Package, then attempt to modify the installation by setting new user credentials using the Add or Remove Programs tool in Windows server. This message might appear if the User Account Control (UAC) feature is enabled in Windows Server 2008 or Windows Server 2008 R2.
Corrective action	Set the UAC security level to low or you can change the Host Package settings by restarting the Host Package installer.

Error 1067 while starting webui service

Description	This message occurs during the installation of the Core Package on a system that if there is any other Java installation (older, newer, or same version) which sets Java specific environment variables. It might result in this problem in which the DFM WebUi service fails to start when the installation is complete.
Corrective action	You can uninstall the tool or application that set the Java specific environment variables or you can delete these variables when the DFM WebUi service fails to start after you install the Core Package. You can start the service manually by typing the command <code>dfm service start webui/http</code> .

Verifying host service to DataFabric Manager server communication

Issue	You can use the <code>dfm hs diag</code> command to verify that communication is enabled between the host service and the DataFabric Manager server, and to verify that the host service can communicate with either the VMware or Hyper-V plug-in. You
--------------	---

can use this command to troubleshoot connectivity issues or to verify that communication is enabled before starting a host service backup.

**Corrective
action**

1. On the DataFabric Manager server console, type the following command:

```
dfm hs diag <host service>
```

Administrators usergroup does not exist on <vFiler name>

Description

This message occurs when you have a vFiler and you did not run the RBAC monitor for that vFiler, causing the vFiler configuration job for adding the vFiler credentials to the host service to fail.

**Corrective
action**

1. Run the RBAC monitor for the vFiler using the command `dfm host discover -m rbac <Vfiler Name>`.
2. Run the configuration job for the vFiler.

Host service fails to connect to DataFabric Manager server after a restart

Cause

If there not enough space on the disk, the Windows Event Log automatically stops the plug-in services.

**Corrective
action**

You must ensure there is enough space on the system drive and then restart the services that were stopped. The plug-in service has to be restarted before starting the host service.

Host service is unresponsive after successful installation of OnCommand Host Package

Issue

After you successfully install the Host Package, the host service does not display in the Host Services tab of the OnCommand console. You cannot configure a host service and no virtual objects are discovered.

Cause

This problem occurs because of a limitation in XML, when the host name contains two hyphens in a row, causing the host service to become unresponsive. Additionally, another unusual sequence of characters might also cause this problem.

Corrective action

1. Stop the oncommandhostsvc service.
2. You must modify the `hs_plugins.xml` file, which is located in the installation directory.

The location of this file is at `C:\Program Files\NetApp\OnCommand Host Package\Host Service` if you installed the Host Package in the default directory at `C:\Program Files\NetApp\OnCommand Host Package`.

3. You must remove the following from within the comments section in a VMware environment:

```
<PlugInEndpointInfo>
  <PlugInName>NetApp OnCommand Host Service VMware
Plug-in</PlugInName>
  <PlugInId>0122AC9E-ACE9-4958-AF1D-F6C0057F8597</
PlugInId>
  <PlugInVersion>1.0.0.0</PlugInVersion>
  <NetAppName>NetApp, Inc.</NetAppName>
  <EndpointURI>https://FCP-Q-VM5--W2K8:8044/smvi/
services/Hsplugin</EndpointURI>
  <EndpointHost>FCP-Q-VM5--W2K8</EndpointHost>
</PlugInEndpointInfo>
```

4. You must remove the following from within the comments section in a Hyper-V environment:

```
<PlugInEndpointInfo>
  <PlugInName>NetApp OnCommand Host Service Hyper-V
Plug-in</PlugInName>
  <PlugInId>735efa4d-6d5e-4bdb-9b95-f4003b5b4a82</
PlugInId>
  <PlugInVersion>1.0.0.0</PlugInVersion>
  <NetAppName>NetApp, Inc.</NetAppName>
  <EndpointURI>https://FCP-Q-VM5--W2K8:8044/
HostServicesPlugin/HyperV</EndpointURI>
  <EndpointHost>FCP-Q-VM5--W2K8:8044</EndpointHost>
</PlugInEndpointInfo>
```

5. Restart the oncommandhostsvc service.

Installing and configuring the OnCommand Core Package in an MSCS environment

Microsoft Cluster Server (MSCS) provides high-availability protection for your Windows environment.

As part of the OnCommand Core Package installation process, the DataFabric Manager server and its associated services are installed on your system. The cluster resources, including the services for the DataFabric Manager server, the network name, the network address, and the shared data disks, are always online and available on one of the nodes. You must configure the network name and address, and the shared data disks, during the OnCommand Core Package installation process.

When any failure occurs, whether a node failure or a failure of one of the resources, all the resources are automatically moved, or failed over, to the partner node by MSCS.

This failover process is assisted by using a quorum resource on the cluster. The quorum resource is a physical storage device that can be accessed by both nodes in the cluster, although only one node has access to the quorum resource at any given time. The node that has access to the quorum resource is the node that has control of the cluster resource.

Preparing to install the OnCommand Core Package in an MSCS environment

An MSCS cluster configured with DataFabric Manager server consists of two nodes, each node running the same version of the DataFabric Manager server.

To ensure high availability of DataFabric Manager server, you must configure the services to be accessible through a network name and a network address. DataFabric Manager server can also use this network name or network address, so you do not need to add new network resources for the services. All DataFabric Manager server data (database files, Performance Advisor files, and so on) are configured to be accessed from a shared data disk.

Prerequisites for installing the OnCommand Core Package in MSCS

Before installing the Core Package in MSCS, you must set up two Windows servers running on identical hardware platforms. You must ensure that all the requirements and guidelines for configuring cluster servers are met, according to the MSCS documentation.

During the MSCS setup, you must ensure that you have completed the following actions:

- Creating a shared data disk to be used as a quorum resource.
- Creating a network name resource and a network address resource.
- Adding cluster resources to a resource group.

Related information

Introducing Microsoft Cluster Service (MSCS)

Configuration requirements for the OnCommand Core Package in MSCS

There are specific configuration requirements that must be met when setting up your MSCS environment with the OnCommand Core Package.

The configuration requirements in your MSCS environment are as follows:

- Microsoft Windows servers running Windows Server 2003 Enterprise Edition, Windows 2008 Enterprise Edition, or Data Center Edition, must run the same patch versions on identical hardware.
 - Note:** MSCS is not supported on Windows Server 2008 and Windows Server 2008 R2. However, you can configure DataFabric Manager 3.8 or later for high availability on these platforms by using Failover Clustering. For more details, see technical report on *High-Availability support for DataFabric Manager server*.
- The DataFabric Manager server must be connected to the storage system either with iSCSI or Fibre Channel (FC), and should be in a SAN environment.
- FC switched fabric or iSCSI-based storage must be used for shared data disks with a NetApp storage system as the storage back-end.
- Members of the cluster must be member servers, and not domain controllers.
- The same version of OnCommand Core Package must be installed at the same path on both of the cluster nodes: for example, `C:\Program Files\NetApp\DataFabric Manager\DFM`.
- All DataFabric Manager server administrators must be domain users, rather than local system users so that the user login works even when the DataFabric Manager server services fail over to the partner node.
- 64-bit Perl in Windows 64-bit 2008 server is required to run DataFabric Manager server configuration scripts.

Related information

Technical report on High-Availability Support for DataFabric Manager server - <http://www.netapp.com/us/library/technical-reports/tr-3767.html>

Configuration limitations for the OnCommand Core Package in MSCS

OnCommand Core Package in MSCS is not supported on certain environmental conditions of the MSCS environment.

The following are configuration limitations of installing OnCommand Core Package in an MSCS environment:

- IPv6 virtual IP address on failover clustering is supported on Windows 2008 only.
- Only the Single Quorum Device Cluster setup is supported on Windows 2003.
- Quorum type “node and disk majority” in Failover Cluster is supported on Windows 2008 server only.

- OnCommand Core Package in MSCS is not supported on Windows running in a virtual machine.
- DataFabric Manager server does not support a host service created as a generic service from failover cluster manager in Microsoft Windows.

Installing the OnCommand Core Package in an MSCS environment

Before installing the OnCommand Core Package, you must configure MSCS with a shared disk for a quorum resource, assign a network name and a network address, place the cluster resources in a cluster resource group. After the installation is complete, you have to add DataFabric Manager server services to MSCS. You can install OnCommand Core Package in MSCS to ensure high availability in a Windows environment. You must install OnCommand Core Package on the first node, and repeat on the second node.

Configuring MSCS to install the OnCommand Core Package

Before you install OnCommand Core Package in MSCS, you must configure your MSCS environment.

About this task

You must complete this task by using the Cluster Administrator in the MSCS interface. See the MSCS documentation for more details.

Before installing the OnCommand Core Package, you must configure MSCS to create the following:

- A shared quorum disk, which is used for storing the cluster configuration information.
- A network name and a network address, which are used for managing the cluster server and DataFabric Manager server.
- A group to store the resources so that all the resources are available to both cluster nodes.

Steps

1. Select a domain user and add the domain user to the **Administrators Group** on both the cluster nodes.

Example

Enter the following command in Administrators Group:

```
domain\dfmuser
```

.

2. Create a shared data disk:
 - a. Make the disk accessible to both the cluster nodes.
 - b. Map the disk to a drive letter (such as drive S:).

Note: The data disk should be mapped to the same drive letter on both the cluster nodes.

- c. Add the shared data disk, as a physical disk resource, to the cluster server.

This disk is a resource for storing data specific to the OnCommand Core Package.

3. Verify that the new resource group can successfully fail over to the partner node.

Result

The Cluster Administrator displays the resources, nodes, and groups. In addition to the content displayed after the initial setup, Cluster Administrator shows a physical disk resource named Disk S:.

Related information

Introducing Microsoft Cluster Service (MSCS) - <http://msdn.microsoft.com>

Installing the OnCommand Core Package in MSCS

You can install OnCommand Core Package in MSCS to ensure high availability in a Windows environment. You must install OnCommand Core Package on the first node, and repeat the installation procedure on the second node.

Before you begin

The following conditions must be met:

- Microsoft Cluster Server is installed and configured on both nodes of the cluster.
- The preinstallation tasks are completed.
- The workstation meets the hardware requirements.
- You have Local Administrator login permission for the DataFabric Manager server.
- If you are upgrading from a previous version of the DataFabric Manager server, you should back up your database before the installation or during the installation process.
- The OnCommand Core Package installer from the NetApp Support Site must have been downloaded.

About this task

The two DataFabric Manager server nodes are configured to use the same database and to monitor the same set of nodes. Therefore, you can install the same license on both the nodes.

During a new installation, you must specify the Core license key. If you are upgrading from an earlier licensed version of DataFabric Manager server, you do not need a license key. The installation and upgrade processes automatically install the AutoSupport feature with AutoSupport enabled and display a message about how to disable the feature.

Steps

1. Log in to the first node of the cluster pair as a domain user, with administrator privileges on the local system.
2. Open the **Cluster Administrator** interface and select **Owner** of the Resources folder, to ensure that the node owns the cluster resources.
3. Run the executable file.
4. Follow the setup prompts to complete the installation and note the installation directory path for later reference.
5. Stop the DataFabric Manager server services after the installation is complete by entering the following command:

```
dfm service stop
```

Attention: You should perform all cluster operations by using either Cluster Administrator or `cluster.exe`. Except where specifically indicated in installation and configuration procedures, you must not use `dfm service start` and `dfm service stop`. These commands interfere with cluster operations.

6. Move the cluster resources to the second node by using the **Move Group** option in MSCS.
7. Log in to the second node of the cluster pair as a domain user with administrator privileges on the local system.

Note: You must log in with the same user name you used on the first node.

8. Install the Core package on the second node at the same directory path that you used on the first node.
9. Stop the DataFabric Manager server services on the second node by entering the following command:

```
dfm service stop
```

10. Disable the automatic start-up of the DataFabric Manager server by entering the following command on both the nodes:

```
dfm service enable -m
```

After you finish

You can start configuring both the cluster nodes by using the configuration scripts that are provided with the installation, or you can perform the configuration manually.

Related concepts

[OnCommand Core Package hardware and software requirements](#) on page 26


Related information

[The NetApp Support Site–support.netapp.com/](http://support.netapp.com/)

Example of MSCS initial setup

You should understand how the cluster, the nodes, the physical disk, the network name and the network IP address are displayed in the Cluster Administrator interface.

The following image is an example of the Cluster Administrator interface after the initial setup of MSCS.



The configuration displayed in this example are as follows:


- Cluster name is Cluster 1.
- First node name is Kalyani.
- Second node name is Toddy.
- Physical disk, the shared disk quorum resource, is created with the name Disk Q: and is mapped to drive letter Q:.
- Network Name resource is called Cluster Name.
- Network IP Address resource is called Cluster IP Address.

DataFabric Manager server service resources added to MSCS

You must add the DataFabric Manager server cluster service resources to MSCS. The services include DFM Monitor, DFM Apache, DFM Watchdog, DFM Event, DFM Server, DFM Scheduler, DFM WebUI, and DFM Sybase.

These services are used for various purposes, such as monitoring storage systems, scheduling jobs, serving HTTP requests and executing servlets, processing events and database queries, and monitoring all the other services.

The following illustration shows the services and the dependencies among the various resources.



Configuring the OnCommand Core Package in an MSCS environment

When you install the OnCommand Core Package, the DataFabric Manager server services are installed with it. To achieve high availability, you must add the DataFabric Manager server cluster services to MSCS. You can configure the services either by using scripts or by adding the services manually.

The following service resources are added to MSCS:

- DFM Monitor
- DFM Apache
- DFM Watchdog
- DFM Event
- DFM Server
- DFM Scheduler
- DFM WebUI
- DFM Sybase

Adding the cluster services using a script

You can configure DataFabric Manager server in your cluster environment by running a configuration script. You can use the script to add the DataFabric Manager server cluster services to the cluster environment.

Steps

1. Log in to the node that owns cluster resources.
2. Move the DataFabric Manager server data to the shared data disk by entering the following command:

```
dfm datastore setup new_clusterdisk_directory
```

3. Stop DataFabric Manager server services by entering the following command:

```
dfm service stop
```

This ensures that DataFabric Manager server does not try to access the data disk to be moved to the secondary node.

4. Ensure that the DataFabric Manager server services do not start automatically by entering the following command:

```
dfm service enable -m
```

The option -m ensures that the DataFabric Manager server services do not start automatically.

5. Manually move the cluster group to the second node.
6. Verify that the secondary node owns the cluster resources.
7. Enter the following commands on the secondary node:

```
dfm service enable -m
```

```
dfm datastore setup -n drive_name
```

Note: You must ensure that you use the same drive letter for the secondary node as the first node. The -n option ensures that the data is not copied again to the shared data disk.

8. Access the directory at `C:\Program Files\NetApp\DataFabric Manager\DFM\examples` or `/opt/NTAPdfm/examples`, and `C:\Program Files(x64)\NetApp\DataFabric Manager\DFM\examples` for x64-bit platform.
9. Configure the DataFabric Manager server services in your cluster environment by running the following script:

```
dfmcluster_add_resources.pl -t cluster_type -g cluster_group -i cluster_ip_resource -n cluster_nameresource
```


Script options for configuring services in MSCS

You can use a configuration script to add the DataFabric Manager server generic service resources to MSCS.

The command to add services to the DataFabric Manager server is as follows:

```
perl dfmcluster_add_resources.pl option name ...
```

- t cluster_type** Cluster solution used for high availability. The values are `mscs` (default) and `vcs`.
- g cluster_group** Name of the cluster group to which the resources are added. This group already includes the other resources.
- i cluster_ip_resource** Name of the cluster IP resource that is displayed under the Name column in the Cluster Administrator.
- n cluster_nameresource** Name of the cluster name resource.
- k data_disk_resource** Name of the data disk resource.

Example

```
perl dfmcluster_add_resources.pl -g ClusterGroup1 -i 172.24.1.20 -n
Cluster1 -k Disk S:
```

Bringing DataFabric Manager server cluster services online in MSCS

After you add the DataFabric Manager server services to MSCS, you must bring the services online.

Steps

1. In the MSCS interface, select **Cluster Group** under the Groups folder.
2. Click **File**, and then click **Bring Online**.

Configuring DataFabric Manager server to use the cluster name in MSCS

When DataFabric Manager server sends e-mail alert messages to administrators, the DataFabric Manager server uses the local system name in the URL, by default. These local system names are not accessible to users in the cluster. Therefore, you must configure DataFabric Manager server to use the cluster name instead.

Step

1. Configure the DataFabric Manager server to use the cluster name by entering the following command:

```
dfm option set localHostName=fqdn-of-cluster
```

FQDN is the fully qualified domain name of the cluster.

Configuring DataFabric Manager server in MSCS manually

You can manually configure DataFabric Manager server in MSCS, which allows you to customize the setup of the cluster. For example, you can move different DataFabric Manager server data files to different shared data disks. However, you cannot move the data files using the configuration scripts.

Configuring DataFabric Manager server services on the first node in MSCS

You must configure the DataFabric Manager server by manually adding the DataFabric Manager server services.

Before you begin

You must be logged in as a domain user, with administrative privileges on the local system to access the shared data drive. By default, the DataFabric Manager server services run using the local system account, and therefore do not provide access to the shared drive where the database files and other files reside.

Steps

1. In the **Cluster Administrator**, select the **Owner** field of the Resources folder.
2. Verify that the first node owns the resource group named Cluster Group
3. Stop the DataFabric Manager server services by entering the command:

```
dfm service stop
```

Attention: You should perform all cluster operations by using either Cluster Administrator or `cluster.exe`. Except where specifically indicated in installation and configuration procedures, you must not use `dfm service start` and `dfm service stop`. These commands interfere with cluster operations.

4. Specify a **Logon As** user account:
 - a. Open Services page from Windows **Control Panel**.
 - b. Double-click **DFM Sybase ASA**.
 - c. In the **General** tab, change the **Startup type** option to **Manual**.
 - d. Click **Apply**.
5. Click the **Log On** tab.
6. Enter the name of the domain user account you want to use to access the DataFabric Manager server service from the shared drive.
7. Click **OK**.
8. Repeat steps from 4 through step 7 to add the cluster services.

Add the following service name one at a time:

- DFM Monitor
- DFM Apache
- DFM Watchdog
- DFM Event
- DFM Server
- DFM Scheduler
- DFM WebUI

Note: You must configure all the services for the cluster to start working.

After you finish

You must move the DataFabric Manager server data files to a shared disk.

Moving DataFabric Manager server data files to a shared disk

You must configure the DataFabric Manager server to allow access to data files in a shared disk.

Steps

1. Move the database files to a nonroot folder in the shared data drive.

Note: This step is required only for the first node that you are configuring to be part of a cluster.

The default location for database files is *installation_directory\data*.

Example

```
S:\dfm\data
```

2. Ensure that the DataFabric Manager server points to the relocated database.

Example

```
dfm database set dbDir=S:\dfm\data
```

3. Verify that all the services are stopped by entering the following command:

```
dfm service list
```

4. Move all other data files to folders in the shared disk:

- You must move the Performance Advisor data files to a folder in the shared data drive. The default location is *installation_directory\perfdata* (for example, *S:\dfm\perfdata*).
- You must move the Script plug-in files to a folder in the shared data drive. The default location is *installation_directory\script-plugins* (for example, *S:\dfm\script-plugins*).

- You must move the Configuration Management plug-in files to a folder in the shared data drive. The default location is *installation_directory\plugins* (for example, S:\dfm\plugins).
 - You must move the archived reports to a folder in the shared data drive. The default location is *installation_directory\reports* (for example, S:\dfm\reports).
5. Start the SQL service by entering the following command:

```
dfm service start sql
```
 6. Set options such that the DataFabric Manager server points to the new location of the relocated files.
 - a. `dfm option set perfArchiveDir=S:\dfm\perfdata`
 - b. `dfm option set pluginsDir=S:\dfm\plugins`
 - c. `dfm option set scriptDir=S:\dfm\script-plugins`
 - d. `dfm option set reportsArchiveDir=S:\dfm\reports`

Note: The `dfm option set` command recommends that you should start the services. You must not start the services after setting each option.
 7. Stop the SQL service by entering the following command:

```
dfm service stop sql
```

Configuring DataFabric Manager server services on the second node in MSCS

After the first node is configured to allow access to all data files from a shared disk, you must configure the second node to allow the same access.

Before you begin

To allow access to the shared data drive, you must be logged in as a domain user, with administrative privileges on the local system.

Steps

1. In the **Cluster Administrator** interface, select the **Owner** field of the Resources folder to ensure that the first node owns the resource group named Cluster Group.
2. Enter the following command to stop DataFabric Manager server services:

```
dfm service stop
```

Attention: You should perform all cluster operations by using either Cluster Administrator or `cluster.exe`. Except where specifically indicated in installation and configuration procedures, do not use `dfm service start` and `dfm service stop`. These commands interfere with cluster operations.

3. Specify a **Logon As** user account:

- a. Open Services page from Windows **Control Panel**.
 - b. Double-click **DFM Sybase ASA**.
 - c. In the **General** tab, change the **Startup type** option to **Manual**.
 - d. Click **Apply**.
4. Click the **Log On** tab.
 5. Enter the name of the domain user account you want to use to access the DataFabric Manager server service from the shared drive.
 6. Click **OK**.
 7. Repeat steps from 3 through step 6 to add the cluster services.

After selecting **Services** from the **Administrative Tools** enter the name of the following service name one at a time:

- DFM Monitor
- DFM Apache
- DFM Watchdog
- DFM Event
- DFM Server
- DFM Scheduler
- DFM WebUI

Note: You must configure all the services for the cluster to start working.

8. Verify that all the services are stopped by entering the following command:

```
dfm service list
```

Configuring DataFabric Manager server services as cluster resources in MSCS

After you install the DataFabric Manager server services, you have to configure them as cluster resources and make them available to both nodes.

Before you begin

- The dependencies that exist between the various cluster resources must be determined. A dependency requires that one service be running before its associated service can be brought online. For example, most services cannot function unless Sybase ASA is already running.
- You must be logged in to the node as a domain use, with administrator privileges on the local system.

About this task

See the following table to add the Resource Name, Dependencies, and Service Name when configuring each new cluster service:

Resource Name field	Dependencies field	Service Name field
DFM Sybase ASA	Cluster IP, Cluster Name, Shared Data Disk, Data Disk	DFMSybase
DFM Apache	DFM Sybase ASA, DFM WebUI	DFMApache
DFM Scheduler	DFM Sybase ASA	DFMScheduler
DFM Watchdog	DFM Sybase ASA	DFMWatchdog
DFM Server	DFM Sybase ASA	DFMServer
DFM Event	DFM Sybase ASA	DFMEvent
DFM Monitor	DFM Event	DFMMonitor
DFM WebUI	DFM Sybase ASA	DFMWebUI

Steps

1. In the **Cluster Administrator** interface, select the **Owner** field of the Resources folder to ensure that the node currently owns all the cluster resources.
2. In the console tree, double-click the **Groups** folder.
3. In the **details** pane, click the group named **Cluster Group**.
4. Select **File** menu, then select **New > Resource**.
5. On the **New Resource** page, complete the following steps:
 - a. Enter the resource name in the **Name** field.
 - b. Select **Generic Service** as the **Service Type**.
 - c. Select **Cluster Group** as the group.
 - d. Click **Next**.
6. On the **Possible Owners** page, complete the following steps:
 - a. Add both nodes as the possible owners of the resource.
 - b. Click **Next**.
7. On the **Dependencies** page, complete the following steps:
 - a. Add **Dependencies** related to the new service.

Example

Set **DFM Sybase ASA Dependencies** as Cluster IP Address, Cluster Name, Disk S:, and Data Disk.

- b. Click **Next**.

8. On the **Generic Service Parameters** page, complete the following steps:

a. Enter the **Service Name**.

Example

Set the name to DFM Sybase.

b. Clear the **Use Network name for computer name** option.

9. On the **Registry Replication** page, click **Finish**.

Note: You do not have to perform registry replication.

10. Repeat steps 5 to 9 for every DataFabric Manager server service.

Related references

[DataFabric Manager server service resources added to MSCS](#) on page 118

Bringing DataFabric Manager server cluster services online in MSCS

After you add the DataFabric Manager server services to MSCS, you must bring the services online.

Steps

1. In the MSCS interface, select **Cluster Group** under the Groups folder.
2. Click **File**, and then click **Bring Online**.

Configuring a host service in MSCS

When you add a new host service in a cluster environment, you must ensure that both nodes in a cluster pair have access to the keys folder. This ensures that when one node fails, the second node of the cluster pair starts functioning.

Steps

1. Copy the keys folder from one node to the other in the cluster pair at `installation_directory\conf`.
2. In the **Cluster Administrator** interface, select the cluster group and click **Move group**, or manually move the cluster group to the second node and verify that the second node owns the resources.
3. Enter the following command on the second node to start using the new setting:
`dfm ssl service reload`
4. Launch the OnCommand console and verify that the host service status is Up in the **Host Services** tab.

Managing DataFabric Manager server in an MSCS environment

You can create and restore backups, set HTTPS options, and configure DataFabric Manager server to share data on the DataFabric Manager server cluster nodes.

Best practices to start and stop DataFabric Manager server services in MSCS

After you set up DataFabric Manager server in MSCS, do not use the `dfm service start` and `dfm service stop` commands, except where specifically indicated in installation and configuration procedures. These commands interfere with the working of MSCS.

You must start or stop all operations by using either the Cluster Administrator in MSCS or the `cluster.exe` command.

Note: Do not change the `Service startup type` to `Automatic` in the Service Control Manager on any of the nodes. Ensure this option is set to `manual`.

Restoring the DataFabric Manager server database in MSCS

You must first stop all services to restore the DataFabric Manager server from an existing backup of the database.

Steps

1. Log in to the node that currently owns the cluster resources.
2. In **Cluster Administrator**, take the services offline:
 - a. Right-click the **DFM Sybase** service.
 - b. Select **Take offline**.

The other services are also taken offline.

3. Restore the database by entering the following command in the OnCommand console:
`dfm backup restore`
4. Stop all the services by entering the following command in the OnCommand console:
`dfm service stop`
5. In **Cluster Administrator**, bring the DataFabric Manager server services online:
 - a. Select **Cluster Group** under the Groups folder.
 - b. Click **File** and click **Bring Online**.

Configuring DataFabric Manager server to use HTTPS in MSCS

You can configure DataFabric Manager server to use HTTPS on both the cluster nodes for a secured data transfer.

About this task

HTTPS must be first set up with an SSL certificate and the HTTPS option must be enabled on both the nodes.

Steps

1. Log in to the first node in the cluster.
2. In **Cluster Administrator**, take the DataFabric Manager server services offline:
 - a. Right-click the **DFM Sybase** service.
 - b. Select **Take offline**.

The other services are also taken offline.

3. Start the SQL service by entering the following command in the OnCommand console:

```
dfm service start sql
```

4. Create an SSL certificate for HTTPS by entering the following command:

```
dfm ssl server setup
```

This creates two files, `server.crt` and `server.key`, in the `installation_directory\conf` folder.

5. Set the DataFabric Manager server option to enable HTTPS by entering the following command:

```
dfm option set httpsEnabled=yes
```

6. Start the HTTP service by entering the following command:

```
dfm service start http
```

Starting the service using `dfm service start` re-creates the `httpd.conf` file with the changed options.

Attention: You should perform all cluster operations by using either Cluster Administrator or `cluster.exe`. Except where specifically indicated in installation and configuration procedures, do not use `dfm service start` and `dfm service stop`. These commands interfere with cluster operations.

7. Stop all the services by entering the following command:

```
dfm service stop
```

Note: You must ensure that DataFabric Manager server services are offline before proceeding. Otherwise, the HTTP service is not enabled on the other node because the configuration is not complete.

8. In **Cluster Administrator**, move the cluster group to the second node by using the **Move Group** option.
9. Log in to the second node in the cluster.
10. Copy the `server.crt` and `server.key` files created on the first node to the `installation_directory\conf` folder on the second node.
11. Start the services and verify they are operating as required by entering the following command:

```
dfm service start
```

Starting the service by using `dfm service start` re-creates the `httpd.conf` file with the changed options.

12. Stop the services by entering the following command:

```
dfm service stop
```

13. In **Cluster Administrator**, bring the DataFabric Manager server services online:

- a. Select **Cluster Group** under the Groups folder.
- b. Click **File**, and click **Bring Online**.

Changing HTTP options in an MSCS environment

You can change the HTTP options to enable HTTPS, or change the default HTTP and HTTPS port.

Steps

1. Log in to the first node in the cluster.
2. In **Cluster Administrator**, take the DataFabric Manager server services offline:
 - a. Right-click the DFM Sybase service.
 - b. Select **Take offline**.

The other services are also taken offline.

3. Start the SQL service by entering the following command:

```
dfm service start sql
```

Attention: You should perform all cluster operations by using either Cluster Administrator or `cluster.exe`. Except where specifically indicated in installation and configuration procedures, do not use `dfm service start` and `dfm service stop`. These commands interfere with cluster operations.

4. Set the required HTTP option by entering the following command:

```
dfm option set option-name=option-value
```

Example

```
dfm option set httpsPort=443
```

5. Start the HTTP service by entering the following command:

```
dfm service start http
```

Starting the service by using `dfm service start` re-creates the `httpd.conf` file with the changed options.

6. Stop all the services by entering the following command:

```
dfm service stop
```

Note: You must ensure that DataFabric Manager server services are offline before proceeding. Otherwise, the HTTP is not enabled on the other node because the configuration is not complete.

7. In **Cluster Administrator**, move the cluster group to the second node by using the **Move Group** option.

8. Log in to the second node in the cluster.

9. Start the services by entering the following command:

```
dfm service start
```

10. Stop the services by entering the following command:

```
dfm service stop
```

11. In **Cluster Administrator**, bring the DataFabric Manager server services online:

- a. Select **Cluster Group** under the Groups folder.
- b. Click **File** and click **Bring Online**.

DataFabric Manager server monitoring in MSCS

Microsoft provides the Server Clusters Management Pack as part of Microsoft Operations Manager. You can monitor the cluster server, and report node status, resource status, and alerts by using Cluster Administrator in MSCS. DataFabric Manager server does not provide any additional cluster monitoring or alerting functionality.

Data shared by MSCS cluster nodes

You must configure the DataFabric Manager server nodes to access files from a shared disk. If each node uses its own local copy of files, any updates to these files might not be reflected in the files of the other nodes, after a failover.

The MSCS cluster nodes share the following files:

installation_directory\data

Sybase database files

<code>installation_directory\perfdata</code>	Performance Advisor data files
<code>installation_directory\scriptplugins</code>	Installed script plug-ins and related files
<code>installation_directory\plugins</code>	Storage system configuration plug-ins
<code>installation_directory\reports</code>	Archived reports
<code>installation_directory\dataExport</code>	DataFabric Manager server and Performance Advisor data
<code>installation_directory\jetty</code>	Libraries and Web application files

Data that is not shared by MSCS cluster nodes

Files such as executables, configuration files, and licenses are not shared by the MSCS cluster nodes. This ensures that the same version is maintained in the cluster nodes.

The following files are not shared:

<code>installation_directory\bin</code>	Executable files
<code>installation_directory\conf</code>	Configuration files
<code>installation_directory\docs</code>	Third-party licenses
<code>installation_directory\examples</code>	Cluster configuration scripts, and so on
<code>installation_directory\log</code>	Log files
<code>installation_directory\misc</code>	Configuration files
<code>installation_directory\sbin</code>	Third-party executables
<code>installation_directory\scripts</code>	Sybase_install.sql
<code>installation_directory\src</code>	Storage system configuration plug-ins
<code>installation_directory\web\clients</code>	Performance Advisor clients
<code>installation_directory\web\com</code>	JAR files for applets
<code>installation_directory\web\help</code>	Help files
<code>installation_directory\web\man</code>	Manual pages
<code>installation_directory\web\media</code>	Images used on Web interfaces
<code>installation_directory\web\scripts</code>	Java script files
<code>installation_directory\web\styles</code>	CSS style sheets
<code>installation_directory\perfExport</code>	Exported performance counter data for specified objects

Uninstalling the OnCommand Core Package in an MSCS environment

To uninstall OnCommand Core Package from a cluster, you have to delete the cluster services from each cluster node.

Steps

1. In **Cluster Administrator**, delete all the DataFabric Manager server services:

- a. Right-click the **DFM Sybase** resource.
- b. Select **Delete**.

The other DataFabric Manager server services are also deleted.

2. Log in to any one of the cluster nodes.
3. From the **Add/Remove Programs** utility, uninstall the OnCommand Core Package.
4. Repeat steps 2 and 3 for the other nodes.

Upgrading the OnCommand Core Package in an MSCS environment

When you upgrade the OnCommand Core Package cluster nodes, you must ensure that all the nodes in the cluster are upgraded.

Before you begin

- A backup of your existing DataFabric Manager server database must be created.
- The OnCommand Core Package installer must be downloaded from the NetApp Support Site.
- Add the DFM WebUI services to the DataFabric Manager server.

Steps

1. In **Cluster Administrator**, take the DataFabric Manager server services offline:

- a. Right-click the DFM Sybase service.
- b. Select **Take offline**.

The other services are also taken offline.

2. Select the **Owner** field of the Resources folder and ensure that the first node owns the resource group named `Cluster Group`.

3. Upgrade to the OnCommand Core Package installation on the first node:
 - a. Run the executable file.
 - b. Follow the OnCommand Core Package setup prompts to complete the installation.
4. Stop all the DataFabric Manager server services by entering the following command:
`dfm service stop`
5. Disable the automatic service start-up during reboot by entering the following command:
`dfm service enable -m`
6. In **Cluster Administrator**, move the cluster group to the second cluster node by selecting the group name in **Services and Applications**, and then click **Move this service or application to other node**.
7. Select the **Owner** field of the **Resources** folder to upgrade the second node.
Ensure that the second node currently owns all the cluster resources.
8. Upgrade to the OnCommand Core Package installation on the second node:
 - a. Get the OnCommand Core Package installer from the NetApp Support Site, and run the executable file.
 - b. Follow the OnCommand Core Package setup prompts to complete the installation.
9. Stop all the DataFabric Manager server services by entering the following command:
`dfm service stop`
10. Disable the automatic service start-up during reboot by entering the following command:
`dfm service enable -m`
11. In **Cluster Administrator**, click the console tree, and double-click the **Groups** folder.
12. In the **details** pane, click the group named **Cluster Group**.
13. Select the **File** menu, and then select **New > Resource**.
14. On the **New Resource** page, complete the following steps:
 - a. Enter DFM WebUI as the **Name** field.
 - b. Select **Generic Service** as the **Service Type**.
 - c. Select **Cluster Group** as the group.
 - d. Click **Next**.
15. On the **Possible Owners** page, add both the nodes as the possible resource owners, and click **Next**.
16. On the **Dependencies** page, add DFM Sybase ASA to be dependency on DFM WebUI, and click **Next**.

In the DFM Apache Properties page set DFM WebUI to be dependant on DFM Apache.

17. On the **Generic Service Parameters** page, complete the following steps:

- a. Enter DFM WebUI as the **Service Name**.
- b. Clear the **Use Network name for computer name** option.

18. Bring the DataFabric Manager server services online:

- a. Select **Cluster Group** under the **Groups** folder.
- b. Click **File**, and click **Bring Online**.

Related tasks

[Adding the cluster services using a script](#) on page 120

Installing and configuring the OnCommand Core Package in a VCS environment

Veritas Cluster Server (VCS) provides high-availability protection for cluster configuration.

As part of the OnCommand Core Package installation process, the DataFabric Manager server and its associated services are installed on your system. The cluster resources, including the services for the DataFabric Manager server, the network name, the network address, and the shared data disks, are always online and available on one of the nodes. You must configure the network name and address, and the shared data disks, During the OnCommand Core Package installation process.

When a resource of node failure is detected, all the resources are automatically moved, or failed over, to the partner node by VCS.

Preparing to install the OnCommand Core Package in a VCS environment

A VCS cluster configured with DataFabric Manager server consists of two nodes, each node running the same version of the DataFabric Manager server.

To ensure high availability of the DataFabric Manager server services, you must configure the services to be accessible through a network name and a network address. DataFabric Manager server can also use this network name or network address, so you do not need to add new network resources for the services. All of the DataFabric Manager server data (database files, Performance Advisor files, and so on) is configured to be accessed from a shared data disk.

Prerequisites for installing the OnCommand Core Package in VCS

Before installing the OnCommand Core Package in VCS, you must ensure that the configuration requirements are met.

- VCS must be installed according to the instructions provided in the *Veritas Cluster Server 5.0 Installation Guide*.
- You must ensure that the correct configurations exist on your system. See the Veritas Cluster Server guides for more information.

Related information

Veritas Cluster Server - <http://www.symantec.com/business/cluster-server>

Symantec Support - <http://www.symantec.com/business/support>

Configuration requirements for the OnCommand Core Package in VCS

Before installing the OnCommand Core Package in VCS, you must ensure that the cluster nodes are properly configured to support the OnCommand software.

You must ensure that the VCS configuration meets the following requirements:

- Both the cluster nodes must be running a supported operating system version.
The minimum supported operating systems are Red Hat Enterprise Linux 4 Update 3, SUSE Linux Enterprise Server 9 with SP3.
- The same version of the OnCommand Core Package must be installed at the same path on both the cluster nodes.
- Veritas File System and Volume Manager on Native ext3 File System and Logical Volume Manager (LVM) must be used.
- The DataFabric Manager server should be connected to the storage system with Fibre Channel (FC).

Also ensure that the FC link is active and that the LUNs created on the storage systems are accessible to both the cluster nodes.

- The shared data disk should have enough space to accommodate the DataFabric Manager server database, performance data, and script plug-in folders.
- A minimum of two network interfaces must be set up on each system: one for node-to-node communication and the other for node-to-client communication.
The name of the network interface used for node-to-client communication should be the same on both the systems.
- A separate heartbeat link must be established between the cluster nodes, otherwise the network interface is used to communicate between the cluster nodes.

Configuration limitations for the OnCommand Core Package in VCS

You must be aware of the configuration limitations before you install the OnCommand Core Package in a VCS environment.

The following are configuration limitations in VCS:

- Only two-node clusters are supported.
- The OnCommand Core Package in VCS is not supported on VMware.
- For shared disks, the storage back-end must be an FC-based storage only.
- iSCSI storage is not supported for the OnCommand Core Package in VCS.

Installing the OnCommand Core Package in a VCS environment

You must install Veritas Storage Foundation first and then install the core package in VCS. After you install these on both the nodes, you must configure VCS on the first node to use data from a shared disk, configure the DataFabric Manager server, and configure VCS on the second node.

Configuring VCS to install the OnCommand Core Package

Before you install OnCommand Core Package in VCS, you must install SnapDrive, Fibre Channel adapter, Veritas Storage Foundation, configure VCS, and then use SnapDrive for UNIX to create file systems.

Before you begin

- All requirements and guidelines for configuring cluster servers must be met, according to the VCS documentation.
- SnapDrive for UNIX must be installed.

Steps

1. Install Veritas Storage Foundation and High Availability Solutions 5.0 with Maintenance Pack 1 (MP 1).

Installing Veritas Storage Foundation and High Availability Solutions 5.0 also installs VCS.

2. Configure VCS by entering the following command:

```
installvcs -configure
```

3. Enter the network address (virtual IP address).
4. Use SnapDrive for UNIX to create file systems and logical volumes.

Related information

Veritas Cluster Server - <http://www.symantec.com/business/cluster-server>

Veritas Storage Foundation - <http://www.symantec.com/en/in/business/storage-foundation>

SnapDrive UNIX- <http://now.netapp.com/NOW/knowledge/docs/docs.cgi>

Installing the OnCommand Core Package in VCS

You can install OnCommand Core Package in VCS to ensure high availability.

Before you begin

- VCS is installed and configured on both nodes of the cluster.

- The same version of the OnCommand Core Package is installed on both the nodes.
- The installation directory is the same on both nodes: for example, `/opt/NTAPdfm`.
- The first node owns the cluster resources.
- Root privileges to log in to the DataFabric Manager server.

About this task

The two DataFabric Manager server nodes are configured to use the same database and to monitor the same set of nodes. Therefore, you can use the same license to install, on both the nodes.

If you are upgrading from a previous version of the DataFabric Manager server, you can backup your database before or during the installation process.

During a new installation, you must specify the OnCommand Core license key. If you are upgrading from an earlier licensed version of DataFabric Manager server, you do not need a license key. The installation and upgrade process automatically installs the AutoSupport feature with AutoSupport enabled and displays a message about how to disable the feature.

Steps

1. Log in to the first node of the cluster pair.
2. Download the OnCommand Core Package installer from the NetApp Support Site.
3. Run the executable file.
4. Follow the setup prompts to complete the installation.
5. When the installation is complete, enter the following command to stop the DataFabric Manager server services:

```
dfm service stop
```

6. Disable the automatic start-up of the DataFabric Manager server by entering the following command:

```
dfm service enable -m
```

Attention: You must perform all cluster operations using Cluster Manager. Other than in installation and configuration procedures, you must not use the commands `dfm service start` and `dfm service stop`. These commands interfere with cluster operations.

Related information


[The NetApp Support Site—support.netapp.com/](http://support.netapp.com/)

DataFabric Manager server service resources added to VCS

You must add the DataFabric Manager server cluster service resources to VCS. There are dependencies among the various resources.

These services are used for various purposes, such as monitoring storage systems, scheduling jobs, processing events, and monitoring all the other services.

The following illustration shows the services and the dependencies among the various resources:



Configuring the OnCommand Core Package in a VCS environment

After installing the OnCommand Core Package, you have to configure the DataFabric Manager server in VCS. You must configure the DataFabric Manager server on the nodes sequentially and then bring the cluster services online.

1. Configure the DataFabric Manager server on the first node.
2. Configure the DataFabric Manager server on the second node.
3. Configure the DataFabric Manager server services for clustering, either manually or by running a script.

4. Bring the cluster services online.

Configuring DataFabric Manager server on the first node in VCS

You can configure the DataFabric Manager server on the first node by using the `dfm datastore setup` command.

Steps

1. Ensure that the first node owns all the cluster resources, such as Mount, NIC, and Volume.
2. Move all the shared data, such as database files and performance data files, to the shared storage system by entering the following command:

```
dfm datastore setup
```

Configuring DataFabric Manager server on the second node in VCS

You can configure the DataFabric Manager server on the second node by disabling the services and then by running the `dfm datastore setup -n` command.

Steps

1. Perform manual failover so that the second node owns all of the resources, such as disks and virtual IP addresses.
 - a. Open **Cluster Manager** by entering the following command at the command prompt:

```
hagui
```
 - b. Right-click the **service group**, click **Switch To**, and select the second cluster node for failover.
2. In **Cluster Administrator**, take the services offline on the second node:
 - a. Right-click the **DFM Sybase** service.
 - b. Select **Take offline**.

The other services are also taken offline.
3. Configure the node to use the shared data by entering the command:

```
dfm datastore setup -n
```

You must use the `-n` option when you configure the second node. This ensures that DataFabric Manager server uses the data that was copied during the configuration of the first node.

Adding the cluster services using a script

You can configure DataFabric Manager server in your cluster environment by running a configuration script. You can use the script to add the DataFabric Manager server cluster services to the cluster environment.

Steps

1. Log in to the node that owns cluster resources.
2. Move the DataFabric Manager server data to the shared data disk by entering the following command:

```
dfm datastore setup new_clusterdisk_directory
```

3. Stop DataFabric Manager server services by entering the following command:

```
dfm service stop
```

This ensures that DataFabric Manager server does not try to access the data disk to be moved to the secondary node.

4. Ensure that the DataFabric Manager server services do not start automatically by entering the following command:

```
dfm service enable -m
```

The option -m ensures that the DataFabric Manager server services do not start automatically.

5. Manually move the cluster group to the second node.
6. Verify that the secondary node owns the cluster resources.
7. Enter the following commands on the secondary node:

```
dfm service enable -m
```

```
dfm datastore setup -n drive_name
```

Note: You must ensure that you use the same drive letter for the secondary node as the first node. The -n option ensures that the data is not copied again to the shared data disk.

8. Access the directory at `C:\Program Files\NetApp\DataFabric Manager\DFM\examples` or `/opt/NTAPdfm/examples`, and `C:\Program Files(x64)\NetApp\DataFabric Manager\DFM\examples` for x64-bit platform.
9. Configure the DataFabric Manager server services in your cluster environment by running the following script:

```
dfmcluster_add_resources.pl -t cluster_type -g cluster_group -i cluster_ip_resource -n cluster_nameresource
```

Script options for configuring services in VCS

You have to configure the DataFabric Manager server to add its service resources to VCS. You can add the services manually, or by using the Perl configuration script.

The command to add services to the DataFabric Manager server is as follows:

```
perl dfmcluster_add_resources.pl -t cluster_type option ...
```

-t <i>cluster_type</i>	Cluster solution used for high availability. The possible values are <code>vcs</code> (default value on UNIX) and <code>mscs</code> .
-h <i>cluster_node1 cluster_node2</i>	Nodes used for cluster setup, separated by a space.
-g <i>cluster_group_name</i>	Name of the cluster service group to which the resources are added.
-e <i>nic_resource_name</i>	Name of the network interface card. This must be the same on both cluster nodes.
-i <i>cluster_ip_resource_name</i>	Name of the cluster IP resource.
-n <i>cluster_name_resource_name</i>	Host name of the cluster, which is mapped to the cluster virtual IP address.
-f <i>mount_point_resource_name</i>	Name of the mount resource.
-v <i>volume_resource_name</i>	Name of the volume resource that contains the filesystem represented by the mountpoint resource.
-d <i>disk_group_resource_name</i>	Name of the disk group that contains the volume represented by the volume resource.
-m <i>netmask</i>	Netmask associated with the cluster IP address.
-l <i>installation_directory</i>	OnCommand Core Package installation directory. The default value is <code>.</code>

Bringing DataFabric Manager server cluster services online in VCS

After you finish configuring the DataFabric Manager server on both nodes and adding the cluster services to the DataFabric Manager server, you must bring the services online.

Steps

1. Open **Cluster Manager** by entering the following command at the command prompt:
`hagui`
2. Right-click the **service group**.
3. Click **Online**.

4. Select the first cluster node.
5. Make sure the LUNs are visible to the host by entering the following command:

```
snapdrive config prepare luns -count n
```

You must ensure that the LUNs are visible to the host each time the server is rebooted.

Configuring DataFabric Manager server in VCS manually

You can manually configure the DataFabric Manager server using the VCS Application Configuration wizard.

Before you begin

If DataFabric Manager server is not installed at `/opt/NTAPdfm`, you should modify the path entries accordingly.

About this task

Configuring the DataFabric Manager server in VCS manually enables you to customize the cluster.

Steps

1. Run the **VCS Application Configuration** wizard by entering the following command on the node where VCS is set up:

```
hawizard
```

2. Select **Create Application Service Group** and click **Next**.
3. Enter **Service Group Name** and select the cluster from **Available Cluster** systems.
4. Click **Next**.
5. Enter the application details:
 - a. Specify `/usr/bin/dfm` as the path in **Start Program**.
 - b. Select **root** as user.
6. Click **Next**.
7. Select the processes that must be monitored by the DataFabric Manager server by entering the process monitor string.

See the table for the output values.

Process	Process monitor string
+ dfmmonitor	/opt/NTAPdfm/sbin/dfmmonitor
+ dfmserver	/opt/NTAPdfm/sbin/dfmserver

Process	Process monitor string
+ dfmscheduler	/opt/NTAPdfm/sbin/dfmscheduler
+ dfmeventd	/opt/NTAPdfm/sbin/dfmeventd start
+ database server	/opt/NTAPdfm/sbin/dbsrv10 @/opt/NTAPdfm/conf/sybase.conf
+ Apache server	/opt/NTAPdfm/sbin/httpd -f /opt/NTAPdfm/conf/httpd.conf
+Webui	/opt/NTAPdfm/java/bin/java /opt/NTAPdfm/jetty/start.jar /opt/NTAPdfm/conf/jetty.conf

8. Optionally, you can verify the process monitor string for each process by using the `ps -u root -o args` command.
9. Click **Next**.
10. Configure the mount resources and click **Next**.
11. Configure the IP and NIC resources and click **Next**.
12. Repeat the steps 5 to 11 for each DataFabric Manager server process.
13. Open the **Cluster Manager** to configure remaining cluster resources.
14. Select the service group **dfm_sg** in the left pane.
15. In the **Resource** tab, right-click **Resource View**.
16. Enter the details for each **Resource Type**.
On Linux, you should select only `LVMLogicalVolume` and `Mount` as the Resource Types. The `FSType` attribute should be set to `ext3` for `Mount`.
17. Select `NIC` from the **Resource Type** list.
18. Right-click the added resources and select **Link**.
19. Create a dependency tree and bring all the services online.
20. Ensure the DataFabric Manager server uses the cluster name (instead of the local system name) by entering the following command:

```
dfm option set localHostName=fqdn-of-cluster
```

The DataFabric Manager server uses the name of the local system to send e-mail alerts to administrators.

Configuring a host services in VCS

When you add a new host service in VCS, you must ensure that both nodes in a cluster pair have access to the keys folder. This ensures that when one node fails, the second node of the cluster starts functioning.

Steps

1. Copy the keys folder from one node to the other in the cluster pair at `installation_directory\conf`.
2. Open the **Cluster Manager** by entering the following command at the command prompt:
`hagui`
3. In the **Cluster Manager**, right-click the **service group**, click **Switch To**, and select the second cluster node for failover
4. Enter the following command on the second node to start using the new setting:
`dfm ssl service reload`
5. Launch the OnCommand console, verify that the host service status is Up in the **Host Services** tab.

Managing the DataFabric Manager server in a VCS environment

You can create and restore backups, set HTTPS options, and configure DataFabric Manager server to share data on the DataFabric Manager server cluster nodes.

Best practices to start and stop DataFabric Manager server services in VCS

After you set up DataFabric Manager server in VCS, do not use the `dfm service start` and `dfm service stop` commands, except where specifically indicated in installation and configuration procedures. You must perform all operations by using the Cluster Manager.

- You should disable the DataFabric Manager server init scripts after installation on both the cluster nodes.
- You should not change the service start-up type to Automatic in Service Control Manager on any of the nodes.

The DataFabric Manager server reactivates these scripts during an upgrade and then disables them again when the upgrade is complete.

Restoring the DataFabric Manager server database in VCS

You can restore the DataFabric Manager server database by disabling it through Cluster Manager and using the `dfm backup restore` command.

Steps

1. In **Cluster Manager**, disable DataFabric Manager server services by right-clicking the name of the service group and then clicking **Offline**.
2. Select the first cluster node in which the services are online.
3. Ensure that one of the nodes owns the cluster resources (such as the mountpoint) by completing the following steps:
 - a. Select the service group **dfm_sg**.
 - b. In the **Resources** tab, right-click **Resource View**.
 - c. Right-click the resource **Mount** and click **Online**.
4. Restore the database by entering the command in the node that owns the Mount resource:
`dfm backup restore`
5. In **Cluster Manager**, right-click the service group, then click **Online**, and select the first cluster node that is used for restore.

Configuring the DataFabric Manager server to use HTTPS in VCS

You can configure the DataFabric Manager server to use HTTPS on both the cluster nodes for a secured data transfer.

About this task

You must not take the `dfm-dbsrv` service offline.

Steps

1. In **Cluster Manager**, take the DataFabric Manager server services offline:
 - a. Right-click the service group **dfm-sg**, and click **Offline**.
 - b. Select the first cluster node where the services are online.
 - c. In the **Resources** tab, right-click **Resource View**.
 - d. Right-click the resource **dfm-dbsrv** and click **Online**.
2. Create an SSL certificate by entering the following command:
`dfm ssl server setup`

3. Copy the files `server.crt` and `server.key` to the second node before starting the services on that node.

The files are located in the `installation_directory/conf` folder.

4. Enable HTTPS by setting the following DataFabric Manager server option to yes:

```
dfm option set httpsEnabled=yes
```

5. Start the HTTP service by entering the following command:

```
dfm service start http
```

This re-creates the `httpd.conf` file with the changed options.

6. Stop all the services by entering the following command:

```
dfm service stop
```

Note: You must ensure that DataFabric Manager server services are offline. Otherwise, the HTTP service fails to be enabled on the other node, because the configuration is not complete.

7. In **Cluster Manager**, move the cluster group to the second node by using the option **Switch To**.

8. Log in to the second node in the cluster.

9. Copy the files `server.crt` and `server.key` created on the first node to the folder `install-dir/conf`.

10. Start the services and verify that they are operating by entering the following command:

```
dfm service start
```

This creates the `httpd.conf` file with the changed options.

11. Stop the services by entering the following command:

```
dfm service stop
```

12. In **Cluster Manager**, reenab the DataFabric Manager server services.

Changing the HTTP options in a VCS environment

You can change the HTTP options to enable HTTPS, or change the default HTTP and HTTPS port.

About this task

You must not take the `dfm-dbsrv` service offline.

Steps

1. In **Cluster Manager**, take the DataFabric Manager server services offline:
 - a. Right-click the service group, and click **Offline**.
 - b. Select the first cluster node where the services are online.

- c. In the **Resources** tab, right-click **Resource View**.
 - d. Right-click the resource **dfm-dbsrv** and click **Online**.
2. Set the required HTTP option by entering the following command:

```
dfm option set option-name=option-value
```

Example

```
dfm option set httpsPort=443
```

3. Restart the HTTP service by entering the following command:

```
dfm service start http
```

Attention: You must perform all cluster operations using Cluster Manager. Apart from installation and configuration procedures, you should not use the commands `dfm service start` and `dfm service stop`. These commands interfere with cluster operations.

4. Stop all the services by entering the following command:

```
dfm service stop
```

This re-creates the file `httpd.conf` with the changed options.

Note: You must ensure that DataFabric Manager server services are offline. Otherwise, the HTTP service fails to come up on the other node because the configuration is not complete.

5. In **Cluster Manager**, move the cluster group to the second node by using the option **Switch To**.
 6. Log in to the second node in the cluster.
 7. Start the services by entering the following command:
- ```
dfm service start
```
8. Stop the services by entering the following command:
- ```
dfm service stop
```
9. In **Cluster Manager**, bring the DataFabric Manager server services online.

Data shared by VCS cluster nodes

You must configure DataFabric Manager server nodes to access files from a shared disk. If each node uses its own local copy of files, any updates to files might not be accessible to the other nodes, after a failover.

The VCS cluster nodes share the following files:

<code>installation_directory/data</code>	Sybase database files
<code>installation_directory/perfdata</code>	Performance Advisor data files
<code>installation_directory/scriptplugins</code>	Installed script plug-ins and related files

<i>installation_directory/plugins</i>	Storage system configuration plug-ins
<i>installation_directory/reports</i>	Archived reports
<i>installation_directory/dataExport</i>	DataFabric Manager server and Performance Advisor data
<i>installation_directory/jetty</i>	Libraries and Web application files

Data that is not shared by VCS cluster nodes

To ensure that the same version is maintained in both the cluster nodes, executable and configuration files, license information, and so on are not shared by the DataFabric Manager server cluster nodes.

The VCS cluster nodes do not share the following files:

<i>installation_directory/bin</i>	Executable files
<i>installation_directory/conf</i>	Configuration files
<i>installation_directory/docs</i>	Third-party licenses
<i>installation_directory/examples</i>	Cluster configuration scripts, and other script files
<i>installation_directory/log</i>	Log files
<i>installation_directory/misc</i>	Configuration files
<i>installation_directory/sbin</i>	Third-party executables
<i>installation_directory/scripts</i>	Location of the <code>Sybase_install.sql</code> file
<i>installation_directory/src</i>	Storage system configuration plug-ins
<i>installation_directory/web/clients</i>	Performance Advisor clients
<i>installation_directory/web/com</i>	JAR files for applets
<i>installation_directory/web/help</i>	Help files
<i>installation_directory/web/man</i>	Manual (man) pages
<i>installation_directory/web/media</i>	Images used on Web interfaces
<i>installation_directory/web/scripts</i>	Java script files
<i>installation_directory/web/styles</i>	CSS style sheets

Uninstalling the OnCommand Core Package in a VCS environment

To uninstall OnCommand Core Package from a cluster, you must delete all the DataFabric Manager server services from the cluster nodes.

Steps

1. In **Cluster Manager**, delete all the DataFabric Manager server services:
 - a. Right-click the service group **dfm-sg**.
 - b. Select **Delete**.
2. Log in to one of the cluster nodes.
3. Uninstall by entering the one of the following command:
 - `rpm -e NTAPdfm`
 - `rpm --erase NTAPdfm`
4. Repeat the steps of logging in to each cluster node and running the uninstall command.

Upgrading the OnCommand Core Package in a VCS environment

When you upgrade to the OnCommand Core Package cluster nodes, you must ensure that all the nodes in the cluster are upgraded.

Before you begin

- The DataFabric Manager server installer from must be downloaded.

Steps

1. In **Cluster Manager**, take all DataFabric Manager server services offline by completing the following steps:
 - a. Right-click the service group, and then click **Offline**.
 - b. Select the first cluster node where the services are online.
2. Upgrade to the OnCommand Core Package on this node.
3. Stop all the DataFabric Manager server services by entering the following command:
`dfm service stop`

Attention: You must perform all cluster operations using Cluster Manager. Other than in installation and configuration procedures, do not use the commands `dfm service start` and `dfm service stop` unless advised to. These commands interfere with cluster operations.

4. Disable the automatic service start-up during reboot by entering the following command:
`dfm service enable -m`
5. Switch the mount resource and its dependents to the second node by selecting the option **Switch To**.
6. Ensure that the second node owns all the cluster resources.
7. Upgrade to the OnCommand Core Package installation on this node.
8. Stop all the DataFabric Manager server services by entering the following command:
`dfm service stop`
9. Disable the automatic service start-up during reboot by entering the following command:
`dfm service enable -m`
10. In **Cluster Manager**, make all DataFabric Manager server services online.
11. Select the **cluster service** group, and right-click **dfm-sg** group to remove the DataFabric Manager server services.
12. To re-create the cluster service group and to add the DFM Web UI service run the following command:
`dfmcluster_add_resources.pl -t cluster_type -g cluster_group -i cluster_ip_resource -n cluster_nameresource`

Related tasks

[Adding the cluster services using a script](#) on page 120

Copyright information

Copyright © 1994–2011 NetApp, Inc. All rights reserved. Printed in the U.S.A.

No part of this document covered by copyright may be reproduced in any form or by any means—graphic, electronic, or mechanical, including photocopying, recording, taping, or storage in an electronic retrieval system—without prior written permission of the copyright owner.

Software derived from copyrighted NetApp material is subject to the following license and disclaimer:

THIS SOFTWARE IS PROVIDED BY NETAPP "AS IS" AND WITHOUT ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, WHICH ARE HEREBY DISCLAIMED. IN NO EVENT SHALL NETAPP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

NetApp reserves the right to change any products described herein at any time, and without notice. NetApp assumes no responsibility or liability arising from the use of products described herein, except as expressly agreed to in writing by NetApp. The use or purchase of this product does not convey a license under any patent rights, trademark rights, or any other intellectual property rights of NetApp.

The product described in this manual may be protected by one or more U.S.A. patents, foreign patents, or pending applications.

RESTRICTED RIGHTS LEGEND: Use, duplication, or disclosure by the government is subject to restrictions as set forth in subparagraph (c)(1)(ii) of the Rights in Technical Data and Computer Software clause at DFARS 252.277-7103 (October 1988) and FAR 52-227-19 (June 1987).

Trademark information

NetApp, the NetApp logo, Network Appliance, the Network Appliance logo, Akorri, ApplianceWatch, ASUP, AutoSupport, BalancePoint, BalancePoint Predictor, Bycast, Campaign Express, ComplianceClock, Cryptainer, CryptoShred, Data ONTAP, DataFabric, DataFort, Decru, Decru DataFort, DenseStak, Engenio, Engenio logo, E-Stack, FAServer, FastStak, FilerView, FlexCache, FlexClone, FlexPod, FlexScale, FlexShare, FlexSuite, FlexVol, FPolicy, GetSuccessful, gFiler, Go further, faster, Imagine Virtually Anything, Lifetime Key Management, LockVault, Manage ONTAP, MetroCluster, MultiStore, NearStore, NetCache, NOW (NetApp on the Web), Onaro, OnCommand, ONTAPI, OpenKey, PerformanceStak, RAID-DP, ReplicatorX, SANscreen, SANshare, SANtricity, SecureAdmin, SecureShare, Select, Service Builder, Shadow Tape, Simplicity, Simulate ONTAP, SnapCopy, SnapDirector, SnapDrive, SnapFilter, SnapLock, SnapManager, SnapMigrator, SnapMirror, SnapMover, SnapProtect, SnapRestore, Snapshot, SnapSuite, SnapValidator, SnapVault, StorageGRID, StoreVault, the StoreVault logo, SyncMirror, Tech OnTap, The evolution of storage, Topio, vFiler, VFM, Virtual File Manager, VPolicy, WAFL, Web Filer, and XBB are trademarks or registered trademarks of NetApp, Inc. in the United States, other countries, or both.

IBM, the IBM logo, and ibm.com are trademarks or registered trademarks of International Business Machines Corporation in the United States, other countries, or both. A complete and current list of other IBM trademarks is available on the Web at www.ibm.com/legal/copytrade.shtml.

Apple is a registered trademark and QuickTime is a trademark of Apple, Inc. in the U.S.A. and/or other countries. Microsoft is a registered trademark and Windows Media is a trademark of Microsoft Corporation in the U.S.A. and/or other countries. RealAudio, RealNetworks, RealPlayer, RealSystem, RealText, and RealVideo are registered trademarks and RealMedia, RealProxy, and SureStream are trademarks of RealNetworks, Inc. in the U.S.A. and/or other countries.

All other brands or products are trademarks or registered trademarks of their respective holders and should be treated as such.

NetApp, Inc. is a licensee of the CompactFlash and CF Logo trademarks.

NetApp, Inc. NetCache is certified RealSystem compatible.

How to send your comments

You can help us to improve the quality of our documentation by sending us your feedback.

Your feedback is important in helping us to provide the most accurate and high-quality information. If you have suggestions for improving this document, send us your comments by e-mail to doccomments@netapp.com. To help us direct your comments to the correct division, include in the subject line the product name, version, and operating system.

You can also contact us in the following ways:

- NetApp, Inc., 495 East Java Drive, Sunnyvale, CA 94089
- Telephone: +1 (408) 822-6000
- Fax: +1 (408) 822-4501
- Support Telephone: +1 (888) 4-NETAPP

Index

- ## A
- associating storage systems 73
 - authentication
 - certificate-based 83
 - certificate-based, disabling 86
 - certificate-based, generating a key and certificate 84
- ## C
- certificate details
 - displaying DataFabric Manager server 86
 - certificates
 - about SSL 83
 - authentication using 83
 - displaying details from truststore 85
 - list in a truststore 84
 - management of 85
 - management of cloud service client 83
 - management of host services client 86
 - migrating manually 87
 - removing from the truststore 84
 - certificates, installing 84
 - changing user credentials 109
 - checklist
 - configuration 9, 10
 - installation 9, 10
 - cloud service client
 - certificate management 83
 - cmdlets
 - installing 50
 - configuration checklist 9, 10
 - configuring
 - DataFabric Manager server in MSCS 121
 - DataFabric Manager server in VCS 144
 - Standard edition 65
 - configuring Express edition
 - configuring 61
 - Express edition 61
 - connection issues 105
 - Core Package
 - installing on Windows 42
 - See also OnCommand Core Package
 - See also OnCommand Core Package
 - core package cmdlets
 - installing 50
 - credentials
 - storage systems 75
 - cursor displays in multiple locations 105
- ## D
- dashboard panel, cursor displays in multiple locations 105
 - DataFabric Manager server
 - adding cluster services using scripts 120, 143
 - Express edition functionality 20
 - Standard edition functionality 20
 - verifying host service registration 66
 - with Express and Standard editions 19
 - DataFabric Manager server certificate
 - displaying details 86
 - DataFabric Manager server in MSCS
 - bringing services online 121, 127
 - cluster service resources 118
 - configuring 121
 - configuring cluster services 125
 - configuring HTTP and HTTPS 130
 - configuring HTTPS 129
 - guidelines to start and stop services 128
 - monitoring 131
 - restoring the database 128
 - shared data by cluster nodes 131
 - unshared data by cluster nodes 132
 - DataFabric Manager server in VCS
 - bringing services online 144
 - cluster service resources 141
 - configuring 144
 - configuring first node 142
 - configuring HTTP and HTTPS 149
 - configuring HTTPS 148
 - configuring manually 145
 - configuring second node 142
 - guidelines to start and stop services 147
 - restoring the database 148
 - shared data by cluster nodes 150
 - unshared data by cluster nodes 151
 - DataFabric Manager truststore 83
 - See also truststore
 - disable certificate-based authentication 86
 - duplicate UUID 108

E

- error messages
 - Access is denied 109
 - Address already in use 105
 - Could not find any storage mapping for application object 107
 - Operation timed out 108
 - Primary key for table is not unique 108
 - There is a problem with this Windows Installer package 105

ESX timeout 108

- Express edition
 - description 19

H

- hardware requirements
 - Linux workstation or server 30, 31
 - Windows Server 2003 29, 30
 - Windows Server 2008 27–29
- Host Package 16–18
 - See also OnCommand Host Package
- host service fails to connect to DataFabric Manager server 110
- host service is unresponsive 110
- host services
 - adding 71
 - associating with vCenter Server 69
 - authorizing access to storage 68
 - communication with plug-ins 72
 - configuring in MSCS 127
 - configuring in VCS 147
 - overview 12, 13
 - registering 71
 - registering with vCenter Server 69
 - verifying communication with DataFabric Manager server 109
 - verifying server registration 66
- host services client
 - certificate management 86

I

- icon does not appear in the vSphere Client 108
- installation checklist 9, 10
- installation of OnCommand Core Package 41
- installation of OnCommand Host Package 51, 52
- installation of OnCommand Host Package for Hyper-V 55
- installing
 - core package cmdlets 50
 - OnCommand Core Package in MSCS 116
 - OnCommand Core Package in VCS 139

K

- key
 - migrating manually 87
- key and certificate, generating 84
- keys
 - management of 85
- keys folder
 - sharing between nodes in a cluster 127, 147

L

- Linux workstation or server
 - hardware requirements 30, 31
- login credentials 75

M

- Management Console
 - installing 49
- manual migration
 - DataFabric Manager server certificates 87
- Microsoft Cluster Server (MSCS) 113
- MSCS (Microsoft Cluster Server) 113
- MSCS environment
 - configuring 115
 - configuring a host service in 127
 - setup example 118

N

- NDMP credentials 75

O

- OnCommand Core Package
 - downloading software 41
- OnCommand
 - architecture 11
 - browser requirements 23
 - components 9
 - Express edition 19
 - Express edition configuration 61
 - installation process 10
 - license requirements 25
 - Standard edition 19
 - Standard edition configuration 65
 - troubleshooting 105
- OnCommand Core Package

- configuring 61
- contents 14
- functionality 14
- hardware and software requirements 26
- installed components 14
- installing 41
- installing on Linux 44
- installing with a script 45
- required ports 32
- required software 26
- scripted install options on Linux 47
- scripted install options on Windows 46
- unattended install 45
- uninstalling 101
- uninstalling on Linux 102
- uninstalling on Windows 101
- upgrading 89
- upgrading on Linux 90
- upgrading on Windows 89
- OnCommand Core Package in MSCS
 - configuration 119
 - configuration limitations 114
 - installation 115
 - installation prerequisites 113
 - installing 116
 - preparing 113
 - supported configurations 114
 - uninstalling 133
 - upgrading 133
- OnCommand Core Package in VCS
 - configuration 141
 - configuration limitations 138
 - installation 139
 - installation prerequisites 137
 - installing 139
 - preparing 137
 - supported configurations 138
 - uninstalling 152
 - upgrading 152
- OnCommand Host Package
 - configuring 61
 - contents 16
 - downloading software 51
 - functionality in a Hyper-V environment 18
 - functionality in a VMware environment 17
 - hardware and software requirements 33
 - hardware requirements 34
 - installation 51
 - installed components in a Hyper-V environment 17
 - installed components in a VMware environment 16

- installing 52
- installing with a script 57
- operating system requirements 34, 36
- regenerating an SSL certificate 81
- registering with vCenter Server 77
- required ports 38
- required software 35–37
- scripted install options for Hyper-V 59
- scripted install options for VMware 58
- unattended install 57
- uninstalling 101
- uninstalling in a Hyper-V environment 103
- uninstalling in a VMware environment 102
- upgrading 89
- upgrading in a Hyper-V environment 94
- upgrading in a VMware environment 91
- OnCommand Host Package for Hyper-V
 - installing 55
- outbound ports, insufficient 105

P

- plug-in container for Firefox stops working 106
- plug-ins
 - communication with host service 72
- ports, insufficient outbound 105

R

- Related Objects list
 - no physical servers displayed 106
- required ports
 - OnCommand Core Package 32
 - OnCommand Host Package 38
- restore fails 108

S

- SnapDrive for Windows
 - updating user credentials 80
- SnapManager for Hyper-V
 - manually transitioning dataset information 79
- Standard edition
 - configuring 65
 - description 19
- storage mapping error 106, 107
- storage systems
 - associating with a host service 73
 - authorizing host service access 68

- determining domain or workgroup 79
- login credentials 75
- NDMP credentials 75

T

- transitioning legacy Hyper-V dataset information manually 79
- truststore
 - certificate list 84
 - certificates, removing 84
 - contents of 83
 - displaying certificate details from 85
 - installing certificates 84
 - migrating manually 87

U

- uninstalling
 - OnCommand Core Package in MSCS 133
 - OnCommand Core Package in VCS 152
- upgrade of OnCommand Host Package 91, 94
- upgrading
 - cmdlets 50
 - OnCommand Core Package in MSCS 133

- OnCommand Core Package in VCS 152
- using FC LUN
 - no physical servers displayed 107

V

- vCenter Server
 - associating a host service 69
 - registering a host service 69
- vCenter Server timeout 108
- VCS (Veritas Cluster Server (VCS)) 137
- VCS environment
 - configuring 139
 - configuring a host service in 147
- Veritas Cluster Server (VCS) 137

W

- Windows Firewall
 - adding port exceptions 80
- Windows Installer service error 105
- Windows Server 2003
 - hardware requirements 29, 30
- Windows Server 2008
 - hardware requirements 27–29